Insert Dealer Logo



Date:		Sales Person:		
End User: Stock Order Work Order Number:		Customer PO: Request Delivery Date:		
o/a Height o/a Length Axle spread King pin setting King pin height Wall height RTAC compliant	9' 6" with a 50" Fifth Wheel 37' 60" 15", 84" Turning Clearance 50" 48" Yes	Picture of End Dump		
Box Front - 10 gauge steel, Box Sides - 12 gauge steel to Top Rail - 7X5 inch steel tu Box Floor - 3/16 inch abras Tailgate - 10 gauge steel fo Suspension - Intraax AA250 Axles - 77 inch track, 25,00 Wheels - Unimount 10 hole	and capacity h, 5 stage, 265 inch stroke, head lift telescoping hydround corners, formed ribs upper half with full length horizontal rib, 10 gauge be top rail live resistant 200 steel, edges rounded 90 degrees of the control of the control of the control of the control, 11Rx22.5 radial tires / Firestone T 819 of manual overide	steel lower half with no vertical seams up 9 inches on each side ain holes		

CATEGORY		Weight	PART NUMBER
BOX POSITION Asphalt - 18" overhang BODY BODY		16380	lbs A1360B35A360
1/4" AR 200 on floor 4 mm Hardox 450 on floor 4 mm Hardox 450 on walls Additional step passenger side; 2 outside & 1 inside			
TAILGATE Watertight tailgate with 4 turnbuckles Sealed tailgate with 2 turnbuckles Hydraulic operated tailgate. Includes 12" Planks			
8in high lift tail gate Turnbuckles on tailgate - specify location Quantity BOARDS			
x 2" x 6" Wood planks 2" x 12" Wood planks Std Box 2" x 6" Steel planks 3/16" wall 2" x 12" Steel planks 3/16" wall, (stacked 2" x 6")			A1XEA247600
<u>TARPS</u>	Tarp colour - If colour is not specified tarp will be black		
Mesh - cable style - 12" hoops with aluminum hood Mesh - cable style - 18" hoops with aluminum hood X Vinyl - Cable style - 12" hoops Vinyl - Cable style - 18" hoops			###
## #REF! ## #REF!	#REF!		### ###

CATEGORY			Weight PART NUMBER			
	Work Order #		•			
	LIG 3 Hole aluminum light box - LED Back up light with 3 hole light box -					
	Additional lights on rub rail - LED SUSPE	Lift Location				
	1 axle auto deploy lift kit 2 axle auto deploy lift kit (simultane TIRES AN					
Х	 11R22.5 Tires 11R24.5 Tires				A0V4644040	
	Cooper Road Master RM 230 HH I wheels unless otherwise noted				A9X1611012	
	Steel Aluminum look-alike Aluminum Machined					
1	Aluminum Polished MUDI	FLAPS				
	Mud flaps, below rear bumper	fournancian				
	Mud flaps, box mounted in front of Mud flaps, bank of 4 in front of sus					
	Mud flaps, frame mounted, 2 in fro	ont of suspension				
	Mud flaps, frame mounted, 4 in fro 2 Removable mud flaps, at rear of t					
	z Removable mud haps, at rear of t					
	Aluminum front frame cover	al an aluticana at U.V	KNAc			
	Hubodometer for 22.5 tire (installe Hubodometer for 24.5 tire (installe	KMs KMs				
	Two speed crank down legs	a on anvers side,				
	Vibrator, 12 volt DC3500 Electric					
	Spare tire carrier under frame					
	Remote grease system for Tri Axle 6 CHAIN HANGERS - U BOLT 3/4X5)	X17 RD				
	Gravel shed plate at rear channel a					
	Manitoba Safety Inspection					
	PDI	ODTIONS				
	QUOTED	<u>OPTIONS</u>				
	Std. Paint for Box	Std. Paint for Frame				
Х	White SW 1971					
		X Black SW 14808				
	Black SW 14808	BOX COLOUR	PAINT CODE			
	Box colour	white	I AINT CODE			
	Frame colour	black				
	Board colour	black				
	Stripe					
	Tier					
				17520.02 LBS		
	NOTES:					
		-				
		Purchaser's Signature		Date		