		X QUOTE				
		Version #37 August 29 2022				
Date:		Sales Person:				
End User:		Customer PO:				
Work Order Number:		Request Delivery Date:				
ri Axle CG Hopper						
o/a Height o/a Length	10' 1" with 12" Planks 37'					
Axle spread	60"					
King pin setting	15"	Distance of Find Duman				
King pin height	48"	Picture of End Dump				
RTAC compliant	Yes					
Base spec / to base mod	el					

Body Capacity with 12" boards - 27 3/4 cubic yard capacity Cylinders - 5" bore 20" stroke air cylinder Front & Back Slopes - 10 gauge with formed ribs

Wheels - Unimount 10 hole wheels with light weight hubs and drums, 8.25x22.5

Box Sides - 12 gauge steel with horizontal rib Top Rail - 4" x 4" steel tube top rail

Axles - 77 inch track, 25,000 pound capacity per axle

Tires - BF Goodrich, ST576, 11Rx22.5 radial tires

Suspension - HT230TB

ORDER

MARNE'S

ABS 2 sensor, 1 module						
CATEGORY		Weight	PART NUMBER			
SUSPENSION Air Ride 1 axle auto deploy lift kit 2 axle auto deploy lift kit (simultaneous)	Lift Location		A2C37A360			
X 2" x 6" Wood planks 2" x 12" Wood planks	Tarp Colour - If		A2XHA066800			
<u>TARPS</u>	colour is not specified tarp will be black					
Mesh - cable style - 12" hoops Vinyl - Cable style - 12" hoops						
Electric tarp kit for cable style Dura Flip Mesh Tarp						
Dura Flip Mesh Electric Tarp						
Incandesent Lights LIGHT X LED lights			A2XLED			
TIRES AND RIMS 11R22.5 Tires X 11R24.5 Tires			A 0 V 4 C 4 4 O 4 2			
X Cooper Road Master RM 230 HH Steel wheels unless otherwise noted			A9X1611012			
Steel Aluminum look-alike Aluminum Machined Aluminum Polished						

CATEGORY			Weight	PART NUMBER	
	Work Order #				
	<u>MUDFLAF</u>	<u> </u>	_		
	Mud flaps, bank of 2 off bumper				
	Mud Flaps, bank of 4 in front of susp				
	OPTIONS	<u> </u>			
	Backup Alarm Hubodometer for 22.5 tire (installed	on drivers side)	KMs		
	Hubodometer for 24.5 tire (installed	KMs			
	Cam Closures for Tri Axle				
=	Push Block bolt on style				
	Individual Gate Controls				
	Shock Straps for Tri Axle				
	Remote grease system for Tri Axle				
	Vibrator, 12 volt DC3500 Electric				
	Ladder, front mounted X gate hoppe				
	Manitoba Safety Inspection				
	PDI	TIONS			
	QUOTED OPT	IONS			
	Std. Paint for Box	Std. Paint for Boards			
Х	White CLR 21971	x			
	Silver CLR 17752	X Black CLR 14808			
	Black CLR 14808				
		<u>COLOUR</u>	PAINT CODE		
	Colour	51.4.61/			
	Board colour	BLACK			
	Stripe				
	Tier				
				19879.02	IBS
				13073.02	255
	NOTES:				
		Date			