



Platinum Trailers
226-301-4048
2302 Rd 125
St. Marys ON N4X 1C9
Canada

DEALER

Maxim Truck and Trailer
1860 Brookside Blvd
Winnipeg R4B0A7
Phone: (204-790-6599
Sales Manager: Andre Du Toit

CUSTOMER

MAXIM TRUCK AND TRAILER
Attn: Andre Du Toit
Email: adutoit@maximtruckandtrailer.com
Phone: 204-790-6599
1860 Brookside Blvd
WINNIPEG Manitoba R4B0A7
Canada

DEALER QUOTE # Q260827000-D

Quotation Date:
08/31/2026

Expiration:
09/30/2026

Salesperson:
[Salesperson]

Trailer Configuration



Description	Quantity	Unit Price	Disc.	Amount
PLATINUM SUPER B-TRAIN				
STANDARD EQUIPED WITH:				
King pin 24" standard Lead , 18" Standard Pup				
Slopes 30" minimum angle on slopes				
Lead water level 1305 cu ft. Pup 1347 cu ft. Total 2652 cu ft.				
Lead heaped 1435 cu ft. Pup 1482 cu ft. Total 2917 cu ft.				
Jost Low Lube fifth wheel coupler				
Jost Aluminum landing gear 5 Year Warranty (Aluminum Bracing and Supports)				
Long mudflaps (4) mounted at landing gear lead and pup				
Walls & Slopes:				
Fully Welded Vertical Reinforced Hollow Core Aluminum Boards				
Lead And Pup Vented Through Midwall				
Not Polished				
FRAMES:				
Fully Fabricated components				
Crossmembers and mainframe				
Hot dipped galvanized				
Tow hooks at rear of pup				
CATWALK and LADDERS				
Aluminum ladders with extra wide safety grip rungs				
At Front and Rear of Lead and Pup trailer				
Access steps at rear of Lead :				
Fabricated aluminum steps and platform with safety grip perforated decking including grab handles to access platform securely				
Decking extended over fenders to provide extra wide secure platform				
Interior offset hopper steps to ensure safe entrance and minimize material hangup				
Steps on both sides of hopper divider ergonomically spaced				
Bluetooth onboard scale, to read weigh on your phone for lead and pup				
Lead control box mounted near landing gear drivers side with sight window and backlighting showing liquid filled suspension gauge,				
Weatherproof light switch and air suspension dump inside box				
Auxiliary box mounted at rear of lead trailer with sight window and backlighting showing liquid filled suspension gauge with M style quick coupler located inside of box				
Pup control box mounted near landing gear drivers side including air suspension dump,				
Liquid filled suspension gauge and weatherproof light switch				
PLATINUM SUPER B-TRAIN	1.00 Units			

Trailer Dimensions & Options

LEAD Length = 29' 6"
PUP Length = 30'
Exterior Width = 102"
Interior Width = 98"

82 Inch Sidewall 1.00 Units

Overall Height 142" with 82" wall
Lead water level 1305 cu ft. Pup 1347 cu ft. Total 2652 cu ft.
Lead heaped 1435 cu ft. Pup 1482 cu ft. Total 2917 cu ft.

Tarps

3 inch aluminum roof bows;
Aluminum end caps

MICHELS ELECTRIC SIDE ROLL
TARP SYSTEM 1.00 Units

Electric side roll tarp system inclusive of, one remote with charger, electric motors, trailer mounted controller (1 per trailer), black canvas, aluminum endcaps, aluminum roof bows

Hopper & Chute configuration

stainless steel chute shafts and U joints;
stainless steel chute with stainless rack and pinion
2 piece polly bearings
Polly sliders for chute to open on
Hammer hit brackets on hoppers(1 per chute opener)

Hopper Ground Clearance - Standard 22.625" with 11R22.5 tires	1.00 Units
--	------------

Chute Size - Standard 24Wx24L	1.00 Units
-------------------------------	------------

Chute Opening Direction for LEAD and PUP - Front Chute Opens Towards Front (lead & pup)	1.00 Units
---	------------

Chute Opening Direction for LEAD and PUP - Rear Chute Opens Towards Rear (lead & pup)	1.00 Units
---	------------

Chute Locks, Openers - Electric Chute Opener Michels, passenger side	1.00 Units
---	------------

Hammer Hits Mounted at opener locations

Chute Locks, Openers - Manual Opener opposite To Electric opener	1.00 Units
---	------------

Hammer Hits Mounted at opener locations

Chute Locks, Openers - Hardwired remote buttons mounted opposite side of electric chute opener	1.00 Units
--	------------

Hammer Hits Mounted at opener locations

Air System

WABCO ABS and Sealco valves
Aluminum Air tanks with rubber isolators and stainless hardware

Axle Spacing

Lead 61-61
Pup 50

Axle/Brake/Hubs

Standard Axle/ Hub 1.00 Units

25000 Hendrickson Intraax AAT
Wide pivot connection
77.5 inch track
Cast iron hubs with long studs
Semi fluid filled hubs Chevron Delo
Wheel seal Federal Mogul
WABCO ABS and Sealco valves
All axles come with parallel spindles as standard equipment

Hendrickson Centrifuse Drum brake

Hendrickson long stroke brake chambers
Short enclosed S cams
Long life brake lining

Rims/Tires

Rovello Ram 3 16ply 11R22.5 Tires
with 8.25R22.5 Alu Mac Rim 1.00 Units

Standard

Fenders

Aluminum fender on front of lead trailer with stainless hardware and aluminum brackets
No fender on front of pup trailer

Stainless fenders class 8 16GA 1.00 Units

Lighting & Electrical

Seven wire connector on trailer front,
Grote Ultra Blue Wiring Harness
LED Lamps
Grote wiring harness fully sealed,
Standard one Interior and one unload light per hopper,
Bluetooth load scale system,

12 extra sidelight per trailer 1.00 Units

Lead Trailer

Air Control box equipped with air ride valve, suspension gauge, electronic weigh system, sight window and light at front of trailer

Air Control box rear with suspension gauge, air chuck, sight glass and light located at rear bridge

Quick dump suspension feature, no need to dump air while unloading

Lighting and indicator lights same as at as pup

Walk up Steps on both sides of trailer

Brake pot protection mud flaps 1.00 Units

Pup Trailer

Air Control box equipped with air ride valve, suspension gauge, electronic weigh system, sight window and light at front of trailer

Quick dump suspension feature, no need to dump air while unloading

Tow rings on rear of steel frame

Brake pot protection mud flaps 1.00 Units

Miscellaneous

Customer Requests 1.00 Units

- 1) Grab Handles at top of ladders
- 2) Mudflaps at rear of plastic fenders
- 3) Full width flaps behind rear axle on Pup
- 4) Wireless Controller with tarp & Chute openers programed
- 5) Hardwired control box at front of lead & pup for tarp operation
- 6) Chute traps operate on sealed rollers