		QUOTE		
			Version # 33 April 28 2022	
Date: End User:		Sales Person:		
		Customer PO:		
Work Order Number:		Request Delivery Date:		
END DUMP TRIAXLE TUB ST	YLE			
o/a Height	9' 6" with a 50" Fifth Wheel			
o/a Length	37'			
Axle spread	60"			
King pin setting	15", 84" Turning Clearance			
King pin height	50"	Picture o	of End Dump	
Wall height	50"		·	
RTAC compliant	Yes			
Base spec / to base model				

ORDER

ARNE'S

CATEGORY		Weight	PART NUMBER
DOV DOCITION			
BOX POSITION Asphalt - 18" overhang Gravel - 2" overhang		16380	lbs A1360TUB35A360
TAILGATE		10300	192 VI20010B22W200
8" High Lift Tailgate			
Hydraulic High Lift Tailgate with 12" Planks			
Watertight tailgate with 4 turnbuckles Tub Box			
Sealed Tailgate 2 locks on the bottom			
Sealed Tailgate 2 locks on the sides			
Tailgate - 2 locks bottom			
Tailgate - 2 locks sides			
BOARDS			
X 2" x 6" Wood planks Tub Box			A4XEA200302
2" x 12" Wood planks Tub Box			
2" x 6" Steel planks 3/16" wall			
2" x 12" Steel planks 3/16" wall, (stacked 2" x 6")			
Z X 12 Steel plants 3/10 Wall, (Stacked 2 X 0)	Tarp Colour - If		
	colour is not		
<u>TARPS</u>	specified tarp will		
	be black		
Mesh - cable style - 12" hoops with aluminum hood			
Mesh - cable style - 18" hoops with aluminum hood			
X Vinyl - Cable style - 12" hoops			###
Vinyl - Cable style - 18" hoops			
Electric tarp kit for cable style			
Electric Tarp Conduit			
LIGHT			
3 Hole aluminum light box - LED			
Back up light with 3 hole light box - LED			
SUSPENSION	Lift Location		
1 axle auto deploy lift kit			
2 axle auto deploy lift kit (simultaneous)			

Body Capacity - 31 cubic yard capacity

Box Sides & Floor - 4 mm Hardox, AR450

Ladder - formed steel welded to the box

Box Front - 3/16" 50000 Yield Steel

Top Rail - Formed Steel Channel

ABS 2 sensor, 1 mondule

LED Lights

Hoist - Custom Hoist, 8 inch, 5 stage, 265 inch stroke, head lift

Tailgate - 3/16 gauge formed one piece, plated spreader chains

Axles - 77 inch track, 25,000 pound capacity per axle

Tires - BF Goodrich, ST576, 11Rx22.5 radial tires Tailgate Latch - air trip with manaul overide

Suspension - Intraax AA250 air ride, 25,000 pound capacity per suspension

Wheels - Unimount 10 hole wheels with light weight hubs and drums, 8.25x22.5

CATEGORY		Weight	PART NUMBER	
Work Order #				
TIRES AND	RIMS	_		
11R22.5 Tires				
X 11R24.5 Tires			A0V4C44042	
Cooper Road Master RM 230 HH			A9X1611012	
Steel wheels unless otherwise noted				
Steel Aluminum look-alike				
Aluminum Machined				
Aluminum Polished				
MUDFLA	DS			
Mud flaps, below rear bumper	<u> </u>			
Mud flaps, bank of 4 in front of suspe				
Mud flaps, frame mounted, 2 in front				
Mud flaps, frame mounted, 4 in front	of landing gear			
2 Removable mud flaps, at rear of tra				
<u>OPTION</u>	<u>IS</u>			
Aluminum Trim Package	ntad Fandara			
Aluminum Trim Package for Box Mou	KMs			
Hubodometer for 22.5 tire (installed a Hubodometer for 24.5 tire for 24.5 tire (installed a Hubodometer for 24.5 tire	KMs			
Two speed crank down legs				
Vibrator, 12 volt DC3500 Electric				
Spare tire carrier under frame				
Remote grease system for Tri Axle				
Aluminum Front Cover Plate				
Box Mounted Fenders with Mud Flap	S			
Black Plastic Fenders				
Front Placard				
Rear Placard	_			
Hardox 450 - 5 piece 4mm Front Line Hardox 450 - 5 piece 1/4" Front Liner				
Hardox 450 - 5 piece 1/4 Front Emer				
Hardox 450 - 1/4" - Gate Liner				
Ladder, front mounted				
CHAIN HANGERS - U BOLT 3/4X5X17 I	RD			
Manitoba Safety Inspection				
PDI				
QUOTED OP	TIONS			
 				
Std. Paint Colour for Box	Std. Paint Colour frame			
White CLR 21971				
X Silver CLR 17752	X Black CLR 14808			
Black CLR 14808				
_	<u>COLOUR</u>	PAINT CODE	1	
Box colour		ļ		
Frame colour	hii-			
Board colour Stripe	black black			
Stripe Tier	DIACK	-		
Hel		1	I	
			0	LBS
		-		
NOTES:				
		[Date	