## Insert Dealer Logo

ORDER	<b>ARNE'S</b>
	WARNES
QUOTE	

0

		Version 42 November 3 2025
Date:		Sales Person:
End User:		Customer PO:
Work Order Number:		Request Delivery Date:
SIDE DUMP V Max II Tri	Axle Lead	
o/a Height	9' 10"	
o/a Length	35' 10"	
Axle spread	60"	
King pin setting	15" is Std	
King pin height	50"	Picture of End Dump
Wall height	54"	·
RTAC compliant	Yes	
Base spec / to base n	nodel	

Top Rail - Formed top rail Suspension -Hendrickson Intraax 250, 25,000 pound capacity per suspension Axles - 77 inch track, 25,000 pound capacity per axle Wheels - Unimount 10 hole wheels with light weight hubs and drums, 8.25x22.5 Tires - BF Goodrich, Cross Control, 11Rx22.5 radial tires / Firestone T 819 ABS 2 sensor, 1 module Steps - between 1st and 2nd axles Aluminum 1/2 round fenders Liners cannot be installed on any side dump boxes **CATEGORY** Weight **PART NUMBER BOX POSITION** X Std Box 16380 lbs Tarp Colour - If colour is **TARPS** not specified tarp will be black Electric Side Kicker Tarp BLACK MESH with aluminum arms &

roll tube Electric Side Kicker Tarp BLACK VINYL with aluminum arms & roll tube AR-0900100 Wire for electric tarp to rear unit, lead units only **A5XWIREELECTARP** Tarp Hood Side Kicker Tarp Hood / Cap Over Tarp Caps Between Tarp Caps **LIGHT** A5XKIT201VM2LD x LED lights Incandescent Lights SUSPENSION

1 axle auto deploy lift kit

2 axle auto deploy lift in Lift Location 2 axle auto deploy lift kit (simultaneous) A5XKITEA3010A-D **TIRES AND RIMS** 11R22.5 Tires 11R24.5 Tires Cooper Road Master RM 230 HH A9X1611006 Steel wheels unless otherwise noted A9X16029396 Steel Aluminum look-alike Aluminum Polished Finish **MUDFLAPS** 

Mud flaps, frame mounted, 2 in front of suspension

Body Capacity - 20 cubic yard capacity Box Front & Wall - Hardox 450, 1/8" Box Sides & Floor - Hardox 450, 1/8"

	CATE	GORY		Weight	PART NUMBER
	Work Order #				
			<b>_</b>		
	OF	PTIONS			
Х	22ft Box in Lieu of a 20ft - up	ocharge			
Х	Two speed crank down legs V	Max II option			A5XSA072200
	Hubodometer for 22.5 tire (in	stalled on drivers side)	KMs		
	Hubodometer for 24.5 tire (in	stalled on drivers side)	KMs		
	Vibrator, 12 volt DC3500				
	Backup Alarm				
	CHAIN HANGERS - U BOLT 3/4				
	Remote grease system for Tri	Axle			40746010000
	Black Plastic Fenders		b		A9X46010000
	Calcium Tank		ນ		
	Stripe Manitoba Safety Inspection				
$\vdash$	PDI				
		D OPTIONS			
Х	sheete	d in corners			
	Sheete	a in conficis			
	Std. Box Colour	Std. Frame Colour			
	White CLR 21971	Dis als CLD 14000			
	Silver CLR 17752 Black CLR 14808	X Black CLR 14808			
Х	Black CLN 14808	<b>BOX COLOUR</b>	PAINT CODE		
	Box colour	Black		1	
	Frame colour	Black		1	
	Board colour			1	
	Stripe	Red	SW0567	1	
	Tier			1	
				•	
					LBS
					KG
	NOTES				
	NOTES:				
		-			
		-			
		Dumaha anda Ci			D-4-
		Purchaser's Signature			Date

Insert	$D^{\alpha}$	lor I	$1 \sim \alpha \sim$
msert	Dea	ıeı	しいをい

ABS 2 sensor, 1 module Steps - between 1st and 2nd axles

Aluminum 1/2 Round Fenders
Liners cannot be installed on any side dump boxes

ORDER	<b>ARNE'S</b>
QUOTE	Version 39 -August 22 2025
	Version 39 -August 22 2023
ery Date:	
Diet	ure of End Dumn
	QUOTE

		QUOTE	
Data		Calaa Barraan	Version 39 -August 22 2025
Date:		Sales Person:	
End User:		Customer PO:	
Work Order Number:		Request Delivery Date:	
SIDE DUMP V Max II TDM Axle	Rear		
o/a Height	9' 5"		
o/a Length	28' 6"		
Axle spread	50"		
King pin setting	15" is Std		
King pin height	46"	Pictur	e of End Dump
Wall height	54"		·
RTAC compliant	Yes		
Base spec / to base mo	odel		
Body Capacity - 20 cubic ya			
Box Front & Rear Wall- Ha			
Box Sides & Floor - Hardox	450, 1/8"		
Top Rail - Formed top rail	, .		
Suspension - Hendrickson	Intraax 250, 25,000 pounds capacity per suspension		
Axles - 77 inch track, 25,00			
	e wheels with light weight hubs and drums, 8.25x22.5		
	Control, 11Rx22.5 radial tires / Firestone T 819		
ABS 2 sensor 1 module	,		

CATEGORY		Weight	PART NUMBER
BOX POSITION  X V Max II TDM Axle Rear		16380 lb	os A5XSC032300
TARPS  Electric Side Kicker Tarp BLACK MESH with aluminum arms & roll	Tarp Colour - If colour is not specified tarp will be black		
tube    X   Electric Side Kicker Tarp BLACK VINYL with aluminum arms & roll tube   X   Side Kicker Tarp Hood / Cap   X   Over Tarp Caps   Between Tarp Caps   LIGHT   Incandescent Lights   X   LED lights			A5X0900100 Tarp Hood A5XKIT201VM2LD
SUSPENSION  1 axle auto deploy lift kit	Lift Location		
TIRES AND RIMS  x 11R22.5 Tires 11R24.5 Tires x Cooper Road Master RM 230 Steel wheels unless otherwise noted			A9X1611006
Steel Aluminum look-alike Aluminum Polished Finish			
MUDFLAPS  Mud flaps, frame mounted, 2 in front of suspension x Dealer Logo Rear Mud flaps (2) 24 x 30			misc

CATEGOR	Υ		Weight	PART NUMBER
Work Order #				<u> </u>
X 22ft Box in lieu of 20ft - Upcharge X Two speed crank down legs V Max II Hubodometer for 22.5 tire (installed Hubodometer for 24.5 tire (installed Vibrator, 12 volt DC3500 Backup Alarm	option on drivers side)	KMs KMs		A5XSA072200
CHAIN HANGERS - U BOLT 3/4X5X17 Remote grease system for TDM Axle  X Black Plastic Fenders  Stripe Manitoba Safety Inspection PDI  QUOTED OF	•			A9X46010000
x sheeted in c	orners			
Std. Box Colour White CLR 21971 Silver CLR 17752 X Black CLR 14808  Box colour Frame colour Board colour Stripe Tier	Std. Frame Colour  Black CLR 14808  BOX COLOUR  Black  Black  Black  Red	PAINT CODE SW00567		
NOTES:				LBS KG
	Purchaser's Signature			Date