



**Booking #:** 647569

**Booking Name:** Combo Flat T/A C-152247

**Booking Revision #:** 1

**Dealer/Customer:** MAXIM TRANSPORTATION (WINNIPEG,MB)TRL

**Contact:** MAXIM TRANSPORTATION SERVICES INC

**Sales Person:** Chris Kowaliszyn

**Dealers Customer:**

**Dealers Customer #:**

**Expiration Date:** 10/23/2022

**Date:** 8/24/2022

**Requested Date:** 04/07/2023

**Dealer/Branch P.O.:**

**Customer #:** 91870

**Customer P.O.:**

Itm	Product	Reference #	Name	Model #	Qty
1	FLP - Combo Platform	C-152247	Combo Flat-53FT-ClosedT/A-QTY21-08.23.22	FLP-0024-00053	21

**Line Item 1**

**Configuration Reference #:** C-152247

**Configuration Name:** Combo Flat-53FT-ClosedT/A-QTY21-08.23.22

**FG Item:** 24248xxxx

**Product:** FLP - Combo Platform

**Model #:** FLP-0024-00053

**Mode of Transportation:** Please Select

**Product**

<b>Product</b>	FLP - Combo Platform
<b>Manufacturing Plant</b>	Huntsville, TN
<b>Model Year</b>	2024

**Geometric Dimensions**

<b>CARB/GHG Phase 2</b>	CARB/GHG2 compliance not required.
<b>Serial Identification</b>	Canadian and U.S. Certification
<b>Overall Length</b>	53' 0"
<b>Overall Width</b>	102.00"
<b>Upper Coupler Height</b>	48"
<b>Kingpin Location</b>	24.00"
<b>Landing Gear Location</b>	106.0" From Kingpin
<b>Undercarriage Design</b>	Tandem Axle, Slide Air- Ride Suspension, 60" Axle Centers
<b>Miscellaneous Text (TAB A)</b>	None

**Front**

<b>Front Crossmember</b>	Steel Front Crossmember
<b>Front Corner Type</b>	Diagonal Platform Trailer Corner
<b>Electrical Connector and Gladhand Location</b>	Near Center Front

**Great Dane LLC**



<b>Hose Couplers (Gladhands)</b>	Great Dane Control and Supply with Urethane Seals
<b>Document Holder</b>	Tite Seal #158 Located at Landing Gear Crossmember Roadside
<b>Additional Manifest Box</b>	None
<b>Additional Manifest Box Location</b>	None
<b>Stake Pockets Front</b>	None
<b>Front Stake Pockets Material and Size</b>	None
<b>Miscellaneous Text (TABB)</b>	None

#### Telematics

<b>Telematics / Tracking System</b>	Install FleetPulse Base Telematics System
<b>Alternative Telematics System</b>	...
<b>Telematics System Install and Commission</b>	Factory Furnished and Commissioned
<b>Telematics System Installation Detail</b>	Great Dane Standard Location
<b>Telematics Data Contract</b>	FleetPulse 1 Year Data Contract

#### Front Bulkhead

<b>Bulkhead Type</b>	None
<b>Bulkhead Design</b>	None
<b>Side Kit Modification</b>	None
<b>Tarp Tie Bar</b>	None
<b>Chain Rack</b>	None
<b>Miscellaneous Text (TBAA)</b>	None

#### Tarp Restraint Front

<b>Tarp Restraint (Rope Hook) Location, Front</b>	None
<b>Front Rope Hook Type</b>	None
<b>Front Rope Hook Quantity</b>	None
<b>Rope Hook Installation, Front</b>	None
<b>Rope Hook Spacing</b>	None
<b>Miscellaneous Text (TABZ)</b>	None

#### Side Exterior and Structural

<b>Side Rail Type</b>	Extruded Aluminum
<b>Side Stake Pockets</b>	Outside
<b>Stake Pockets Material and Size Side</b>	Aluminum, 1.81" x 3.38" Inside x 4" Deep
<b>Stake Pockets Spacing</b>	24" Centers
<b>Stake Pocket Location</b>	0.38" Below Top of Side Rail
<b>Rub Rail Type</b>	3.00 Aluminum
<b>Rub Rail Location</b>	Locate As Close To Top Of Pocket As Possible
<b>Spool Quantity</b>	Single
<b>Miscellaneous Text (TBBB)</b>	None

#### Rear

<b>Buckplate Material</b>	Aluminum
<b>Rear Stake Pockets</b>	None
<b>Stake Pocket Material and Size Rear</b>	None
<b>Filler Plate</b>	Aluminum
<b>Rear Bumpers</b>	Rubber Blocks, 1 Pair at Rear Corners



<b>Rear Impact Guard</b>	Carbon Steel Rear Impact Guard
<b>Tag Bracket Location</b>	None
<b>License Plate Installation</b>	None
<b>Tarp Restraint (Rope Hook) Location, Rear</b>	None
<b>Rear Rope Hook Type</b>	None
<b>Rear Rope Hook Quantity</b>	None
<b>Rear Rope Hook Installation</b>	None
<b>Rear Rope Hook Spacing</b>	None
<b>Miscellaneous Text (TABE)</b>	None

#### Floor

<b>Type of Floor</b>	Alum 1.25" Safety Grip w/2 Apitong nail strips
<b>Floor Cargo Restraint Type</b>	None
<b>Floor Cargo Restraint Quantity</b>	None
<b>Floor Cargo Restraint Location</b>	None
<b>Removable Chain Tie Downs Storage Box</b>	None
<b>Miscellaneous Text (TABH)</b>	None

#### Understructure

<b>Upper Coupler Type</b>	Unitized
<b>Bottom Plate Thickness</b>	0.25"
<b>Landing Gear</b>	GD65
<b>Landing Gear Foot / Shoe Type</b>	10" X 10" Cushion Foot
<b>Landing Gear Handle Location</b>	Roadside
<b>Tire Carrier</b>	None
<b>Mainbeam Flanges</b>	0.50" x 5.00" Top; 0.50 x 5.00" Bottom
<b>Bay Area Crossmembers</b>	4" Aluminum I-Beam on 16" Centers
<b>Extra Crossmembers</b>	None
<b>Tool Box Quantity</b>	Install Toolbox Brackets only for a 48" Tool Box on C/S and R/S behind landing gear for future tool box install
<b>Dunnage Rack</b>	None
<b>Dunnage Rack Location</b>	None
<b>Miscellaneous Text (TBHH)</b>	None

#### Tool Boxes

<b>Type of Tool Box</b>	0
<b>Tool Box Mounting Location</b>	
<b>Tool Box Door Hinge Location</b>	Hinged at Sides

#### Side Winch and Tarp Restraint

<b>Quantity of Fixed Winches Mounted between Crossmembers</b>	None
<b>Quantity of Fixed Undermount Winches In Bay-Area</b>	None
<b>Quantity of Sliding Winches</b>	Twenty-six
<b>Sliding Winch Track</b>	Both Sides (Curbside and Roadside) Sliding Winch Track, Double "L"
<b>Winch Track Length (Slide)</b>	Unitized Track Extruded into Siderail



<b>Sliding Winch Type</b>	Canadian-style 3 -bar Winch
<b>Winch Strap Type (Sliding Winches)</b>	None
<b>Winch Strap Quantity (Sliding Winches)</b>	None
<b>Miscellaneous Text (TBCC)</b>	SLIDING ROPES HOOKS ON SIDE, "J" HOOKS .63" STEEL - (26) TOTAL HOOKS, OPPOSITE WINCHES. (HOOKS TO BE INSTALLED ON ALTERNATING PATTERN WITH WINCHES, R/S STARTS WITH WINCH, C/S STARTS WITH HOOK)

#### Suspension

<b>Model of Suspension</b>	Hendrickson AAZNT Platform Slider
<b>Axle Type</b>	Hendrickson Tapered Spindle Standard Wall
<b>Ready-to-Roll Wheel End</b>	HXL5 Hendrickson Extended-Life 5-Year System
<b>Bogie Location</b>	48" Slide Travel (Minimum)
<b>Locking Mechanism</b>	Air-Assist Pin Release
<b>Dump Valve</b>	Manual Dump Valve w/Weatherproof Box and Liquid Air Pressure Gauge
<b>Auxillary Dump Valve</b>	None
<b>Auxillary Dump Valve Location</b>	None
<b>Pintle Hook</b>	None
<b>Miscellaneous Text (TABL)</b>	None

#### Rear Ramps and Mud Flaps

<b>Mudflaps</b>	Great Dane, Ribbed Black with Logo
<b>Mudflap Mounting Location</b>	Behind Rear Axle
<b>Miscellaneous Text (TABM)</b>	None

#### Brakes, Tire Inflation Systems and Wheel Ends

<b>Brake Size</b>	16.50" x 7.00"
<b>Brake Actuators</b>	Great Dane Standard 2.5" Stroke
<b>Brake Lining</b>	Standard Brake Lining
<b>Brake Shoe Type</b>	Extended Service
<b>Brake Adjusters</b>	Meritor Automatic 5.50"
<b>Supplemental Brake Stroke Indicator</b>	None
<b>Dust Shield Type</b>	Great Dane Standard
<b>Tire-Inflation-System/Tire/Wheel Options</b>	Prep axle(s) for future installation of tire inflation system ( 3 Holes )
<b>Tire Inflation System Pressure</b>	None
<b>Auxiliary Pressure Check Port</b>	None
<b>Wheel Seals</b>	Furnished with RTR Wheel End System
<b>Axle Spindle Nuts</b>	Furnished with RTR Wheel End System
<b>Hubcaps</b>	Furnished with RTR Wheel End System
<b>Wheel Lubricant</b>	Semi-Fluid Grease Furnished with RTR Wheel End System
<b>Anti-Lock Brakes</b>	Wabco 2S/2M iABS Premium
<b>ECU Monitored Option</b>	ABS Fault Codes and Mileage
<b>Optional Diagnostic Cable</b>	None
<b>Brake Valves</b>	Sealco
<b>Air-Tank Drain Valve</b>	Manual
<b>Hubodometer YN</b>	None
<b>Miscellaneous Text (TABN)</b>	None



#### Tires / Wheels / Hubs and Drums

<b>Rim/Disc Wheel Size</b>	22.5" X 8.25"
<b>Hub/Wheel And Drum</b>	Hendrickson HXL Ductile Iron Hub Piloted 10 Stud Hub With Webb Outboard Cast Drums
<b>Brake Drum Balancing</b>	Supplied Balanced Only
<b>Wheel Type</b>	22.5" Steel Disc Wheels With Aluminum Disc Wheels Outboard, Hub Piloted
<b>Wheel/Rim Vendor</b>	Great Dane Steel/Great Dane Aluminum
<b>Wheel Stud Options</b>	Long Studs Furnished with HXL Wheel End System
<b>Wheel Spacer (Corrosion Barrier)</b>	Spacer between Inner and Outer Disc Wheels
<b>Tire Size</b>	11R 22.5
<b>Tire Brand</b>	Bridgestone Ecopia R123 (G)
<b>Miscellaneous Text (TABO)</b>	None

#### Electrical

<b>Exterior Light Package</b>	All Lights LED, Grote Long Life Light System, AMP Connector, Grote MicroNova Dot Lamps
<b>Type of Clearance Lights</b>	Grote, LED MicroNova Dot Lamps with Dual Intensity ID Lamps
<b>Electrical Connector Type</b>	Great Dane Standard 7-Way Split Pin
<b>Telematics Data Bus</b>	CAN Bus Communications with FleetPulse Base
<b>Side Bottom Lights</b>	3 Each Side (Front, Rear, and standard Midship Combination)
<b>Side Bottom Light Locations</b>	Evenly spaced Front to Rear
<b>Buckplate Light Type</b>	Grote Series 40, LED Flange Mount
<b>Buckplate Lights Qty &amp; Loc</b>	2 Each Side
<b>Midship Turn Signal</b>	Grote LED Combination Turn and Clearance
<b>Location of Turn Signal</b>	Roadside and Curbside, Center of Trailer
<b>Installation of Turn Signal</b>	Attach To Bottom Of Crossmember
<b>Supplemental Turn Signal</b>	None
<b>Type of Supplemental Turn-Signal</b>	None
<b>Location of Supplemental Turn Signal</b>	None
<b>Installation of Supplemental turn Signal</b>	None
<b>Miscellaneous Text (TABP)</b>	INSTALL 4-WAY PLUG AT REAR OF TRAILER
<b>Miscellaneous Text (TBDD)</b>	None

#### Finish/Paint/Decal

<b>Paint</b>	Black, Urethane
<b>Wheel Finish</b>	White Steel, Standard Finish Aluminum Outboard
<b>Conspicuity Treatment Location</b>	Great Dane on Siderails
<b>Manufacturer's Logo Installation</b>	Red Logos
<b>Installation Of Customer Decals</b>	None
<b>Exterior Unit Numbers</b>	None
<b>Miscellaneous Text (TABR)</b>	None
<b>Miscellaneous Text (TBFF)</b>	None
<b>Miscellaneous Text (TBGG)</b>	None

#### Calculated Values

<b>CARB Compliance Year</b>	2023
-----------------------------	------

#### Geometric Dimensions



**Packaged Options** None

Floor

**Special Floor Rating** None

Rear Ramps and Mud Flaps

**Mudflap Quantity/Bracket Material** 1-Pair

Tires / Wheels / Hubs and Drums

**Spare Tire** None

Miscellaneous Text (TABP) - INSTALL 4-WAY PLUG AT REAR OF TRAILER

EENID-2 BOMID-501429 CPQ-

Miscellaneous Text (TBCC) - SLIDING ROPES HOOKS ON SIDE, "J" HOOKS .63" STEEL - (26) TOTAL HOOKS, OPPOSITE WINCHES.

(HOOKS TO BE INSTALLED ON ALTERNATING PATTERN WITH WINCHES, R/S STARTS WITH WINCH, C/S STARTS WITH HOOK)

EENID-1 BOMID-501430 CPQ-

Tool Box Quantity - Install Toolbox Brackets only for a 48" Tool Box on C/S and R/S behind landing gear for future tool box install

EENID-3 BOMID-501431 CPQ-

Note: All Model year 2022 quotes subject to change pending legal regulations in regard to GHG2 requirements.