



**Booking #:** 678591

**Booking Name:** 9x Stock Tridem Steel Flat Deck May 2026

**Booking Revision #:** 5

**Dealer/Customer:** MAXIM TRANSPORTATION (WINNIPEG,MB)TRL  
**Contact:** MAXIM TRANSPORTATION SERVICES INC  
**Sales Person:** Chris Kowaliszyn  
**Dealers Customer:** MAXIM TRANSPORTATION (WINNIPEG,MB)TRL  
**Dealers Customer #:** 91870

**Expiration Date:** 7/12/2026  
**Date:** 6/12/2026  
**Requested Date Earliest:** 05/15/2026  
**Requested Date:** 10/30/2026  
**Dealer/Branch P.O.:**  
**Customer #:** 91870  
**Customer P.O.:**

Itm	Product	Reference #	Name	Model #	Qty
1	FSP - Steel Platform	C-227179	6x Stock Tridem Steel Flat Deck May 2026	FSP-0026-00053	9

**Line Item 1**

**Configuration Reference #:** C-227179  
**Configuration Name:** 6x Stock Tridem Steel Flat Deck May 2026  
**FG Item:** 27248xxxx  
**Product:** FSP - Steel Platform  
**Model #:** FSP-0026-00053  
**Mode of Transportation:** Customer Pick-Up

**Product**

---

**Product** FSP - Steel Platform  
**Manufacturing Plant** Huntsville, TN  
**Model Year** 2027

**Geometric Dimensions**

---

**CARB/CA Phase 2 GHG** CARB/GHG2 compliance not required.  
**Serial Identification** Canadian and U.S. Certification  
**Overall Length** 53' 0"  
**Overall Width** 102.00"  
**Upper Coupler Height** 48"  
**Kingpin Location** 24.00"  
**Landing Gear Location** 106.0" From Kingpin  
**Undercarriage Design** Tridem Axle, Slide Air-Ride Suspension, 60" Axle Centers  
**Miscellaneous Text (TAB A)** None

**Front**

---

**Front Crossmember** Steel Front Crossmember  
**Front Corner Type** Diagonal Platform Trailer Corner



<b>Electrical Connector and Gladhand Location</b>	Near Center Front
<b>Hose Couplers (Gladhands)</b>	Great Dane Control and Supply with Urethane Seals
<b>Document Holder</b>	Tite Seal #158 Located at Landing Gear Crossmember Roadside
<b>Additional Manifest Box</b>	None
<b>Additional Manifest Box Location</b>	None
<b>Stake Pockets Front</b>	Five
<b>Front Stake Pockets Material and Size</b>	0.25 Steel, 7.00" Deep with 4" x 3.88" ID Opening
<b>Miscellaneous Text (TABB)</b>	None
<b>Telematics</b>	
<b>Telematics / Tracking System</b>	FleetPulseGo Track
<b>Alternative Telematics System</b>	...
<b>Telematics System Install and Commission</b>	Factory Furnished and Factory Commissioned
<b>Telematics System Installation Detail</b>	Great Dane Standard Location
<b>Telematics / Tracking Power Supply</b>	...
<b>Front Bulkhead</b>	
<b>Bulkhead Type</b>	None
<b>Bulkhead Design</b>	None
<b>Side Kit Modification</b>	None
<b>Tarp Tie Bar</b>	None
<b>Chain Rack</b>	None
<b>Miscellaneous Text (TBAA)</b>	None
<b>Tarp Restraint Front</b>	
<b>Tarp Restraint (Rope Hook) Location, Front</b>	None
<b>Front Rope Hook Type</b>	None
<b>Front Rope Hook Quantity</b>	None
<b>Rope Hook Installation, Front</b>	None
<b>Rope Hook Spacing</b>	None
<b>Miscellaneous Text (TABZ)</b>	None
<b>Side Exterior and Structural</b>	
<b>Side Rail Type</b>	6" Deep 8.2# Structural Channel
<b>Side Stake Pockets</b>	Outside
<b>Stake Pockets Material and Size Side</b>	Steel 0.19" x 1.81" x 3.38" Inside x 3" Deep
<b>Stake Pockets Spacing</b>	24" Centers
<b>Stake Pocket Location</b>	0.38" Below Top of Side Rail
<b>Rub Rail Type</b>	0.25" X 2.00"
<b>Rub Rail Location</b>	Centered on Stake Pocket
<b>Spool Quantity</b>	Single
<b>Miscellaneous Text (TBBB)</b>	None
<b>Rear</b>	
<b>Buckplate Material</b>	Carbon Steel
<b>Rear Stake Pockets</b>	Five



<b>Stake Pocket Material and Size Rear</b>	Steel, .019" X 1.81" Inside X 3.38" Inside X 3" Deep
<b>Filler Plate</b>	Aluminum
<b>Rear Bumpers</b>	Rubber Blocks, 1 Pair at Rear Corners
<b>Rear Impact Guard</b>	Carbon Steel Rear Impact Guard
<b>Tag Bracket Location</b>	Centered on Filler Plate
<b>License Plate Installation</b>	None
<b>Tarp Restraint (Rope Hook) Location, Rear</b>	None
<b>Rear Rope Hook Type</b>	None
<b>Rear Rope Hook Quantity</b>	None
<b>Rear Rope Hook Installation</b>	None
<b>Rear Rope Hook Spacing</b>	None
<b>Fork Lift Package</b>	None
<b>Counter Weight</b>	None
<b>Miscellaneous Text (TABE)</b>	None

**Floor**

<b>Type of Floor</b>	Apitong 1.13"
<b>Floor Cargo Restraint Type</b>	None
<b>Floor Cargo Restraint Quantity</b>	None
<b>Floor Cargo Restraint Location</b>	None
<b>Twist Lock / Container Lock</b>	None
<b>Miscellaneous Text (TABH)</b>	None

**Understructure**

<b>Upper Coupler Type</b>	Unitized
<b>Bottom Plate Thickness</b>	0.38"
<b>Landing Gear</b>	GD65
<b>Landing Gear Foot / Shoe Type</b>	10" X 10" Cushion Foot
<b>Landing Gear Handle Location</b>	Roadside
<b>Tire Carrier</b>	None
<b>Mainbeam Flanges</b>	0.50" x 5.00" Top; 0.63 x 5.00" Bottom
<b>Curtainside Preparation</b>	None
<b>Bay Area Crossmembers</b>	4" Steel I-Beam on 16" Centers
<b>Extra Crossmembers</b>	None
<b>Tool Box Quantity</b>	One
<b>Dunnage Rack</b>	Aluminum Undermount Dunnage Rack 108"
<b>Dunnage Rack Location</b>	Roadside Bay
<b>Miscellaneous Text (TBHH)</b>	None

**Tool Boxes**

<b>Type of Tool Box</b>	Aluminum, 24" Wide x 24" High x 48" Long, Double Door (CamLock Style Closure)
<b>Tool Box Mounting Location</b>	Roadside Behind Landing Gear
<b>Tool Box Door Hinge Location</b>	Hinged at Sides

**Side Winch and Tarp Restraint**

<b>Quantity of Fixed Winches Mounted between Crossmembers</b>	None
---	------



<b>Quantity of Fixed Undermount Winches In Bay-Area</b>	None
<b>Quantity of Sliding Winches</b>	None
<b>Miscellaneous Text (TBCC)</b>	INSTALL (25) LOW-PROFILE WINCHES WELDED TO BODY BORDER UNDER RUB-RAIL POINTING OUTWARD. EQUALLY SPACE AND STAGGER WINCHES STARTING 2FT FROM NOSE AND APPROX EVERY 2FT. ENSURE THAT SPLINE LOCKS FALL FROM THE TOP AND WINCHES AND "C" HOOK LOCATIONS DO NOT INTERFERE WITH PIPE SPOOLS. MAINTAIN ADEQUATE CLEARANCE BETWEEN SPOOLS, STAKE POCKETS AND WINCHES.

### Suspension

<b>Model of Suspension</b>	Hendrickson AAZNT Platform Slider
<b>Axle Type</b>	Hendrickson Tapered Spindle Standard Wall
<b>Zero Maintenance Damping</b>	None
<b>Integrated Wheel End Package</b>	RTR HXL5 Hendrickson Extended-Life 5-Year System
<b>Bogie Location</b>	48" Slide Travel (Minimum)
<b>Locking Mechanism</b>	Air-Assist Pin Release
<b>Dump Valve</b>	Manual Dump Valve w/Weatherproof Box and Liquid Air Pressure Gauge
<b>Auxillary Dump Valve</b>	None
<b>Auxillary Dump Valve Location</b>	None
<b>Pintle Hook</b>	None
<b>Miscellaneous Text (TABL)</b>	None

### Rear Ramps and Mud Flaps

<b>Mudflaps</b>	Great Dane, Ribbed Black with Logo
<b>Mudflap Mounting Location</b>	Behind Rear Axle
<b>Miscellaneous Text (TABM)</b>	None

### Brakes, Tire Inflation Systems and Wheel Ends

<b>Brake Size</b>	16.50" x 7.00"
<b>Brake Actuators</b>	Great Dane Standard 2.5" Stroke
<b>Brake Lining</b>	Standard Brake Lining
<b>Brake Shoe Type</b>	Extended Service
<b>Brake Adjusters</b>	Meritor Automatic 5.50"
<b>Supplemental Brake Stroke Indicator</b>	None
<b>Dust Shield Type</b>	Great Dane Standard
<b>Tire-Inflation-System/Tire/Wheel Options</b>	None
<b>Tire Inflation System Pressure</b>	None
<b>Auxiliary Pressure Check Port</b>	None
<b>Wheel Seals</b>	Furnished with Integrated Wheel End System
<b>Axle Spindle Nuts</b>	Furnished with Integrated Wheel End System
<b>Hubcaps</b>	Furnished with Integrated Wheel End System
<b>Wheel Lubricant</b>	Semi-Fluid Grease Furnished with Integrated Wheel End System
<b>Anti-Lock Brakes</b>	Wabco 2S/2M iABS Premium
<b>ECU Monitored Option</b>	None
<b>Brake Valves</b>	Sealco 110500 Spring Brake Priority



<b>Air-Tank Drain Valve</b>	Manual
<b>Hubodometer YN</b>	None
<b>Miscellaneous Text (TABN)</b>	None
<b>Tires / Wheels / Hubs and Drums</b>	
<b>Rim/Disc Wheel Size</b>	24.5" X 8.25"
<b>Hub/Wheel And Drum</b>	Hendrickson HXL Ductile Iron Hub Piloted 10 Stud Hub With Webb Outboard Cast Drums
<b>Brake Drum Balancing</b>	Supplied Balanced Only
<b>Wheel Type</b>	24.5" Steel Disc Wheel, Hub Piloted, 5HH
<b>Wheel/Rim Vendor</b>	Great Dane
<b>Wheel Stud Options</b>	Long Studs Furnished with HXL Wheel End System
<b>Wheel Spacer (Corrosion Barrier)</b>	None
<b>Tire Size</b>	11R 24.5
<b>Tire Brand</b>	Bridgestone R196A (G)
<b>Miscellaneous Text (TABO)</b>	None
<b>Electrical</b>	
<b>Exterior Light Package</b>	All Lights LED, Grote Long Life Light System, AMP Connector, Grote MicroNova Dot Lamps
<b>Type of Clearance Lights</b>	Grote, LED MicroNova Dot Lamps with Dual Intensity ID Lamps
<b>Electrical Connector Type</b>	Great Dane Standard 7-Way Split Pin
<b>Side Bottom Lights</b>	3 Each Side (Front, Rear, and standard Midship Combination)
<b>Side Bottom Light Locations</b>	Evenly spaced Front to Rear
<b>Buckplate Light Type</b>	Grote Series 40, LED Flange Mount
<b>Buckplate Lights Qty &amp; Loc</b>	3 Each Side, Stop/Tail/Red Turn
<b>Midship Turn Signal</b>	Grote LED Combination Turn and Clearance
<b>Location of Turn Signal</b>	Roadside and Curbside, Center of Trailer
<b>Installation of Turn Signal</b>	Attach To Bottom Of Crossmember
<b>Supplemental Turn Signal</b>	None
<b>Type of Supplemental Turn-Signal</b>	None
<b>Location of Supplemental Turn Signal</b>	None
<b>Installation of Supplemental turn Signal</b>	None
<b>Miscellaneous Text (TABP)</b>	Install 4-Way Plug at Rear of Trailer
<b>Miscellaneous Text (TBDD)</b>	None
<b>Finish/Paint/Decal</b>	
<b>Paint</b>	Black, Urethane
<b>Wheel Finish</b>	White Powder Coat
<b>Conspicuity Treatment Location</b>	Great Dane on Siderails
<b>Manufacturer's Logo Installation</b>	Red Logos
<b>Installation Of Customer Decals</b>	None
<b>Exterior Unit Numbers</b>	None
<b>Miscellaneous Text (TABR)</b>	None
<b>Miscellaneous Text (TBFF)</b>	None
<b>Miscellaneous Text (TBGG)</b>	None



**Calculated Values**

<b>Production Line</b>	Production Line To Be Determined
<b>CARB Compliance Year</b>	2026

**Geometric Dimensions**

<b>Packaged Options</b>	None
<b>Drop Depth</b>	None

**Calculated Values**

<b>Side Door Y/N</b>	No
----------------------	----

**Floor**

<b>Special Floor Rating</b>	None
-----------------------------	------

**Suspension**

<b>Brake Type</b>	010_drum
-------------------	----------

**Rear Ramps and Mud Flaps**

<b>Mudflap Quantity/Bracket Material</b>	1-Pair
--	--------

**Tires / Wheels / Hubs and Drums**

<b>Spare Tire</b>	None
-------------------	------

Miscellaneous Text (TABP) - Install 4-Way Plug at Rear of Trailer		
EENID-1	BOMID-828754	CPQ-
Miscellaneous Text (TBCC) - INSTALL (25) LOW-PROFILE WINCHES WELDED TO BODY BORDER UNDER RUB-RAIL POINTING OUTWARD. EQUALLY SPACE AND STAGGER WINCHES STARTING 2FT FROM NOSE AND APPROX EVERY 2FT. ENSURE THAT SPLINE LOCKS FALL FROM THE TOP AND WINCHES AND "C" HOOK LOCATIONS DO NOT INTERFERE WITH PIPE SPOOLS. MAINTAIN ADEQUATE CLEARANCE BETWEEN SPOOLS, STAKE POCKETS AND WINCHES.		
EENID-2	BOMID-828755	CPQ-

Pricing and lead times are provided as estimates and are subject to change based on final chassis specifications including make, model, configuration, and availability. Complete chassis details must be provided at the time of order. Final pricing, delivery schedules, and product compatibility will be confirmed upon review of the full chassis specification. Any change to chassis information may impact our ability to build the requested solution and could result in adjustments to cost and lead time.