



Order #: 167180

Order Name: Alum Flat RAS - QTY 9 - 09.16.21

Order Revision #: 0

Dealer/Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL

Date: 9/21/2021

Contact: MAXIM TRANSPORTATION SERVICES INC

Requested Date: 1/28/2022

Sales Person: Tom Klassen

Dealer/Branch P.O: 6

Dealers Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL

Customer #: 91870

Dealers Customer #: 91870

Customer P.O: 3126

Itm	Product	Reference #	Name	Model #	Qty
1	FXP - Aluminum Platform	C-136447	ALL ALUMINUM RAS - STOCK - 09.16.21	FXP-0029-00053	9

Line Item 1

Configuration Reference #: C-136447

Configuration Name: ALL ALUMINUM RAS - STOCK - 09.16.21

FG Item: 232480023

Product: FXP - Aluminum Platform

Model #: FXP-0029-00053

Mode of Transportation: Customer Pick-Up

Product

Product FXP - Aluminum Platform

Manufacturing Plant Huntsville, TN

Model Year 2023

Geometric Dimensions

CARB/GHG Phase 2 CARB/GHG2 compliance not required.

Serial Identification Canadian and U.S. Certification

Overall Length 53' 0"

Overall Width 102.00"

Upper Coupler Height 48"

Kingpin Location 24.00"

Landing Gear Location 106.0" From Kingpin

Undercarriage Design CUSTOMER IS LOOKING FOR RTAC AND CALIFORNIA COMPLIANT
- SLIDE REAR, FIXED FRONT AIR-SUSPENSION 61"-121"
(INCLUDES 60K BOTTOM BEAM EXTRUSION)

Miscellaneous Text (TAB A) None

Front



Front Corner Type	Diagonal Platform Trailer Corner
Telematics / Tracking System	None
Telematics System Installation Detail	None
Telematics Data Contract	
Electrical Connector and Gladhand Location	Near Center Front
Hose Couplers (Gladhands)	Great Dane Control and Supply with Urethane Seals
Document Holder	Tite Seal #158 Located at Landing Gear Crossmember Roadside
Additional Manifest Box	None
Additional Manifest Box Location	None
Stake Pockets Front	None
Front Stake Pockets Material and Size	None
Miscellaneous Text (TABB)	None

Front Bulkhead

Bulkhead Type	None
Bulkhead Design	None
Side Kit Modification	None
Tarp Tie Bar	None
Chain Rack	None
Miscellaneous Text (TBAA)	None

Tarp Restraint Front

Tarp Restraint (Rope Hook) Location, Front	None
Front Rope Hook Type	None
Front Rope Hook Quantity	None
Rope Hook Installation, Front	None
Rope Hook Spacing	None
Miscellaneous Text (TABZ)	None

Side Exterior and Structural

Side Rail Type	Extruded Aluminum
Side Stake Pockets	Outside
Stake Pockets Material and Size Side	Aluminum, 1.81" x 3.38" Inside x 4" Deep
Stake Pockets Spacing	24" Centers
Stake Pocket Location	0.38" Below Top of Side Rail
Rub Rail Type	3.00 Aluminum
Rub Rail Location	Centered on Stake Pocket
Spool Quantity	Single
Miscellaneous Text (TBBB)	None

Rear

Buckplate Material	Aluminum
---------------------------	----------



Rear Stake Pockets	None
Stake Pocket Material and Size Rear	None
Filler Plate	Aluminum
Rear Bumpers	Rubber Blocks, 1 Pair at Rear Corners
Rear Impact Guard	Aluminum Rear Impact Guard
Tag Bracket Location	None
License Plate Installation	None
Tarp Restraint (Rope Hook) Location, Rear	None
Rear Rope Hook Type	None
Rear Rope Hook Quantity	None
Rear Rope Hook Installation	None
Rear Rope Hook Spacing	None
Miscellaneous Text (TABE)	None

Floor

Type of Floor	Alum 1.25" Safety Grip w/2 Apitong nail strips
Floor Cargo Restraint Type	None
Floor Cargo Restraint Quantity	None
Floor Cargo Restraint Location	None
Removable Chain Tie Downs Storage Box	None
Miscellaneous Text (TABH)	None

Understructure

Upper Coupler Type	Unitized
Bottom Plate Thickness	0.25"
Landing Gear	Holland Mark V
Landing Gear Foot / Shoe Type	12" Dia Round Foot
Landing Gear Handle Location	Roadside
Tire Carrier	None
Mainbeam Flanges	Extruded Aluminum Beams
Bay Area Crossmembers	4" Aluminum I-Beam on 16" Centers
Extra Crossmembers	Single Coil Package In Single Coil Area
Tool Box Quantity	One
Dunnage Rack	None
Dunnage Rack Location	None
Miscellaneous Text (TBHH)	None

Tool Boxes

Type of Tool Box	Aluminum, 24" Wide x 24" High x 48" Long, Double Door (CamLock Style Closure)
Tool Box Mounting Location	Roadside Behind Landing Gear



Tool Box Door Hinge Location	Hinged at Sides
Side Winch and Tarp Restraint	
Quantity of Fixed Undermount Winches In Bay-Area	None
Quantity of Sliding Winches	Twenty-four
Sliding Winch Track	Both Sides (Curbside and Roadside) Sliding Winch Track, Double "L"
Winch Track Length (Slide)	Unitized Track Extruded into Siderail
Sliding Winch Type	Canadian-style 3 -bar Winch
Winch Strap Type (Sliding Winches)	None
Winch Strap Quantity (Sliding Winches)	None
Miscellaneous Text (TBCC)	INSTALL TOTAL OF (24) SLIDING J-HOOKS: (12) WINCHES PER SIDE, PLEASE ADD (12) SLIDING J HOOKS PER SIDE STAGGERED BETWEEN WINCHES
Suspension	
Model of Suspension	Hendrickson AANT 23K
Axle Type	Hendrickson Tapered Spindle Standard Wall
Ready-to-Roll Wheel End	None
Bogie Location	"California-Legal": 40 Ft. Maximum From KP To Center Of Rear Axle
Dump Valve	Manual Dump Valve w/Weatherproof Box and Liquid Air Pressure Gauge
Auxillary Dump Valve	None
Auxillary Dump Valve Location	None
Miscellaneous Text (TABL)	None
Rear Ramps and Mud Flaps	
Mudflaps	Great Dane, Ribbed Black with Logo
Mudflap Mounting Location	Behind Rear Axle
Miscellaneous Text (TABM)	None
Brakes, Tire Inflation Systems and Wheel Ends	
Brake Size	16.50" x 7.00"
Brake Actuators	Great Dane Standard 2.5" Stroke
Brake Lining	Standard Brake Lining
Brake Shoe Type	Extended Service
Brake Adjusters	Meritor Automatic 5.50"
Supplemental Brake Stroke Indicator	None
Dust Shield Type	Great Dane Standard
Tire-Inflation-System/Tire/Wheel Options	Prep axle(s) for future installation of tire inflation system (3 Holes)
Tire Inflation System Pressure	None
Auxiliary Pressure Check Port	None
Wheel Seals	Platinum-Plus Performance Package
Axle Spindle Nuts	Zip-Torq Spindle Nut



Hubcaps	Aluminum Sentinel
Wheel Lubricant	Oil
Anti-Lock Brakes	Wabco 2S/1M Easy Stop
Optional Diagnostic Cable	None
Brake Valves	Sealco
Air-Tank Drain Valve	Manual
Hubodometer YN	None
Miscellaneous Text (TABN)	None
Tires / Wheels / Hubs and Drums	
Rim/Disc Wheel Size	22.5" X 8.25"
Hub/Wheel And Drum	Great Dane Hub Piloted Universal 10 Stud Hub with Outboard Cast Drums
Brake Drum Balancing	None-Not Balanced
Wheel Type	22.5" Aluminum Disc Wheel, Hub Piloted
Wheel/Rim Vendor	Great Dane
Wheel Stud Options	Long Studs for Future Alum Wheels
Wheel Spacer (Corrosion Barrier)	Spacer between Hub and Disc Wheel
Tire Size	11R 22.5
Tire Brand	Bridgestone Ecopia R123 (G)
Miscellaneous Text (TABO)	None
Electrical	
Exterior Light Package	All Lights LED, Grote Long Life Light System, Grote MicroNova Dot Lamps
Type of Clearance Lights	Grote, LED MicroNova Dot Lamps with Dual Intensity ID Lamps
Electrical Connector Type	Great Dane Standard 7-Way Solid Pin
Side Bottom Lights	3 Each Side (Front, Rear, and standard Midship Combination)
Side Bottom Light Locations	Evenly spaced Front to Rear
Buckplate Light Type	Grote Series 40, LED Flange Mount
Buckplate Lights Qty & Loc	3 Each Side, Stop/Tail/Red Turn
Midship Turn Signal	Grote LED Combination Turn and Clearance
Location of Turn Signal	Roadside and Curbside, Center of Trailer
Installation of Turn Signal	Attach To Bottom Of Crossmember
Supplemental Turn Signal	None
Type of Supplemental Turn-Signal	None
Location of Supplemental Turn Signal	None
Installation of Supplemental turn Signal	None
Miscellaneous Text (TABP)	INSTALL 4 WAY PLUG AT REAR OF TRAILER
Miscellaneous Text (TBDD)	None
Finish/Paint/Decal	
Paint	Black, Urethane



Wheel Finish	Standard Finish Inboard, Mirror Polish Dish Side Outboard
Conspicuity Treatment Location	Great Dane on Siderails
Manufacturer's Logo Installation	Red Logos
Installation Of Customer Decals	None
Exterior Unit Numbers	None
Miscellaneous Text (TABR)	None
Miscellaneous Text (TBFF)	None
Miscellaneous Text (TBGG)	None
Calculated Values	
CARB Compliance Year	2022
Geometric Dimensions	
Packaged Options	None
GHG2 Green House Gas Compliance	
GHG2 Green House Gas Classification	Excluded
Floor	
Special Floor Rating	None
Suspension	
Locking Mechanism	None
Pintle Hook	None
Rear Ramps and Mud Flaps	
Mudflap Quantity/Bracket Material	1-Pair
Tires / Wheels / Hubs and Drums	
Spare Tire	None

Miscellaneous Text (TABP) - INSTALL 4 WAY PLUG AT REAR OF TRAILER		
EENID-136447-3	BOMID-442099	CPQ-
Undercarriage Design - CUSTOMER IS LOOKING FOR RTAC AND CALIFORNIA COMPLIANT - SLIDE REAR, FIXED FRONT AIR-SUSPENSION 61"-121" (INCLUDES 60K BOTTOM BEAM EXTRUSION)		
EENID-136447-1	BOMID-442100	CPQ-
Miscellaneous Text (TBCC) - INSTALL TOTAL OF (24) SLIDING J-HOOKS: (12) WINCHES PER SIDE, PLEASE ADD (12) SLIDING J HOOKS PER SIDE STAGGERED BETWEEN WINCHES		
EENID-136447-2	BOMID-442101	CPQ-