



Order #: 166603

Order Name: Combo Flat - Tandem Slide - QTY6 - 03.17.21

Order Revision #: 0

Dealer/Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL

Date: 3/22/2021

Contact: MAXIM TRANSPORTATION SERVICES INC

Requested Date: 9/3/2021

Sales Person: Tom Klassen

Dealer/Branch P.O: 6

Dealers Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL

Customer #: 91870

Dealers Customer #: 91870

Customer P.O: 3077

Itm	Product	Reference #	Name	Model #	Qty
1	FLP - Combo Platform	C-131677	Combo Flat-53FT-Tandem-QTY6-03.17.21	FLP-0024-00053	6

**Line Item 1**

**Configuration Reference #:** C-131677

**Configuration Name:** Combo Flat-53FT-Tandem-QTY6-03.17.21

**FG Item:** 22248xxxx

**Product:** FLP - Combo Platform

**Model #:** FLP-0024-00053

**Mode of Transportation:** Customer Pick-Up

**Product**

**Product** FLP - Combo Platform

**Manufacturing Plant** Huntsville, TN

**Model Year** 2022

**Geometric Dimensions**

**CARB/GHG Phase 2** CARB/GHG2 compliance not required.

**Serial Identification** Canadian and U.S. Certification

**Overall Length** 53' 0"

**Overall Width** 102.00"

**Upper Coupler Height** 48"

**Kingpin Location** 24.00"

**Landing Gear Location** 106.0" From Kingpin

**Undercarriage Design** Tandem Axle, Slide Air-Ride Suspension, 49" Axle Centers

**Miscellaneous Text (TABA)** None

**Front**

**Front Crossmember** Steel Front Crossmember



<b>Front Corner Type</b>	Diagonal Platform Trailer Corner
<b>Telematics / Tracking System</b>	None
<b>Telematics System Installation Detail</b>	None
<b>Electrical Connector and Gladhand Location</b>	Near Center Front
<b>Hose Couplers (Gladhands)</b>	Great Dane Control and Supply with Urethane Seals
<b>Document Holder</b>	Tite Seal #158 Located at Landing Gear Crossmember Roadside
<b>Additional Manifest Box</b>	None
<b>Additional Manifest Box Location</b>	None
<b>Stake Pockets Front</b>	None
<b>Front Stake Pockets Material and Size</b>	None
<b>Miscellaneous Text (TABB)</b>	None
<b>Front Bulkhead</b>	
<b>Bulkhead Type</b>	None
<b>Bulkhead Design</b>	None
<b>Side Kit Modification</b>	None
<b>Tarp Tie Bar</b>	None
<b>Chain Rack</b>	None
<b>Miscellaneous Text (TBAA)</b>	None
<b>Tarp Restraint Front</b>	
<b>Tarp Restraint (Rope Hook) Location, Front</b>	None
<b>Front Rope Hook Type</b>	None
<b>Front Rope Hook Quantity</b>	None
<b>Rope Hook Installation, Front</b>	None
<b>Rope Hook Spacing</b>	None
<b>Miscellaneous Text (TABZ)</b>	None
<b>Side Exterior and Structural</b>	
<b>Side Rail Type</b>	Extruded Aluminum
<b>Side Stake Pockets</b>	Outside
<b>Stake Pockets Material and Size Side</b>	Aluminum, 1.81" x 3.38" Inside x 4" Deep
<b>Stake Pockets Spacing</b>	24" Centers
<b>Stake Pocket Location</b>	0.38" Below Top of Side Rail
<b>Rub Rail Type</b>	3.00 Aluminum
<b>Rub Rail Location</b>	Locate As Close To Top Of Pocket As Possible
<b>Spool Quantity</b>	Single
<b>Miscellaneous Text (TBBB)</b>	None
<b>Rear</b>	
<b>Buckplate Material</b>	Aluminum
<b>Rear Stake Pockets</b>	None



<b>Stake Pocket Material and Size Rear</b>	None
<b>Filler Plate</b>	Aluminum
<b>Rear Bumpers</b>	Rubber Blocks, 1 Pair at Rear Corners
<b>Rear Impact Guard</b>	Carbon Steel Rear Impact Guard
<b>Tag Bracket Location</b>	None
<b>License Plate Installation</b>	None
<b>Tarp Restraint (Rope Hook) Location, Rear</b>	None
<b>Rear Rope Hook Type</b>	None
<b>Rear Rope Hook Quantity</b>	None
<b>Rear Rope Hook Installation</b>	None
<b>Rear Rope Hook Spacing</b>	None
<b>Miscellaneous Text (TABE)</b>	None

#### Floor

---

<b>Type of Floor</b>	Alum 1.25" Safety Grip w/2 Apitong nail strips
<b>Floor Cargo Restraint Type</b>	None
<b>Floor Cargo Restraint Quantity</b>	None
<b>Floor Cargo Restraint Location</b>	None
<b>Removable Chain Tie Downs Storage Box</b>	None
<b>Miscellaneous Text (TABH)</b>	None

#### Understructure

---

<b>Upper Coupler Type</b>	Unitized
<b>Bottom Plate Thickness</b>	0.25"
<b>Landing Gear</b>	GD65
<b>Landing Gear Foot / Shoe Type</b>	10" X 10" Cushion Foot
<b>Landing Gear Handle Location</b>	Roadside
<b>Tire Carrier</b>	None
<b>Mainbeam Flanges</b>	0.50" x 5.00" Top; 0.50 x 5.00" Bottom
<b>Bay Area Crossmembers</b>	4" Aluminum I-Beam on 16" Centers
<b>Extra Crossmembers</b>	None
<b>Tool Box Quantity</b>	One
<b>Dunnage Rack</b>	None
<b>Dunnage Rack Location</b>	None
<b>Miscellaneous Text (TBHH)</b>	None

#### Tool Boxes

---

<b>Type of Tool Box</b>	Aluminum, 24" Wide x 24" High x 60" Long, Double Door
<b>Tool Box Mounting Location</b>	R/S BEHIND LANDING GEAR
<b>Tool Box Door Hinge Location</b>	Hinged at Sides

#### Side Winch and Tarp Restraint



<b>Quantity of Fixed Winches Mounted between Crossmembers</b>	None
<b>Quantity of Fixed Undermount Winches In Bay-Area</b>	None
<b>Quantity of Sliding Winches</b>	Twenty-six
<b>Sliding Winch Track</b>	Both Sides (Curbside and Roadside) Sliding Winch Track, Double "L"
<b>Winch Track Length (Slide)</b>	Unitized Track Extruded into Siderail
<b>Sliding Winch Type</b>	Canadian-style 3 -bar Winch
<b>Winch Strap Type (Sliding Winches)</b>	None
<b>Winch Strap Quantity (Sliding Winches)</b>	None
<b>Miscellaneous Text (TBCC)</b>	SLIDING ROPES HOOKS ON SIDE, "J" HOOKS .63" STEEL - 26 OPPOSITE WINCHES.

#### Suspension

---

<b>Model of Suspension</b>	Hendrickson AAZNT Platform Slider
<b>Axle Type</b>	Hendrickson Tapered Spindle Standard Wall
<b>Ready-to-Roll Wheel End</b>	None
<b>Bogie Location</b>	ENSURE TRAILER CAN MEET RTAC COMPLIANCE (41FT FROM KP TO CENTER OF TANDEM)
<b>Locking Mechanism</b>	Air-Assist Pin Release
<b>Dump Valve</b>	Manual Dump Valve w/Weatherproof Box and Liquid Air Pressure Gauge
<b>Auxillary Dump Valve</b>	None
<b>Auxillary Dump Valve Location</b>	None
<b>Pintle Hook</b>	None
<b>Miscellaneous Text (TABL)</b>	None

#### Rear Ramps and Mud Flaps

---

<b>Mudflaps</b>	Great Dane, Ribbed Black with Logo
<b>Mudflap Mounting Location</b>	Behind Rear Axle
<b>Miscellaneous Text (TABM)</b>	None

#### Brakes, Tire Inflation Systems and Wheel Ends

---

<b>Brake Size</b>	16.50" x 7.00"
<b>Brake Actuators</b>	Great Dane Standard 2.5" Stroke
<b>Brake Lining</b>	Standard Brake Lining
<b>Brake Shoe Type</b>	Extended Service
<b>Brake Adjusters</b>	Meritor Automatic 5.50"
<b>Supplemental Brake Stroke Indicator</b>	None
<b>Dust Shield Type</b>	Great Dane Standard
<b>Tire-Inflation-System/Tire/Wheel Options</b>	Prep axle(s) for future installation of tire inflation system ( 3 Holes )
<b>Tire Inflation System Pressure</b>	None



<b>Auxiliary Pressure Check Port</b>	None
<b>Wheel Seals</b>	Platinum-Plus Performance Package
<b>Axle Spindle Nuts</b>	Zip-Torq Spindle Nut
<b>Hubcaps</b>	Aluminum Sentinel
<b>Wheel Lubricant</b>	Oil
<b>Anti-Lock Brakes</b>	Wabco 2S/1M Easy Stop
<b>Optional Diagnostic Cable</b>	None
<b>Brake Valves</b>	Sealco
<b>Air-Tank Drain Valve</b>	Manual
<b>Hubodometer YN</b>	None
<b>Miscellaneous Text (TABN)</b>	None
<b>Tires / Wheels / Hubs and Drums</b>	
<b>Rim/Disc Wheel Size</b>	22.5" X 8.25"
<b>Hub/Wheel And Drum</b>	Great Dane Hub Piloted Universal 10 Stud Hub with Outboard Cast Drums
<b>Brake Drum Balancing</b>	None-Not Balanced
<b>Wheel Type</b>	22.5" Steel Disc Wheels With Aluminum Disc Wheels Outboard, Hub Piloted
<b>Wheel/Rim Vendor</b>	Great Dane Steel/Great Dane Aluminum
<b>Wheel Stud Options</b>	Long Studs for Future Alum Wheels
<b>Wheel Spacer (Corrosion Barrier)</b>	Spacer between Inner and Outer Disc Wheels
<b>Tire Size</b>	11R 22.5
<b>Tire Brand</b>	Bridgestone Ecopia R123 (G)
<b>Miscellaneous Text (TABO)</b>	None
<b>Electrical</b>	
<b>Exterior Light Package</b>	All Lights LED, Grote Long Life Light System, Grote MicroNova Dot Lamps
<b>Type of Clearance Lights</b>	Grote, LED MicroNova Dot Lamps with Dual Intensity ID Lamps
<b>Electrical Connector Type</b>	Great Dane Standard 7-Way Split Pin
<b>Side Bottom Lights</b>	3 Each Side (Front, Rear, and standard Midship Combination)
<b>Side Bottom Light Locations</b>	Evenly spaced Front to Rear
<b>Buckplate Light Type</b>	Grote Series 40, LED Flange Mount
<b>Buckplate Lights Qty &amp; Loc</b>	2 Each Side
<b>Midship Turn Signal</b>	Grote LED Combination Turn and Clearance
<b>Location of Turn Signal</b>	Roadside and Curbside, Center of Trailer
<b>Installation of Turn Signal</b>	Attach To Bottom Of Crossmember
<b>Supplemental Turn Signal</b>	None
<b>Type of Supplemental Turn-Signal</b>	None
<b>Location of Supplemental Turn Signal</b>	None



<b>Installation of Supplemental turn Signal</b>	None
<b>Miscellaneous Text (TABP)</b>	INSTALL 4-WAY PLUG AT REAR OF TRAILER
<b>Miscellaneous Text (TBDD)</b>	None

**Finish/Paint/Decal**

<b>Paint</b>	Black, Urethane
<b>Wheel Finish</b>	White Steel, Standard Finish Aluminum Outboard
<b>Conspicuity Treatment Location</b>	Great Dane on Siderails
<b>Manufacturer's Logo Installation</b>	Red Logos
<b>Installation Of Customer Decals</b>	None
<b>Exterior Unit Numbers</b>	None
<b>Miscellaneous Text (TABR)</b>	None
<b>Miscellaneous Text (TBFF)</b>	None
<b>Miscellaneous Text (TBGG)</b>	None

**Calculated Values**

<b>CARB Compliance Year</b>	2021
-----------------------------	------

**Geometric Dimensions**

<b>Packaged Options</b>	None
-------------------------	------

**Floor**

<b>Special Floor Rating</b>	None
-----------------------------	------

**Rear Ramps and Mud Flaps**

<b>Mudflap Quantity/Bracket Material</b>	1-Pair
------------------------------------------	--------

**Tires / Wheels / Hubs and Drums**

<b>Spare Tire</b>	None
-------------------	------

Miscellaneous Text (TABP) - INSTALL 4-WAY PLUG AT REAR OF TRAILER EENID-131677-3	BOMID-423595	CPQ-
Tool Box Mounting Location - R/S BEHIND LANDING GEAR EENID-131677-4	BOMID-423596	CPQ-
Bogie Location - ENSURE TRAILER CAN MEET RTAC COMPLIANCE (41FT FROM KP TO CENTER OF TANDEM) EENID-131677-2	BOMID-423597	CPQ-
Miscellaneous Text (TBCC) - SLIDING ROPES HOOKS ON SIDE, "J" HOOKS .63" STEEL - 26 OPPOSITE WINCHES. EENID-131677-1	BOMID-423598	CPQ-