		ORDER ARNE'S					
		QUOTE					
Date:		Version #22 -August 29 2022 Sales Person:					
End User:		Customer PO:					
Work Order Number:		Request Delivery Date:					
Advantage Tri Axle LXG 3 F	lopper						
o/a Height	10' 4" with 12" Planks						
o/a Length	39' 10 3/4"						
Axle spread	60"						
King pin setting	15"	Picture of End Dump					
King pin height	49 1/4"	Picture of End Dump					
RTAC compliant	Yes						
Base spec / to base model							
Body Capacity with 12" boards	- 28.1 cubic yard capacity						
Cylinders - 8" bore 21" stroke a	ir cylinder						
Front & Back Slopes - 10 gauge	50W steel						
Box Sides - 10 gauge 50 W stee	I						

Top Rail - 3"X 3" steel tube top rail

ABS 2 sensor, 1 module

Axles - 77 " track, 25,000 pound capacity per axle

Tires - BF Goodrich, ST576, 11Rx22.5 radial tires

Suspension - Intraax AA250 Air Ride, 25000lb capacity per suspension

Wheels - Unimount 10 hole with light weight hubs and drums, 8.25x22.5

CATEGORY		Weight	PART NUMBER
SUSPENSION Air Ride 1 axle auto deploy lift kit 2 axle auto deploy lift kit (simultaneous)	Lift Location		HH03250
2" x 6" Wood planks X 2" x 12" Wood planks TARPS	Tarp Colour - If colour is not specified tarp will		HA0901A
X Mesh - cable style - 12" hoops Vinyl - Cable style - 12" hoops Electric tarp kit for cable style Dura Flip Mesh Tarp Dura Flip Mesh Electric Tarp	be black		A2X4640109
Incandesent Lights LIGHT x LED lights			A2XLED
TIRES AND RIMS 11R22.5 Tires 11R24.5 Tires X Cooper Road Master RM 230 HH Steel wheels unless otherwise noted			A9X1611006
Steel Aluminum look-alike Aluminum Machined Aluminum Polished			

CATEGORY			Weight	PART NUMBER
Work Order #			•	
MUDFLAPS				
Mud flaps, bank of 2 off bumper				
Mud Flaps, bank of 4 in front of suspension				
<u>OPTIONS</u>				
Backup Alarm				
Hubodometer for 22.5 tire (installed o		KMs		
Hubodometer for 24.5 tire (installed on drivers side)		KMs		
Push Block bolt on style				
Individual Gate Controls				
Shock Straps for Tri Axle				
Remote grease system for Tri Axle				
Vibrator, 12 volt DC3500 Electric				
Ladder, front mounted X gate hopper				
Manitoba Safety Inspection				
PDI CLICTED COTIO	ONIC			
QUOTED OPTIONS				
X Cover Mac Valves Complet	ely with Alum			
Std. Colour				
White CLR 21971				
Silver CLR 17752				
Black CLR 14808				
Didek CEN 14000	COLOUR	PAINT CODE		
Colour		1		
Board colour	BLACK			
Stripe				
Tier				
			18539.6	LBS
NOTES:				
	-			
	Purchaser's Signature _			_ Date