SCHEDULE DATE: ITEM#

CUSTOMER:	Maxim	DATE:	7/7/21	SERIAL #	
	Keri	BODY	SPECIFICATIONS		Qty 1 ref 49122
Length	35' - 6"			Body	
Width	96" Inboard / 102" Chassis	Tarp	NONE	Accessories	SPRAY SKIRTS AT REAR
Side Height	56" (52" + 4")	Bow Holders	NONE		OVER SUSPENSION
Top Rail	4-1/2"	Tarp Bows	NONE		
Side Matl-front	30'100 WALL	Tarp Basket	NONE		
-middle	XXXXXX	Tarp Hooks	NONE		TAILGATE
-rear	6'140 WALL	Bulkhead Mat'l	1/4"	Height	FULL - GENESIS
Side Options	NONE	Bulkhead	SLOPED NOSE	Mat'l Thkness	.140 WALL
Floor Mat'l	1/4" (6)	Options		Slope	8"
	FLOOR LENGTH 33' - 4"	Body Fenders	YES, 14"	Hinges	OVERSLUNG
Crsmbr Spacing	12"	Ladders (Out)	NONE ON BULKHEAD	Side Swing	NONE
			LAST PANEL D/S	Gateseal	NONE
Floor Options	STUB LONGITUDINALS	Inside	NONE ON BULKHEAD		
			ONE LAST PANEL D/S	Safety Latch	ONE EACH SIDE
		Shovel Hgr	NONE		
Tailgate Control	AIR / FRAME + ELEC CC			Coal/Grain Door	NONE
Body Pkg	NONE	Light Panel	NONE - 1/4" REAR SKIRT		
Options				Coal Chute	NONE
Vibrator	NONE	Marker Lights	LED - 3 PR BOTTOM (1)	Gate Options	40" SPREADER CHAINS (5)
Mudflaps	STD+	MMTS	BELOW RAIL - LED		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
	ACROSS REAR CHASSIS	Apron	NONE		
		•	CHASSIS SPECIFICATIONS		
Model	TRI-AXLE	ABS	4S/2M	Tire Carrier	NONE
Beam Mat'l	ALUMINUM (6)			Landing Gear	DROP STAND (2) (4)
Length	34' - 6"				STEEL, LOAD BEARING
Width	102"	Independ. Susp(s)	N/A	Chassis Lights	OO ooo OO LED LIGHTS
Hoist	85-265				USE S/S RINGS
Chassis Neck	STD			Elec Coupler	7 WAY + 6 WAY
King Pin Setting	14" (2)	Distance:	N/A		
5th Whi Plate	3/8"	From:	N/A	Hyd Tank	NONE
5th Whl Ht	49"			Hyd Hose Fitting	MALE BRASS
Overhang	6"	Controls	N/A	Hyd Hose Length	NONE
Rear Axle Setting	21-1/2"			Tow Hooks	TWO - ONE EACH SIDE
K/P To Rear Axle	378-1/2"			Paint	SILVER
Suspension	AAT30K / E3-2-1	Location	N/A		
Susp Control	FRAME SWITCH + ELEC CC	Axle(s)	N/A		NONE
Susp Spacing	60" - 60"				
Susp Options	SEE NOTE (2) (3)	Accessories	N/A	Chassis Options:	
Springs	AIR			-	
Axles	TQ	Brakes	N/A		MUDFLAP ON CHASSIS
Accessories	NONE	Drums	N/A		
Brakes	16-1/2" x 7"		N/A		
Drums	CAST				
Hubs	10 S LWSTEEL - PIL	Wheels	N/A		
Wheels	(12) 22.5" AL HIGH POLISH	Tires	N/A		
Tires	11R 22.5 R196A				
REMARKS:					

## REMARKS:

- (1) INSTALL ONE 2" REAR POST MARKER LIGHT AS OUTSIDE CLEARANCE LIGHT. REF: 49122
- (2) USE HDPE INSULATORS.
- (3) INSTALL FLUSH MOUNT AIR GAUGE (KG) ON FRONT OF CHASSIS NEXT TO GLAD HAND ON D/S FROM SUSPENSION AIR BAGS.
- (4) TUBE STYLE REGISTRATION HOLDER MOUNTED ON D/S NEXT TO LANDING GEAR.
- (5) Spreader chains bolted to the longitudinals, & keyholes on the gate @ 53".
- (6) INSTALL FRONT BODY GUIDES 041-70015 ECN # 1006

REFERENCE 49122

SALESPERSON: Randy Kinder PRICING GOOD FOR 15 DAYS WEIGHT: 13,296