



SINGLE DROP PLATFORM TRAILER

SCHEDULE DATE: _____

CUSTOMER: **MAXIM** DATE: **2/6/24** SERIAL# _____

LENGTH:	53' - 11' UPPER / 42' LOWER / 26" DROP	SUSPENSION:	AANL23K / E3-2-1 - TRIDEM
WIDTH:	102"		RIGHT WEIGH GAUGE (Kg) (2)
NOSE:	SQUARE CORNERS	LOWERING KIT:	MANUAL w/ FRM SWTICH (2)
	FOUR STAKE POCKETS w/ TARP BAR	AXLE TO AXLE:	60"-60"
KING PIN SETTING:	18"	AXLE TO REAR:	66" RTAC
FLOOR:	STD KNURLED - 3 WOOD NAILERS	LIFT / AXLE:	NONE
	3 PAIR KNEE BRACES - STD	SPACING:	
	Integrated + Inside Tie Down Track (6)	F.W. HEIGHT:	46"
XMEMBER SPACING:	16"	CONTROLS:	
COIL PACKAGE:	YES - BASIC	AXLES:	TP SPINDLES
SPOOLS:	DOUBLE	AUTO SLACKS:	STD
POCKETS:	HD	BRAKES:	16-1/2" X 7" EXTENDED LIFE LINNING
ROPE HOOKS:	FOUR ACROSS THE REAR	ABS SYSTEM:	4S-2M WABCO
TIE DOWNS:	10 PR w/ TWO STORAGE @ D/S LG		ADD TIREMAAX-PRO
MARKER LIGHTS:	LED - 5 PR MODEL 33 (7)	HUBS:	10 S LIGHTWEIGHT / LWBD - PILOTED
MID TURN SIGNAL:	LED - BELOW RAIL		ADD TIREMAAX-PRO
LIGHT PANEL:	LED -000 S 000 S 000 (1) (2) (3)	WHEELS:	8.25 x 22.5 ALUM CB
	FULL WIDTH BUMPER		
	EXTRA 4 WAY PLUG IN REAR (5) &(2)	TIRES:	255/70R 22.5 BRIDGESTONE R250 16 PLY
BULKHEAD:	NONE	LANDING GEAR:	2 SPEED JOST ALUMILIGHTX
TYPE:			D/S CRANK
HEIGHT:		TIRE CARRIER:	NONE
RETURNS:		TOOLBOX: QTY:	NONE
MAT'L:		SIZE:	
ACCENT TAPE:	NONE	LOCATION:	
PAINT:	BLACK	MAT'L:	
WINCH TRACK:	INTEGRATED BOTH SIDES (3)	MUDFLAPS:	STD @ REAR
	NO WINCH CUTOUTS	TYPE:	
LOCATION:	WINCHES REMOVE @ WHEEL OPENINGS	LOCATION:	
WINCHES:	22 SLIDING STEEL 3-BAR (4)		
WINCH CLIPS:	22 SLIDING J HOOKS OPPOSING		
STRAPS:	NONE		

REMARK

1) S=STROBES WIRED TO Clearance CIRCUIT w / SWITCH IN CLOSURE BOX.

2) INSTALL POLYCARBONATE ENCLOSURE BOX - AT LANDING GEAR -DS. LOCATE IN THE BOX LOWERING KIT FRAME SWITCH RIGHT WEIGHT AIR GAUGE (TO READ KG's) AND STROBE LIGHT SWITCH - **INTERRUPT SWITCH FOR RED PIN ON 4 WAY PLUG**

3) NO GUSSET ON SIDE RAILS AT REAR - WANT TO INSTALL WINCHES AS FAR ON THE REAR RAIL AS POSSIBLE.

4) 5 LOW PROFILE 3 - BAR WINCHES ON UPPER DECK (17 LOWER). ALL WINCHES AND HOOKS STAGGERED SIDE TO SIDE.

5) WIRE TO CLEARANCE LIGHTS. **LOCATE THE INTRRUPT SWITCH IN THE BOX AT THE LANDING GEAR D/S AND LABEL "4 WAY AUX"**

6) INSTALL INSIDE TIE DOWN TRACK

7) INSTALL TWO PAIR OF WIDE LOAD PULL OUT LIGHTS. ONE SET AT THE REAR -- ONE SET AT THE TRANSITION FROM THE LOWER THE LOWER DECK TO THE UPPER DECK. WIRE INTO THE MARKER LIGHTS - INSTALL SWITCH IN THE ENCLOSURE BOX

SALESPERSON: PAUL
WEIGHT: 11694