



Order #: 166917

Order Name: All Steel Flat - QTY 6 - 05.04.21

Order Revision #: 0

Dealer/Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL

Date: 5/20/2021

Contact: MAXIM TRANSPORTATION SERVICES INC

Requested Date: 9/24/2021

Sales Person: Tom Klassen

Dealer/Branch P.O: 6

Dealers Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL

Customer #: 91870

Dealers Customer #: 91870

Customer P.O: 3095

itm	Product	Reference #	Name	Model #	Qty
1	FSP - Steel Platform	C-133794	Stock - Steel Decks - QTY 6 05/04/21	FSP-0026-00053	6

Line Item 1

Configuration Reference #: C-133794

Configuration Name: Stock - Steel Decks - QTY 6 05/04/21

FG Item: 222482067

Product: FSP - Steel Platform

Model #: FSP-0026-00053

Mode of Transportation: Customer Pick-Up

Product

Product FSP - Steel Platform

Manufacturing Plant Huntsville, TN

Model Year 2022

Geometric Dimensions

CARB/GHG Phase 2 CARB/GHG2 compliance not required.

Serial Identification Canadian and U.S. Certification

Overall Length 53' 0"

Overall Width 102.00"

Upper Coupler Height 48"

Kingpin Location 24.00"

Landing Gear Location 106.0" From Kingpin

Undercarriage Design Tridem Axle, Slide Air-Ride Suspension, 60" Axle Centers

Miscellaneous Text (TABA) None

Front

Front Corner Type Diagonal Platform Trailer Corner



Telematics / Tracking System	None
Telematics System Installation Detail	None
Electrical Connector and Gladhand Location	Near Center Front
Hose Couplers (Gladhands)	Great Dane Control and Supply with Urethane Seals
Document Holder	Tite Seal #158 Located at Landing Gear Crossmember Roadside
Additional Manifest Box	None
Additional Manifest Box Location	None
Stake Pockets Front	Five
Front Stake Pockets Material and Size	0.25 Steel, 7.00" Deep with 4" x 3.88" ID Opening
Miscellaneous Text (TABB)	None

Front Bulkhead

Bulkhead Type	None
Bulkhead Design	None
Side Kit Modification	None
Tarp Tie Bar	None
Chain Rack	None
Miscellaneous Text (TBAA)	None

Tarp Restraint Front

Tarp Restraint (Rope Hook) Location, Front	None
Front Rope Hook Type	None
Front Rope Hook Quantity	None
Rope Hook Installation, Front	None
Rope Hook Spacing	None
Miscellaneous Text (TABZ)	None

Side Exterior and Structural

Side Rail Type	6" Deep 8.2# Structural Channel
Side Stake Pockets	Outside
Stake Pockets Material and Size Side	Steel 0.19" x 1.81" x 3.38" Inside x 3" Deep
Stake Pockets Spacing	24" Centers
Stake Pocket Location	0.38" Below Top of Side Rail
Rub Rail Type	0.25" X 2.00"
Rub Rail Location	Centered on Stake Pocket
Spool Quantity	Single
Miscellaneous Text (TBBB)	None

Rear

Buckplate Material	Carbon Steel
Rear Stake Pockets	Five
Stake Pocket Material and Size Rear	Steel, .019" X 1.81" Inside X 3.38" Inside X 3" Deep



Filler Plate	Aluminum
Rear Bumpers	Rubber Blocks, 1 Pair at Rear Corners
Rear Impact Guard	Carbon Steel Rear Impact Guard
Tag Bracket Location	None
License Plate Installation	None
Tarp Restraint (Rope Hook) Location, Rear	None
Rear Rope Hook Type	None
Rear Rope Hook Quantity	None
Rear Rope Hook Installation	None
Rear Rope Hook Spacing	None
Miscellaneous Text (TABE)	None

Floor

Type of Floor	Apitong 1.13"
Floor Cargo Restraint Type	None
Floor Cargo Restraint Quantity	None
Floor Cargo Restraint Location	None
Miscellaneous Text (TABH)	None

Understructure

Upper Coupler Type	Unitized
Bottom Plate Thickness	0.38"
Landing Gear	GD65
Landing Gear Foot / Shoe Type	10" X 10" Cushion Foot
Landing Gear Handle Location	Roadside
Tire Carrier	None
Mainbeam Flanges	0.50" x 5.00" Top; 0.63 x 5.00" Bottom
Bay Area Crossmembers	4" Steel I-Beam on 16" Centers
Extra Crossmembers	None
Tool Box Quantity	One
Dunnage Rack	None
Dunnage Rack Location	None
Miscellaneous Text (TBHH)	None

Tool Boxes

Type of Tool Box	Aluminum, 24" Wide x 24" High x 60" Long, Double Door
Tool Box Mounting Location	R/S BEHIND L/G
Tool Box Door Hinge Location	Hinged at Sides

Side Winch and Tarp Restraint

Quantity of Fixed Winches Mounted between Crossmembers	None
---------------------------------------------------------------	------



Quantity of Fixed Undermount Winches In Bay-Area	None
Quantity of Sliding Winches	None
Miscellaneous Text (TBCC)	INSTALL (25) LOW-PROFILE WINCHES WELDED TO BODY BORDER UNDER RUB-RAIL POINTING OUTWARD. EQUALLY SPACE AND STAGGER WINCHES STARTING 2FT FROM NOSE AND APPROX EVERY 2FT. ENSURE THAT SPLINE LOCKS FALL FROM THE TOP AND WINCHES AND "C" HOOK LOCATIONS DO NOT INTERFERE WITH PIPE SPOOLS. MAINTAIN ADEQUATE CLEARANCE BETWEEN SPOOLS, STAKE POCKETS AND WINCHES.

Suspension

Model of Suspension	Hendrickson AAZNT Platform Slider
Axle Type	Hendrickson Tapered Spindle Standard Wall
Ready-to-Roll Wheel End	None
Bogie Location	48" Slide Travel (Minimum)
Locking Mechanism	Air-Assist Pin Release
Dump Valve	Manual Dump Valve w/Weatherproof Box and Liquid Air Pressure Gauge
Auxillary Dump Valve	None
Auxillary Dump Valve Location	None
Pintle Hook	None
Miscellaneous Text (TABL)	None

Rear Ramps and Mud Flaps

Mudflaps	Great Dane, Ribbed Black with Logo
Mudflap Mounting Location	Behind Rear Axle
Miscellaneous Text (TABM)	None

Brakes, Tire Inflation Systems and Wheel Ends

Brake Size	16.50" x 7.00"
Brake Actuators	Great Dane Standard 2.5" Stroke
Brake Lining	Standard Brake Lining
Brake Shoe Type	Extended Service
Brake Adjusters	Meritor Automatic 5.50"
Supplemental Brake Stroke Indicator	None
Dust Shield Type	Great Dane Standard
Tire-Inflation-System/Tire/Wheel Options	Prep axle(s) for future installation of tire inflation system (3 Holes)
Tire Inflation System Pressure	None
Auxiliary Pressure Check Port	None
Wheel Seals	Platinum-Plus Performance Package
Axle Spindle Nuts	Zip-Torq Spindle Nut



Hubcaps	Aluminum Sentinel
Wheel Lubricant	Oil
Anti-Lock Brakes	Wabco 2S/1M Easy Stop
Optional Diagnostic Cable	None
Brake Valves	Sealco
Air-Tank Drain Valve	Manual
Hubodometer YN	None
Miscellaneous Text (TABN)	None
Tires / Wheels / Hubs and Drums	
Rim/Disc Wheel Size	24.5" X 8.25"
Hub/Wheel And Drum	Great Dane Hub Piloted Universal 10 Stud Hub with Outboard Cast Drums
Brake Drum Balancing	None-Not Balanced
Wheel Type	24.5" Steel Disc Wheel, Hub Piloted, 5HH
Wheel/Rim Vendor	Great Dane
Wheel Stud Options	Long Studs for Future Alum Wheels
Wheel Spacer (Corrosion Barrier)	None
Tire Size	11R 24.5
Tire Brand	Bridgestone R196A (G)
Miscellaneous Text (TABO)	None
Electrical	
Exterior Light Package	All Lights LED, Grote Long Life Light System, Grote MicroNova Dot Lamps
Type of Clearance Lights	Grote, LED MicroNova Dot Lamps with Dual Intensity ID Lamps
Electrical Connector Type	Great Dane Standard 7-Way Split Pin
Side Bottom Lights	3 Each Side (Front, Rear, and standard Midship Combination)
Side Bottom Light Locations	Evenly spaced Front to Rear
Buckplate Light Type	Grote Series 40, LED Flange Mount
Buckplate Lights Qty & Loc	3 Each Side, Stop/Tail/Red Turn
Midship Turn Signal	Grote LED Combination Turn and Clearance
Location of Turn Signal	Roadside and Curbside,Center of Trailer
Installation of Turn Signal	Attach To Bottom Of Crossmember
Supplemental Turn Signal	None
Type of Supplemental Turn-Signal	None
Location of Supplemental Turn Signal	None
Installation of Supplemental turn Signal	None
Miscellaneous Text (TABP)	Install 4-Way Plug at Rear of Trailer
Miscellaneous Text (TBDD)	None
Finish/Paint/Decal	
Paint	Black, Urethane



Wheel Finish	White Powder Coat
Conspicuity Treatment Location	Great Dane on Siderails
Manufacturer's Logo Installation	Red Logos
Installation Of Customer Decals	None
Exterior Unit Numbers	None
Miscellaneous Text (TABR)	None
Miscellaneous Text (TBFF)	None
Miscellaneous Text (TBGG)	None

Calculated Values

CARB Compliance Year	2021
-----------------------------	------

Geometric Dimensions

Packaged Options	None
-------------------------	------

Floor

Special Floor Rating	None
-----------------------------	------

Rear Ramps and Mud Flaps

Mudflap Quantity/Bracket Material	1-Pair
------------------------------------------	--------

Tires / Wheels / Hubs and Drums

Spare Tire	None
-------------------	------

Miscellaneous Text (TABP) - Install 4-Way Plug at Rear of Trailer EENID-133794-2	BOMID-429348	CPQ-
Tool Box Mounting Location - R/S BEHIND L/G EENID-133794-3	BOMID-429349	CPQ-
Miscellaneous Text (TBCC) - INSTALL (25) LOW-PROFILE WINCHES WELDED TO BODY BORDER UNDER RUB-RAIL POINTING OUTWARD. EQUALLY SPACE AND STAGGER WINCHES STARTING 2FT FROM NOSE AND APPROX EVERY 2FT. ENSURE THAT SPLINE LOCKS FALL FROM THE TOP AND WINCHES AND "C" HOOK LOCATIONS DO NOT INTERFERE WITH PIPE SPOOLS. MAINTAIN ADEQUATE CLEARANCE BETWEEN SPOOLS, STAKE POCKETS AND WINCHES. EENID-133794-1	BOMID-429350	CPQ-