



Order #: 170420-1

Order Name: GD Tandem Dry Vans x10 WinMar Sept 29 2022

Order Revision #: 1

Dealer/Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL

Date: 11/16/2022

Contact: MAXIM TRANSPORTATION SERVICES INC

Requested Date: 04/07/2023

Sales Person: Unknown

Dealer/Branch P.O: 6-3329

Dealers Customer: WIN MAR FREIGHT SYSTEMS LTD (WINNIPEG,MB

Customer #: 91870

Dealers Customer #: 152063

Customer P.O: 6-3329

Itm	Product	Reference #	Name	Model #	Qty
1	CS1 - Champion 101	C-161273	***Built as of 18 Dec 2015*** Copy of C-158635	CS1-1314-21053	20

Line Item 1

Configuration Reference #: C-161273

Configuration Name: ***Built as of 18 Dec 2015*** Copy of C-158635

FG Item: 242150530

Product: CS1 - Champion 101

Model #: CS1-1314-21053

Mode of Transportation: Customer Pick-Up

Product

Product	CS1 - Champion 101
Manufacturing Plant	Brazil, IN
Model Year	2024

Geometric Dimensions

CARB/GHG Phase 2	CARB/GHG2 compliance not required.
Packaged Options	None
Serial Identification	Canadian and U.S. Certification
Overall Height	13' 6"
Overall Length	53' 0"
Overall Width	102.36"
Upper Coupler Height	47"
Kingpin Location	36.00"
Landing Gear Location	98.5" From Kingpin
Wedge	1.00" Wedge
Undercarriage Design	Tandem Axle, Slide Air-Ride Suspension, 49" Axle Centers
Miscellaneous Text (TAB A)	None

Front

Front Corner Type	4.7" Extruded Aluminum Radius
-------------------	-------------------------------

Great Dane LLC

1 of 7



Front Corner Sheet	0.125" Extruded Aluminum Mill Finish
Front Corner Protectors	None
Front Sheets	Aluminum, 0.050"
Front Upright	Four (4) 16ga STL, 2.5" Hats
Front Vents	Front Vent with Access System
Quantity and Type of Front Vent	One Swing Vent, Bottom Hinged
Location of Front Vent	Upper Roadside
Electrical Connector and Gladhand Location	Offset Roadside, Overlaid
Hose Couplers (Gladhands)	Great Dane Control and Supply with Urethane Seals
In-Line Air Filter	None
Document Holder	Great Dane Standard with Logo At Roadside Front
Additional Manifest Box	GREAT DANE STANDARD ADDITIONAL BOX
Additional Manifest Box Location	Front Lower Roadside
Miscellaneous Text (TABB)	None
Telematics	
Telematics / Tracking System	Install FleetPulse Base Telematics System
Alternative Telematics System	...
Telematics System Install and Commission	Factory Furnished and Commissioned
Telematics System Installation Detail	Great Dane Standard Location
Telematics Data Contract	FleetPulse 1 Year Data Contract
Side Exterior and Structural	
Side Sheet Material	Aluminum, 0.050"
Side Sheet Texture	Flat
Side Post Type	Logistic, 0.503" Sgl-Punch "A" (14 Gauge)
Side Post Spacing	12/16/24" Centers
Bottom Rail Fasteners	0.38" Aluminum Rivets
Rub Rail Type	None
Rub Rail Location	None
Side Skylight Quantity	None
Side Skylight Location	None
External Protection Package (Lift Pads)	None
Miscellaneous Text (TABC)	None
Rear	
Rear Frame Type	EnduroGuard Swing Door Frame
Header Type	2.5" Narrow Header
Rear Liftgate	None
Rear Bumpers	Rubber Dock Bumper
Rear Impact Guard	Carbon Steel Rear Impact Guard, Bolt On Vertical, Weld On Horizontal
Dock Lock Bracing	None
Rear Access System	Fixed-Step Curbside with Two handholds located C/S Corner Post Between Hinges
Tag Bracket Location	Standard Location
License Plate Installation	None



Miscellaneous Text (TABE)	None
Rear Doors	
Rear Door Type	0.50" Composite Swing Door, Dual-Seal Gaskets, Galvanized Steel Cover Sheet
Lockrod	1 Per Door
Hinge per Door	4 Per Rear Door
Rear Door Holdback	S-Link
Rear Door Telematics Sensor	Harness Furnished with FleetPulse Base (No Sensor)
Rear Door Vent	One Swing Vent, Bottom Hinged
Rear Vent Location	rear vent location to lower middle of c/s door
Hazardous Placard	None
Haz. Mat. Placard Location	None
Miscellaneous Text (TABF)	None
Roof Options	
Roof Bows	1" Aluminum, 24"centers
Roof Sheet	Aluminum
Miscellaneous Text (TABG)	None
Floor	
Special Floor Rating	None
Type of Floor	Hardwood, Lam. 1.38"
Floor Brand	Factory Choice
Quantity of Wood Floor Screws	3 Screws per Board
Hardwood Floor Top Finish	None
Threshold Plate	Steel Diamondette, 0.125" x 12"
Miscellaneous Text (TABH)	None
Lining / Scuffband	
Side Lining	Thermoplastic Side Lining Recessed Between Uprights
Front Lining	Pine Plywood, 0.50"X48" High, 0.25" to Ceiling
Ceiling Lining	None
Unit Numbers on Lining	None
Rows of Front Scuffband	None
Rows of Side Scuffband	1 Row
Quantity of Rows of Logistic track	None
Miscellaneous Text (TABI)	None
Scuff/Logistic Track	
Type of Side Scuffband (Row One)	10" Galvanized Steel 18 guage Roll Formed
Scuffband Location (Row One)	Installed At Floor Level And Overlaid On Lining
Miscellaneous Text (TABJ)	None
Understructure	
Upper Coupler Type	3.50" Channel
Bottom Plate Thickness	0.38" with Rolled-Lip
Landing Gear	GD60
Landing Gear Foot / Shoe Type	10" X 10" Cushion Foot
Landing Gear Handle Location	Roadside



Landing Gear Lube System	No Special Lube System
Tire Carrier	None
Crossmembers Ahead of Landing Gear	Steel Hat type on 12" Centers, 2" Deep
Crossmembers Over Landing Gear	4" Steel I-Beam on 12" Centers
Bay Area Crossmembers	4" Aluminum I-Beam on 12" Centers
URG Crossmembers	4" Steel I-Beam on 12" Centers
Extra Crossmembers at Rear	None
Extra URG Rail Length	None
Miscellaneous Text (TBHH)	None

Aerodynamic Devices

Aerodynamic Fairings - Front, Gap Reducers	None
Front Fairing Color	None
Aerodynamic Fairings - Skirts, Undercarriage	Transtex Edge E-2330T
Side Fairing Color	Default White
Aerodynamic Fairings - Tails, Rear Frame Top Kits	None
Rear Fairing Color	None
Miscellaneous Text (TABK)	None

Suspension

Model of Suspension	Hendrickson ULTRAAX 40K
Axle Type	Hendrickson Tapered Spindle Standard Wall
Ready-to-Roll Wheel End	None
Locking Mechanism	Air-Assist Pin Release
Dump Valve	Manual Dump Valve w/Weatherproof Box
Pintle Hook	None
Miscellaneous Text (TABL)	None

Rear Ramps and Mud Flaps

Mudflaps	Great Dane, Smooth Black with Logo
Mudflap Quantity/Bracket Material	1-Pair
Mudflap Mounting Location	On Undercarriage
Miscellaneous Text (TABM)	None

Brakes, Tire Inflation Systems and Wheel Ends

Brake Size	16.50" x 7.00"
Brake Actuators	Great Dane Standard 2.5" Stroke
Brake Lining	Standard Brake Lining
Brake Shoe Type	Extended Service
Brake Adjusters	Haldex Automatic 5.50" SABA
Supplemental Brake Stroke Indicator	None
Dust Shield Type	Great Dane Standard
Tire-Inflation-System/Tire/Wheel Options	Hendrickson TIREMAAX PRO
Tire Inflation System Pressure	Great Dane Standard Pressure Setting
Auxiliary Pressure Check Port	None



Wheel Seals	Platinum-Plus Performance Package
Axle Spindle Nuts	Zip-Torq Spindle Nut
Hubcaps	Hubcap To Accommodate Tire Inflation System
Wheel Lubricant	Oil
Anti-Lock Brakes	Wabco 2S/2M iABS Premium
ECU Monitored Option	None
Optional Diagnostic Cable	None
Brake Valves	Sealco
Air-Tank Drain Valve	Manual
Hubodometer YN	None
Miscellaneous Text (TABN)	None
Tires / Wheels / Hubs and Drums	
Rim/Disc Wheel Size	22.5" X 8.25"
Hub/Wheel And Drum	Great Dane Hub Piloted Universal 10 Stud Hub with Outboard Cast Drums
Brake Drum Balancing	Supplied Balanced Only
Wheel Type	22.5" Aluminum Disc Wheel, Hub Piloted
Wheel/Rim Vendor	Great Dane
Wheel Stud Options	Long Studs for Future Alum Wheels
Wheel Spacer (Corrosion Barrier)	Spacer between Hub and Disc Wheel
Tire Size	11R 22.5
Tire Brand	Bridgestone Ecopia R123 (G)
Spare Tire	None
Miscellaneous Text (TABO)	None
Electrical	
Exterior Light Package	All Lights LED, Grote Long Life Light System, AMP Connector, Grote MicroNova Dot Lamps
Electrical Connector Type	Great Dane Standard 7-Way Solid Pin with 20AMP Circuit Breakers
Telematics Data Bus	CAN Bus Communications with FleetPulse Base
Front Top Rail Lights Loc	1 Top Mounted on Side and 1 Top Mounted on Front, Roadside and Curbside
Buckplate Light Type	Grote Series 40, LED Flange Mount
Buckplate Lights Qty & Loc	2 Each Side
Stainless Theft-Resistant Flange for LED Lamps	Installed on Buckplate lamps with Stainless Rivets
Rear Header Light Locations	Center Cluster of 3 with Dual Intensity Brake Indication
Top and Bottom Side Marker Lamps/ Location	Standard Lamp Package, 1 Each Side Top Rail @ Front, 1 Each Side Mid-ship Combination (req'd on trlrs 30' and over), 1 Each Side Bottom Rail @ Rear
Midship Turn Signal	Grote LED Combination Turn and Clearance
Location of Turn Signal	Roadside and Curbside, Center of Trailer
Installation of Turn Signal	Install Below Bottom rail
Supplemental Turn Signal	None
Type of Supplemental Turn-Signal	None
Location of Supplemental Turn Signal	None
Installation of Supplemental turn Signal	None
Miscellaneous Text (TABP)	None



Electrical Interior

Dome Light Quantity	None
Dome Light Vendor/Type	None
Dome Light Location Width-wise	None
Dome Light Location Length-wise	None
Domelight Switch Qty / Type / Loc	None
Miscellaneous Text (TABQ)	None

Finish/Paint/Decal

Front Finish	Pre-Painted White
Side Finish	Pre-Painted White
Rivet Color	Unpainted
Rear Frame Finish	Great Dane Gray Rear Frame with Hot Dip Galvanized Rear Impact Guard
Rear Door Finish	Pre-Painted White
Undercarriage / Frame Finish	Black Undercoat
Wheel Finish	Standard Finish
Upper Coupler Finish	Great Dane Standard Coating
Landing Gear Finish	Finish to Match Undercarriage
Upper Running Gear Finish	Great Dane Standard Coating
Conspicuity Treatment Location	Great Dane on Bottom Rail
Manufacturer's Logo Installation	Red Logos
Installation Of Customer Decals	None
Exterior Unit Numbers	None
Miscellaneous Text (TABR)	None

Calculated Values

Lock Rod Calculated Length	Champion Series DE
CARB Compliance Year	2023

Insulation

Floor Insulation	None
------------------	------

Rear Liftgate

Liftgate Preparation	None
----------------------	------

Rear Ramps and Mud Flaps

Walkramp at Rear	None
------------------	------

Calculated Values

Lock Rod Length (Calculated)	113.56
Lock Rod Stocking Compliance	This Lock Rod Length is Stocked

Additional Manifest Box - GREAT DANE STANDARD ADDITIONAL BOX		
EENID-2	BOMID-514600	CPQ-
Rear Vent Location - rear vent location to lower middle of c/s door		
EENID-3	BOMID-529842	CPQ-


