



Order #: 169894

Order Name: ALL ALUMINUM RAS - STOCK - 08.23.22 no TB

Order Revision #: 0

Dealer/Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL  
Contact: MAXIM TRANSPORTATION SERVICES INC  
Sales Person: Chris Kowaliszyn  
Dealers Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL  
Dealers Customer #: 91870

Date: 10/3/2022  
Requested Date: 04/28/2023  
Dealer/Branch P.O: 6-3308  
Customer #: 91870  
Customer P.O: 6-3308

Itm	Product	Reference #	Name	Model #	Qty
1	FXP - Aluminum Platform	C-157041	Copy of ALL ALUMINUM RAS - STOCK - 08.23.22 no TB	FXP-0029-00053	12

**Line Item 1**

Configuration Reference #: C-157041

Configuration Name: Copy of ALL ALUMINUM RAS - STOCK - 08.23.22 no TB

FG Item: 242480117

Product: FXP - Aluminum Platform

Model #: FXP-0029-00053

Mode of Transportation: Customer Pick-Up

**Product**

Product: FXP - Aluminum Platform  
Manufacturing Plant: Huntsville, TN  
Model Year: 2024

**Geometric Dimensions**

CARB/GHG Phase 2: CARB/GHG2 compliance not required.  
Serial Identification: Canadian and U.S. Certification  
Overall Length: 53' 0"  
Overall Width: 102.00"  
Upper Coupler Height: 48"  
Kingpin Location: 24.00"  
Landing Gear Location: 106.0" From Kingpin  
Undercarriage Design: CUSTOMER IS LOOKING FOR RTAC AND CALIFORNIA COMPLIANT - SLIDE REAR, FIXED FRONT AIR-SUSPENSION 61"-121" (INCLUDES 60K BOTTOM BEAM EXTRUSION)

Miscellaneous Text (TAB A): None

**Front**

Front Corner Type: Diagonal Platform Trailer Corner  
Electrical Connector and Gladhand Location: Near Center Front



<b>Hose Couplers (Gladhands)</b>	Great Dane Control and Supply with Urethane Seals
<b>Document Holder</b>	Tite Seal #158 Located at Landing Gear Crossmember Roadside
<b>Additional Manifest Box</b>	None
<b>Additional Manifest Box Location</b>	None
<b>Stake Pockets Front</b>	None
<b>Front Stake Pockets Material and Size</b>	None
<b>Miscellaneous Text (TABB)</b>	None

#### Telematics

<b>Telematics / Tracking System</b>	Install FleetPulse Base Telematics System
<b>Alternative Telematics System</b>	...
<b>Telematics System Install and Commission</b>	Factory Furnished and Commissioned
<b>Telematics System Installation Detail</b>	Great Dane Standard Location
<b>Telematics Data Contract</b>	FleetPulse 1 Year Data Contract

#### Front Bulkhead

<b>Bulkhead Type</b>	None
<b>Bulkhead Design</b>	None
<b>Side Kit Modification</b>	None
<b>Tarp Tie Bar</b>	None
<b>Chain Rack</b>	None
<b>Miscellaneous Text (TBAA)</b>	None

#### Tarp Restraint Front

<b>Tarp Restraint (Rope Hook) Location, Front</b>	None
<b>Front Rope Hook Type</b>	None
<b>Front Rope Hook Quantity</b>	None
<b>Rope Hook Installation, Front</b>	None
<b>Rope Hook Spacing</b>	None
<b>Miscellaneous Text (TABZ)</b>	None

#### Side Exterior and Structural

<b>Side Rail Type</b>	Extruded Aluminum
<b>Side Stake Pockets</b>	Outside
<b>Stake Pockets Material and Size Side</b>	Aluminum, 1.81" x 3.38" Inside x 4" Deep
<b>Stake Pockets Spacing</b>	24" Centers
<b>Stake Pocket Location</b>	0.38" Below Top of Side Rail
<b>Rub Rail Type</b>	3.00 Aluminum
<b>Rub Rail Location</b>	Centered on Stake Pocket
<b>Spool Quantity</b>	Single
<b>Miscellaneous Text (TBBB)</b>	None

#### Rear

<b>Buckplate Material</b>	Aluminum
<b>Rear Stake Pockets</b>	None
<b>Stake Pocket Material and Size Rear</b>	None
<b>Filler Plate</b>	Aluminum
<b>Rear Bumpers</b>	Rubber Blocks, 1 Pair at Rear Corners



<b>Rear Impact Guard</b>	Aluminum Rear Impact Guard
<b>Tag Bracket Location</b>	None
<b>License Plate Installation</b>	None
<b>Tarp Restraint (Rope Hook) Location, Rear</b>	None
<b>Rear Rope Hook Type</b>	None
<b>Rear Rope Hook Quantity</b>	None
<b>Rear Rope Hook Installation</b>	None
<b>Rear Rope Hook Spacing</b>	None
<b>Miscellaneous Text (TABE)</b>	None

#### Floor

---

<b>Type of Floor</b>	Alum 1.25" Safety Grip w/2 Apitong nail strips
<b>Floor Cargo Restraint Type</b>	None
<b>Floor Cargo Restraint Quantity</b>	None
<b>Floor Cargo Restraint Location</b>	None
<b>Removable Chain Tie Downs Storage Box</b>	None
<b>Miscellaneous Text (TABH)</b>	None

#### Understructure

---

<b>Upper Coupler Type</b>	Unitized
<b>Bottom Plate Thickness</b>	0.25"
<b>Landing Gear</b>	Holland Mark V
<b>Landing Gear Foot / Shoe Type</b>	12" Dia Round Foot
<b>Landing Gear Handle Location</b>	Roadside
<b>Tire Carrier</b>	None
<b>Mainbeam Flanges</b>	Extruded Aluminum Beams
<b>Bay Area Crossmembers</b>	4" Aluminum I-Beam on 16" Centers
<b>Extra Crossmembers</b>	Single Coil Package In Single Coil Area
<b>Tool Box Quantity</b>	None
<b>Dunnage Rack</b>	None
<b>Dunnage Rack Location</b>	None
<b>Miscellaneous Text (TBHH)</b>	Install Toolbox Brackets only for a 48" Tool Box on C/S and R/S behind landing gear for future tool box install

#### Side Winch and Tarp Restraint

---

<b>Quantity of Fixed Undermount Winches In Bay-Area</b>	None
<b>Quantity of Sliding Winches</b>	Twenty-four
<b>Sliding Winch Track</b>	Both Sides (Curbside and Roadside) Sliding Winch Track, Double "L"
<b>Winch Track Length (Slide)</b>	Unitized Track Extruded into Siderail
<b>Sliding Winch Type</b>	Canadian-style 3 -bar Winch
<b>Winch Strap Type (Sliding Winches)</b>	None
<b>Winch Strap Quantity (Sliding Winches)</b>	None
<b>Miscellaneous Text (TBCC)</b>	INSTALL TOTAL OF (24) SLIDING J-HOOKS: (12) WINCHES PER SIDE, PLEASE ADD (12) SLIDING J HOOKS PER SIDE STAGGERED BETWEEN WINCHES

#### Suspension



<b>Model of Suspension</b>	Hendrickson AANT 23K
<b>Axle Type</b>	Hendrickson Tapered Spindle Standard Wall
<b>Ready-to-Roll Wheel End</b>	HXL5 Hendrickson Extended-Life 5-Year System
<b>Bogie Location</b>	"California-Legal": 40 Ft. Maximum From KP To Center Of Rear Axle
<b>Dump Valve</b>	Manual Dump Valve w/Weatherproof Box and Liquid Air Pressure Gauge
<b>Auxillary Dump Valve</b>	None
<b>Auxillary Dump Valve Location</b>	None
<b>Miscellaneous Text (TABL)</b>	None

**Rear Ramps and Mud Flaps**

<b>Mudflaps</b>	Great Dane, Ribbed Black with Logo
<b>Mudflap Mounting Location</b>	Behind Rear Axle
<b>Miscellaneous Text (TABM)</b>	None

**Brakes, Tire Inflation Systems and Wheel Ends**

<b>Brake Size</b>	16.50" x 7.00"
<b>Brake Actuators</b>	Great Dane Standard 2.5" Stroke
<b>Brake Lining</b>	Standard Brake Lining
<b>Brake Shoe Type</b>	Extended Service
<b>Brake Adjusters</b>	Meritor Automatic 5.50"
<b>Supplemental Brake Stroke Indicator</b>	None
<b>Dust Shield Type</b>	Great Dane Standard
<b>Tire-Inflation-System/Tire/Wheel Options</b>	Prep axle(s) for future installation of tire inflation system ( 3 Holes )
<b>Tire Inflation System Pressure</b>	None
<b>Auxiliary Pressure Check Port</b>	None
<b>Wheel Seals</b>	Furnished with RTR Wheel End System
<b>Axle Spindle Nuts</b>	Furnished with RTR Wheel End System
<b>Hubcaps</b>	Furnished with RTR Wheel End System
<b>Wheel Lubricant</b>	Semi-Fluid Grease Furnished with RTR Wheel End System
<b>Anti-Lock Brakes</b>	Wabco 2S/2M iABS Premium
<b>ECU Monitored Option</b>	ABS Fault Codes and Mileage
<b>Optional Diagnostic Cable</b>	None
<b>Brake Valves</b>	Sealco
<b>Air-Tank Drain Valve</b>	Manual
<b>Hubodometer YN</b>	None
<b>Miscellaneous Text (TABN)</b>	None

**Tires / Wheels / Hubs and Drums**

<b>Rim/Disc Wheel Size</b>	22.5" X 8.25"
<b>Hub/Wheel And Drum</b>	Hendrickson HXL Ductile Iron Hub Piloted 10 Stud Hub With Webb Outboard Cast Drums
<b>Brake Drum Balancing</b>	Supplied Balanced Only
<b>Wheel Type</b>	22.5" Aluminum Disc Wheel, Hub Piloted
<b>Wheel/Rim Vendor</b>	Great Dane
<b>Wheel Stud Options</b>	Long Studs Furnished with HXL Wheel End System
<b>Wheel Spacer (Corrosion Barrier)</b>	Spacer between Hub and Disc Wheel
<b>Tire Size</b>	11R 22.5



<b>Tire Brand</b>	Bridgestone Ecopia R123 (G)
<b>Miscellaneous Text (TABO)</b>	None
<b>Electrical</b>	
<b>Exterior Light Package</b>	All Lights LED, Grote Long Life Light System, AMP Connector, Grote MicroNova Dot Lamps
<b>Type of Clearance Lights</b>	Grote, LED MicroNova Dot Lamps with Dual Intensity ID Lamps
<b>Electrical Connector Type</b>	Great Dane Standard 7-Way Solid Pin
<b>Telematics Data Bus</b>	CAN Bus Communications with FleetPulse Base
<b>Side Bottom Lights</b>	3 Each Side (Front, Rear, and standard Midship Combination)
<b>Side Bottom Light Locations</b>	Evenly spaced Front to Rear
<b>Buckplate Light Type</b>	Grote Series 40, LED Flange Mount
<b>Buckplate Lights Qty &amp; Loc</b>	3 Each Side, Stop/Tail/Red Turn
<b>Midship Turn Signal</b>	Grote LED Combination Turn and Clearance
<b>Location of Turn Signal</b>	Roadside and Curbside, Center of Trailer
<b>Installation of Turn Signal</b>	Attach To Bottom Of Crossmember
<b>Supplemental Turn Signal</b>	None
<b>Type of Supplemental Turn-Signal</b>	None
<b>Location of Supplemental Turn Signal</b>	None
<b>Installation of Supplemental turn Signal</b>	None
<b>Miscellaneous Text (TABP)</b>	INSTALL 4 WAY PLUG AT REAR OF TRAILER
<b>Miscellaneous Text (TBDD)</b>	None
<b>Finish/Paint/Decal</b>	
<b>Paint</b>	Black, Urethane
<b>Wheel Finish</b>	Standard Finish Inboard, Mirror Polish Dish Side Outboard
<b>Conspicuity Treatment Location</b>	Great Dane on Siderails
<b>Manufacturer's Logo Installation</b>	Red Logos
<b>Installation Of Customer Decals</b>	None
<b>Exterior Unit Numbers</b>	None
<b>Miscellaneous Text (TABR)</b>	None
<b>Miscellaneous Text (TBFF)</b>	None
<b>Miscellaneous Text (TBGG)</b>	None
<b>Calculated Values</b>	
<b>CARB Compliance Year</b>	2023
<b>Geometric Dimensions</b>	
<b>Packaged Options</b>	None
<b>GHG2 Green House Gas Compliance</b>	
<b>GHG2 Green House Gas Classification</b>	Excluded
<b>Floor</b>	
<b>Special Floor Rating</b>	None
<b>Tool Boxes</b>	
<b>Type of Tool Box</b>	None
<b>Tool Box Mounting Location</b>	None
<b>Tool Box Door Hinge Location</b>	None



Suspension

<b>Locking Mechanism</b>	None
<b>Pintle Hook</b>	None
<b>Rear Ramps and Mud Flaps</b>	
<b>Mudflap Quantity/Bracket Material</b>	1-Pair
<b>Tires / Wheels / Hubs and Drums</b>	
<b>Spare Tire</b>	None

Miscellaneous Text (TABP) - INSTALL 4 WAY PLUG AT REAR OF TRAILER		
EENID-1	BOMID-506069	CPQ-
Undercarriage Design - CUSTOMER IS LOOKING FOR RTAC AND CALIFORNIA COMPLIANT - SLIDE REAR, FIXED FRONT AIR-SUSPENSION 61"-121" (INCLUDES 60K BOTTOM BEAM EXTRUSION)		
EENID-3	BOMID-506070	CPQ-
Miscellaneous Text (TBCC) - INSTALL TOTAL OF (24) SLIDING J-HOOKS: (12) WINCHES PER SIDE, PLEASE ADD (12) SLIDING J HOOKS PER SIDE STAGGERED BETWEEN WINCHES		
EENID-4	BOMID-506071	CPQ-
Miscellaneous Text (TBHH) - Install Toolbox Brackets only for a 48" Tool Box on C/S and R/S behind landing gear for future tool box install		
EENID-2	BOMID-506072	CPQ-