



**Booking #:** 648678 **Booking Name:** MAXIM TRANSPORTATION (WINNIPEG,MB)TRL 232482039 **Booking Revision 1 #:**  
rewrite

**Dealer/Customer:** MAXIM TRANSPORTATION (WINNIPEG,MB)TRL  
**Contact:** MAXIM TRANSPORTATION SERVICES INC  
**Sales Person:** Chris Kowaliszyn  
**Dealers Customer:** MAXIM TRANSPORTATION (WINNIPEG,MB)TRL  
**Dealers Customer #:** 91870

**Expiration Date:**  
**Date:** 10/24/2022  
**Requested Date:** 04/07/2023  
**Dealer/Branch P.O.:** 6-3248  
**Customer #:** 91870  
**Customer P.O.:** 6-3248

itm	Product	Reference #	Name	Model #	Qty
1	FXP - Aluminum Platform	C-159888	Copy of C-157847	FXP-0029-00053	12

**Line Item 1**

**Configuration Reference #:** C-159888  
**Configuration Name:** Copy of C-157847  
**FG Item:** 242480313  
**Product:** FXP - Aluminum Platform  
**Model #:** FXP-0029-00053  
**Mode of Transportation:** Customer Pick-Up

**Product**

---

<b>Product</b>	FXP - Aluminum Platform
<b>Manufacturing Plant</b>	Huntsville, TN
<b>Model Year</b>	2024

**Geometric Dimensions**

---

<b>CARB/GHG Phase 2</b>	CARB/GHG2 compliance not required.
<b>Serial Identification</b>	Canadian and U.S. Certification
<b>Overall Length</b>	53' 0"
<b>Overall Width</b>	102.00"
<b>Upper Coupler Height</b>	48"
<b>Kingpin Location</b>	24.00"
<b>Landing Gear Location</b>	106.0" From Kingpin
<b>Undercarriage Design</b>	CUSTOMER IS LOOKING FOR RTAC AND CALIFORNIA COMPLIANT - SLIDE REAR, FIXED FRONT AIR-SUSPENSION 61"-121" (INCLUDES 60K BOTTOM BEAM EXTRUSION)

**Miscellaneous Text (TAB A)** None

**Front**

---

<b>Front Corner Type</b>	Diagonal Platform Trailer Corner
--------------------------	----------------------------------



<b>Electrical Connector and Gladhand Location</b>	Near Center Front
<b>Hose Couplers (Gladhands)</b>	Great Dane Control and Supply with Urethane Seals
<b>Document Holder</b>	Tite Seal #158 Located at Landing Gear Crossmember Roadside
<b>Additional Manifest Box</b>	None
<b>Additional Manifest Box Location</b>	None
<b>Stake Pockets Front</b>	None
<b>Front Stake Pockets Material and Size</b>	None
<b>Miscellaneous Text (TABB)</b>	None

#### Telematics

<b>Telematics / Tracking System</b>	Alternative Telematics System
<b>Alternative Telematics System</b>	Other
<b>Telematics System Install and Commission</b>	Factory Furnished and Commissioned
<b>Telematics System Installation Detail</b>	None, due to order rewrite
<b>Telematics Data Contract</b>	...

#### Front Bulkhead

<b>Bulkhead Type</b>	None
<b>Bulkhead Design</b>	None
<b>Side Kit Modification</b>	None
<b>Tarp Tie Bar</b>	None
<b>Chain Rack</b>	None
<b>Miscellaneous Text (TBAA)</b>	None

#### Tarp Restraint Front

<b>Tarp Restraint (Rope Hook) Location, Front</b>	None
<b>Front Rope Hook Type</b>	None
<b>Front Rope Hook Quantity</b>	None
<b>Rope Hook Installation, Front</b>	None
<b>Rope Hook Spacing</b>	None
<b>Miscellaneous Text (TABZ)</b>	None

#### Side Exterior and Structural

<b>Side Rail Type</b>	Extruded Aluminum
<b>Side Stake Pockets</b>	Outside
<b>Stake Pockets Material and Size Side</b>	Aluminum, 1.81" x 3.38" Inside x 4" Deep
<b>Stake Pockets Spacing</b>	24" Centers
<b>Stake Pocket Location</b>	0.38" Below Top of Side Rail
<b>Rub Rail Type</b>	3.00 Aluminum
<b>Rub Rail Location</b>	Centered on Stake Pocket
<b>Spool Quantity</b>	Single
<b>Miscellaneous Text (TBBB)</b>	None

#### Rear

<b>Buckplate Material</b>	Aluminum
<b>Rear Stake Pockets</b>	None
<b>Stake Pocket Material and Size Rear</b>	None
<b>Filler Plate</b>	Aluminum



<b>Rear Bumpers</b>	Rubber Blocks, 1 Pair at Rear Corners
<b>Rear Impact Guard</b>	Aluminum Rear Impact Guard
<b>Tag Bracket Location</b>	None
<b>License Plate Installation</b>	None
<b>Tarp Restraint (Rope Hook) Location, Rear</b>	None
<b>Rear Rope Hook Type</b>	None
<b>Rear Rope Hook Quantity</b>	None
<b>Rear Rope Hook Installation</b>	None
<b>Rear Rope Hook Spacing</b>	None
<b>Miscellaneous Text (TABE)</b>	None
<b>Floor</b>	
<b>Type of Floor</b>	Alum 1.25" Safety Grip w/2 Apitong nail strips
<b>Floor Cargo Restraint Type</b>	None
<b>Floor Cargo Restraint Quantity</b>	None
<b>Floor Cargo Restraint Location</b>	None
<b>Removable Chain Tie Downs Storage Box</b>	None
<b>Miscellaneous Text (TABH)</b>	None
<b>Understructure</b>	
<b>Upper Coupler Type</b>	Unitized
<b>Bottom Plate Thickness</b>	0.25"
<b>Landing Gear</b>	Holland Mark V
<b>Landing Gear Foot / Shoe Type</b>	12" Dia Round Foot
<b>Landing Gear Handle Location</b>	Roadside
<b>Tire Carrier</b>	None
<b>Mainbeam Flanges</b>	Extruded Aluminum Beams
<b>Bay Area Crossmembers</b>	4" Aluminum I-Beam on 16" Centers
<b>Extra Crossmembers</b>	Single Coil Package In Single Coil Area
<b>Tool Box Quantity</b>	Two
<b>Dunnage Rack</b>	Aluminum Undermount Dunnage Rack 108"
<b>Dunnage Rack Location</b>	Roadside Bay
<b>Miscellaneous Text (TBHH)</b>	None
<b>Tool Boxes</b>	
<b>Type of Tool Box</b>	Aluminum, 24" Wide x 24" High x 48" Long, Double Door (CamLock Style Closure)
<b>Tool Box Mounting Location</b>	Roadside and Curbside Behind Landing Gear.
<b>Tool Box Door Hinge Location</b>	Hinged at Sides
<b>Side Winch and Tarp Restraint</b>	
<b>Quantity of Fixed Undermount Winches In Bay-Area</b>	None
<b>Quantity of Sliding Winches</b>	Twenty-four
<b>Sliding Winch Track</b>	Both Sides (Curbside and Roadside) Sliding Winch Track, Double "L"
<b>Winch Track Length (Slide)</b>	Unitized Track Extruded into Siderail
<b>Sliding Winch Type</b>	Canadian-style 3 -bar Winch
<b>Winch Strap Type (Sliding Winches)</b>	None



**Winch Strap Quantity (Sliding Winches)** None  
**Miscellaneous Text (TBCC)** INSTALL TOTAL OF (24) SLIDING J-HOOKS:  
 (12) WINCHES PER SIDE, PLEASE ADD (12) SLIDING J HOOKS PER SIDE  
 STAGGERED BETWEEN WINCHES

**Suspension**

**Model of Suspension** Hendrickson AANT 23K  
**Axle Type** Hendrickson Tapered Spindle Standard Wall  
**Ready-to-Roll Wheel End** HXL5 Hendrickson Extended-Life 5-Year System  
**Bogie Location** "California-Legal": 40 Ft. Maximum From KP To Center Of Rear Axle  
**Dump Valve** Manual Dump Valve w/Weatherproof Box and Liquid Air Pressure Gauge  
**Auxillary Dump Valve** None  
**Auxillary Dump Valve Location** None  
**Miscellaneous Text (TABL)** None

**Rear Ramps and Mud Flaps**

**Mudflaps** Great Dane, Ribbed Black with Logo  
**Mudflap Mounting Location** Behind Rear Axle  
**Miscellaneous Text (TABM)** None

**Brakes, Tire Inflation Systems and Wheel Ends**

**Brake Size** 16.50" x 7.00"  
**Brake Actuators** Great Dane Standard 2.5" Stroke  
**Brake Lining** Standard Brake Lining  
**Brake Shoe Type** Extended Service  
**Brake Adjusters** Meritor Automatic 5.50"  
**Supplemental Brake Stroke Indicator** None  
**Dust Shield Type** Great Dane Standard  
**Tire-Inflation-System/Tire/Wheel Options** Prep axle(s) for future installation of tire inflation system ( 3 Holes )  
**Tire Inflation System Pressure** None  
**Auxiliary Pressure Check Port** None  
**Wheel Seals** Furnished with RTR Wheel End System  
**Axle Spindle Nuts** Furnished with RTR Wheel End System  
**Hubcaps** Furnished with RTR Wheel End System  
**Wheel Lubricant** Semi-Fluid Grease Furnished with RTR Wheel End System  
**Anti-Lock Brakes** Wabco 2S/2M iABS Premium  
**Optional Diagnostic Cable** None  
**Brake Valves** Sealco  
**Air-Tank Drain Valve** Manual  
**Hubodometer YN** None  
**Miscellaneous Text (TABN)** None

**Tires / Wheels / Hubs and Drums**

**Rim/Disc Wheel Size** 22.5" X 8.25"  
**Hub/Wheel And Drum** Hendrickson HXL Ductile Iron Hub Piloted 10 Stud Hub With Webb Outboard  
 Cast Drums  
**Brake Drum Balancing** Supplied Balanced Only  
**Wheel Type** 22.5" Aluminum Disc Wheel, Hub Piloted



<b>Wheel/Rim Vendor</b>	Great Dane
<b>Wheel Stud Options</b>	Long Studs Furnished with HXL Wheel End System
<b>Wheel Spacer (Corrosion Barrier)</b>	Spacer between Hub and Disc Wheel
<b>Tire Size</b>	11R 22.5
<b>Tire Brand</b>	Bridgestone Ecopia R123 (G)
<b>Miscellaneous Text (TABO)</b>	None
<b>Electrical</b>	
<b>Exterior Light Package</b>	All Lights LED, Grote Long Life Light System, AMP Connector, Grote MicroNova Dot Lamps
<b>Type of Clearance Lights</b>	Grote, LED MicroNova Dot Lamps with Dual Intensity ID Lamps
<b>Electrical Connector Type</b>	Great Dane Standard 7-Way Solid Pin
<b>Side Bottom Lights</b>	3 Each Side (Front, Rear, and standard Midship Combination)
<b>Side Bottom Light Locations</b>	Evenly spaced Front to Rear
<b>Buckplate Light Type</b>	Grote Series 40, LED Flange Mount
<b>Buckplate Lights Qty &amp; Loc</b>	3 Each Side, Stop/Tail/Red Turn
<b>Midship Turn Signal</b>	Grote LED Combination Turn and Clearance
<b>Location of Turn Signal</b>	Roadside and Curbside, Center of Trailer
<b>Installation of Turn Signal</b>	Attach To Bottom Of Crossmember
<b>Supplemental Turn Signal</b>	None
<b>Type of Supplemental Turn-Signal</b>	None
<b>Location of Supplemental Turn Signal</b>	None
<b>Installation of Supplemental turn Signal</b>	None
<b>Miscellaneous Text (TABP)</b>	INSTALL 4 WAY PLUG AT REAR OF TRAILER
<b>Miscellaneous Text (TBDD)</b>	None
<b>Finish/Paint/Decal</b>	
<b>Paint</b>	Black, Urethane
<b>Wheel Finish</b>	Standard Finish Inboard, Mirror Polish Dish Side Outboard
<b>Conspicuity Treatment Location</b>	Great Dane on Siderails
<b>Manufacturer's Logo Installation</b>	Red Logos
<b>Installation Of Customer Decals</b>	None
<b>Exterior Unit Numbers</b>	None
<b>Miscellaneous Text (TABR)</b>	None
<b>Miscellaneous Text (TBFF)</b>	None
<b>Miscellaneous Text (TBGG)</b>	None
<b>Calculated Values</b>	
<b>CARB Compliance Year</b>	2023
<b>Geometric Dimensions</b>	
<b>Packaged Options</b>	None
<b>GHG2 Green House Gas Compliance</b>	
<b>GHG2 Green House Gas Classification</b>	Excluded
<b>Floor</b>	
<b>Special Floor Rating</b>	None
<b>Suspension</b>	



<b>Locking Mechanism</b>	None
<b>Pintle Hook</b>	None
<b>Rear Ramps and Mud Flaps</b>	
<b>Mudflap Quantity/Bracket Material</b>	1-Pair
<b>Tires / Wheels / Hubs and Drums</b>	
<b>Spare Tire</b>	None

Miscellaneous Text (TABP) - INSTALL 4 WAY PLUG AT REAR OF TRAILER		
EENID-1	BOMID-510968	CPQ-
Undercarriage Design - CUSTOMER IS LOOKING FOR RTAC AND CALIFORNIA COMPLIANT - SLIDE REAR, FIXED FRONT AIR-SUSPENSION 61"-121" (INCLUDES 60K BOTTOM BEAM EXTRUSION)		
EENID-2	BOMID-510969	CPQ-
Miscellaneous Text (TBCC) - INSTALL TOTAL OF (24) SLIDING J-HOOKS: (12) WINCHES PER SIDE, PLEASE ADD (12) SLIDING J HOOKS PER SIDE STAGGERED BETWEEN WINCHES		
EENID-3	BOMID-510970	CPQ-
Telematics System Installation Detail - None, due to order rewrite		
EENID-4	BOMID-521572	CPQ-

Note: All Model year 2022 quotes subject to change pending legal regulations in regard to GHG2 requirements.