



Order #: 171740-2

Order Name: Composite Dry Van Stock Spec

Order Revision #: 2

Dealer/Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL
 Contact: MAXIM TRANSPORTATION SERVICES INC
 Sales Person: Unknown
 Dealers Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL
 Dealers Customer #: 91870

Date: 5/24/2023
 Requested Date: 08/25/2023
 Dealer/Branch P.O: 6-3397
 Customer #: 91870
 Customer P.O: 6-3397

| Itm | Product | Reference # | Name | Model # | Qty |
|-----|--------------------------------|-------------|--|----------------|-----|
| 1 | CCC - Champion Composite Plate | C-171501 | ***Built as of 18 Dec 2015*** Copy of C-170790 | CCC-3314-21053 | 25 |

Line Item 1

Configuration Reference #: C-171501
 Configuration Name: ***Built as of 18 Dec 2015*** Copy of C-170790
 FG Item: 242451835
 Product: CCC - Champion Composite Plate
 Model #: CCC-3314-21053
 Mode of Transportation: Customer Pick-Up

Product

| | |
|---------------------|--------------------------------|
| Product | CCC - Champion Composite Plate |
| Manufacturing Plant | Jonesboro, AR |
| Model Year | 2024 |

Geometric Dimensions

| | |
|----------------------------|--|
| CARB/GHG Phase 2 | CARB/GHG2 compliance not required. |
| Packaged Options | None |
| Serial Identification | Canadian and U.S. Certification |
| Overall Height | 13' 6" |
| Overall Length | 53' 0" |
| Overall Width | 102.36" |
| Upper Coupler Height | 47" |
| Kingpin Location | 36.00" |
| Landing Gear Location | 98.5" From Kingpin |
| Wedge | 1.00" Wedge |
| Undercarriage Design | Tandem Axle, Slide Air-Ride Suspension, 49" Axle Centers |
| Miscellaneous Text (TAB A) | None |

Front

| | |
|-------------------|-------------------------------|
| Front Corner Type | 4.7" Extruded Aluminum Radius |
|-------------------|-------------------------------|



| | |
|---|--|
| Front Corner Sheet | 0.125" Extruded Aluminum Mill Finish |
| Front Corner Protectors | None |
| Front Sheets | 0.265" WITH .016" PP GALV. STEEL SKINS |
| Front Upright | Single Bonded Joint Splice |
| Front Vents | None |
| Quantity and Type of Front Vent | None |
| Location of Front Vent | None |
| Electrical Connector and Gladhand Location | Offset Roadside, Overlaid |
| Hose Couplers (Gladhands) | Great Dane Control and Supply with Urethane Seals |
| In-Line Air Filter | None |
| Document Holder | Great Dane Standard with Logo At Roadside Front |
| Additional Manifest Box | None |
| Additional Manifest Box Location | None |
| Miscellaneous Text (TABB) | None |
| Telematics | |
| Telematics / Tracking System | Install FleetPulse Base Telematics System |
| Alternative Telematics System | ... |
| Telematics System Install and Commission | Factory Furnished and Factory Commissioned |
| Telematics System Installation Detail | Great Dane Standard Location |
| Telematics Data Contract | FleetPulse 1 Year Data Contract |
| Side Exterior and Structural | |
| Side Sheet Material | Composite Plate, 0.30" with .016" PP Galv. Steel Skins |
| Side Sheet Texture | Flat |
| Side Post Type | Logistic Post, Comp Plate Single-Punch "A" (14 Gauge) |
| Side Post Spacing | 50" Centers |
| Bottom Rail Fasteners | 0.38" Aluminum Rivets |
| Rub Rail Type | None |
| Rub Rail Location | None |
| Side Skylight Quantity | None |
| Side Skylight Location | None |
| External Protection Package (Lift Pads) | None |
| Miscellaneous Text (TABC) | None |
| Rear | |
| Rear Frame Type | EnduroGuard Swing Door Frame |
| Header Type | 2.5" Narrow Header |
| Rear Liftgate | None |
| Rear Bumpers | Rubber Dock Bumper |
| Rear Impact Guard | Carbon Steel Rear Impact Guard, Bolt On Vertical, Weld On Horizontal |
| Dock Lock Bracing | None |
| Rear Access System | Handhold Roadside Door (With RIG Intermediate Channel When Clearance Allows) |
| Tag Bracket Location | Standard Location |



| | |
|---|---|
| License Plate Installation | None |
| Miscellaneous Text (TABE) | None |
| Rear Doors | |
| Rear Door Type | 0.50" Composite Swing Door, Dual-Seal Gaskets, Galvanized Steel Cover Sheet |
| Lockrod | 1 Per Door |
| Hinge per Door | 4 Per Rear Door |
| Rear Door Holdback | S-Link |
| Rear Door Telematics Sensor | Harness Furnished with FleetPulse Base (No Sensor) |
| Rear Door Vent | None |
| Rear Vent Location | None |
| Hazardous Placard | None |
| Haz. Mat. Placard Location | None |
| Miscellaneous Text (TABF) | None |
| Roof Options | |
| Roof Bows | 1" Aluminum, 24"centers |
| Roof Sheet | Aluminum |
| Miscellaneous Text (TABG) | None |
| Floor | |
| Special Floor Rating | None |
| Type of Floor | Hardwood, Lam. 1.38" |
| Floor Brand | Factory Choice |
| Quantity of Wood Floor Screws | 3 Screws per Board |
| Hardwood Floor Top Finish | Water Repellant Coating Rear 8' |
| Threshold Plate | Steel Diamondette, 0.125" x 12" |
| Miscellaneous Text (TABH) | None |
| Lining / Scuffband | |
| Front Lining | None |
| Ceiling Lining | None |
| Unit Numbers on Lining | None |
| Rows of Front Scuffband | 1 Row |
| Rows of Side Scuffband | 2 Rows |
| Sidewall Cargo Restraint | None |
| Quantity of Rows of Logistic track | None |
| Miscellaneous Text (TABI) | None |
| Scuff/Logistic Track | |
| Type of Front Scuffband | 12" Carbon Steel Welded to Coupler, 7 Gauge |
| Front Scuffband Location | Installed at Floor Level |
| Front Scuffband Position | Overlaid |
| Type of Side Scuffband (Row One) | 5" Extruded Aluminum Integrated With Bottom Rail |
| Scuffband Location (Row One) | Installed at Floor Level |
| Type of Side Scuffband (Row Two) | 6" Galvanized Steel, 18 gauge |
| Side Scuffband Location (Row Two) | Butted to lower row |
| Miscellaneous Text (TABJ) | None |



Understructure

| | |
|---|--|
| Upper Coupler Type | 3.50" Channel |
| Bottom Plate Thickness | 0.25" with Rolled-Lip |
| Landing Gear | GD60, No-Lube, 10yr Vendor Warranty |
| Landing Gear Foot / Shoe Type | 10" X 10" Cushion Foot |
| Landing Gear Handle Location | Roadside |
| Landing Gear Lube System | No Special Lube System |
| Anti-Hook Plate | None |
| Tire Carrier | None |
| Crossmembers Ahead of Landing Gear | Steel Hat type on 12" Centers, 2" Deep |
| Crossmembers Over Landing Gear | 4" Steel I-Beam on 12" Centers |
| Bay Area Crossmembers | 4" Steel I-Beam on 12" Centers |
| URG Crossmembers | 4" Steel I-Beam on 12" Centers |
| Extra Crossmembers at Rear | None |
| Extra URG Rail Length | None |
| Miscellaneous Text (TBHH) | None |

Aerodynamic Devices

| | |
|--|-----------------------|
| Aerodynamic Fairings - Front, Gap Reducers | None |
| Front Fairing Color | None |
| Aerodynamic Fairings - Skirts, Undercarriage | Transtex Edge E-1930T |
| Side Fairing Color | Default White |
| Aerodynamic Fairings - Tails, Rear Frame Top Kits | None |
| Rear Fairing Color | None |
| Miscellaneous Text (TABK) | None |

Suspension

| | |
|-------------------------------------|--|
| Model of Suspension | Hendrickson ULTRAAK 40K |
| Axle Type | Hendrickson Tapered Spindle Standard Wall |
| Integrated Wheel End Package | RTR HXL5 Hendrickson Extended-Life 5-Year System |
| Locking Mechanism | Air-Assist Pin Release |
| Dump Valve | Hose Coupler Activated (Automatic) Dump Valve |
| Miscellaneous Text (TABL) | None |

Rear Ramps and Mud Flaps

| | |
|--|------------------------------------|
| Mudflaps | Great Dane, Smooth Black with Logo |
| Mudflap Quantity/Bracket Material | 1-Pair |
| Mudflap Mounting Location | On Undercarriage |
| Miscellaneous Text (TABM) | None |

Brakes, Tire Inflation Systems and Wheel Ends

| | |
|------------------------|------------------------------------|
| Brake Size | 16.50" x 7.00" |
| Brake Actuators | WABCO Tristop with IBV 2.5" Stroke |
| Brake Lining | Standard Brake Lining |
| Brake Shoe Type | Extended Service |



| | |
|---|---|
| Brake Adjusters | WABCO EASYFIT 5.50" SLACK ADJUSTER |
| Supplemental Brake Stroke Indicator | None |
| Dust Shield Type | Great Dane Standard |
| Tire-Inflation-System/Tire/Wheel Options | Hendrickson TIREMAAX PRO |
| Tire Inflation System Pressure | Great Dane Standard Pressure Setting |
| Auxiliary Pressure Check Port | None |
| Wheel Seals | Furnished with Integrated Wheel End System |
| Axle Spindle Nuts | Furnished with Integrated Wheel End System |
| Hubcaps | Hubcap To Accommodate Tire Inflation System |
| Wheel Lubricant | Semi-Fluid Grease Furnished with Integrated Wheel End System |
| Anti-Lock Brakes | Wabco 2S/2M iABS Premium |
| ECU Monitored Option | ABS Fault Codes and Mileage |
| Optional Diagnostic Cable | None |
| Brake Valves | Sealco |
| Air-Tank Drain Valve | Manual |
| Hubodometer YN | None |
| Miscellaneous Text (TABN) | None |
| Tires / Wheels / Hubs and Drums | |
| Rim/Disc Wheel Size | 22.5" X 8.25" |
| Hub/Wheel And Drum | Hendrickson HXL Ductile Iron Hub Piloted 10 Stud Hub With Webb Outboard Cast Drums |
| Brake Drum Balancing | Supplied Balanced Only |
| Wheel Type | 22.5" Steel Disc Wheel, Hub Piloted, 2HH |
| Wheel/Rim Vendor | Great Dane |
| Wheel Stud Options | Long Studs Furnished with HXL Wheel End System |
| Wheel Spacer (Corrosion Barrier) | None |
| Tire Size | 11R 22.5 |
| Tire Brand | Bridgestone Ecopia R123 (G) |
| Spare Tire | None |
| Miscellaneous Text (TABO) | None |
| Electrical | |
| Exterior Light Package | All Lights LED, Grote Long Life Light System, AMP Connector, Grote MicroNova Dot Lamps |
| Electrical Connector Type | Great Dane Standard 7-Way Split Pin |
| Front Top Rail Lights Loc | 1 Top Mounted on Front Corner at 45 Degrees; Roadside and Curbside (Canadian Requirement) |
| Buckplate Light Type | Grote Series 40, LED Flange Mount |
| Buckplate Lights Qty & Loc | 2 Each Side |
| Stainless Theft-Resistant Flange for LED Lamps | Installed on Buckplate lamps with Stainless Rivets |
| Rear Header Light Locations | Center Cluster of 3 with Dual Intensity Brake Indication |
| Top and Bottom Side Marker Lamps/ Location | Standard Lamp Package, 1 Each Side Top Rail @ Front, 1 Each Side Mid-ship Combination (req'd on trlrs 30' and over), 1 Each Side Bottom Rail @ Rear |
| Midship Turn Signal | Grote LED Combination Turn and Clearance |



| | |
|---|--|
| Location of Turn Signal | Roadside and Curbside,Center of Trailer |
| Installation of Turn Signal | Install Below Bottom rail |
| Supplemental Turn Signal | None |
| Type of Supplemental Turn-Signal | None |
| Location of Supplemental Turn Signal | None |
| Installation of Supplemental turn Signal | None |
| Miscellaneous Text (TABP) | None |
| Electrical Interior | |
| Dome Light Quantity | None |
| Dome Light Vendor/Type | None |
| Dome Light Location Width-wise | None |
| Dome Light Location Length-wise | None |
| Domelight Switch Qty / Type / Loc | None |
| Miscellaneous Text (TABQ) | None |
| Finish/Paint/Decal | |
| Front Finish | Pre-Painted White |
| Side Finish | Pre-Painted White |
| Rear Frame Finish | Great Dane Gray Rear Frame with Hot Dip Galvanized Rear Impact Guard |
| Rear Door Finish | Pre-Painted White |
| Undercarriage / Frame Finish | Black Undercoat |
| Wheel Finish | White Powder Coat |
| Upper Coupler Finish | Great Dane Standard Coating |
| Landing Gear Finish | Hot Dip Galvanized Wingplates, Fore/Aft Bracing and K Brace |
| Upper Running Gear Finish | Great Dane Standard Coating |
| Conspicuity Treatment Location | Great Dane on Side Sheet |
| Manufacturer's Logo Installation | Red Logos |
| Installation Of Customer Decals | None |
| Exterior Unit Numbers | None |
| Miscellaneous Text (TABR) | None |
| Calculated Values | |
| Lock Rod Product Type | Champion Series PD DE |
| CARB Compliance Year | 2023 |
| Geometric Dimensions | |
| Drop Depth | None |
| Insulation | |
| Floor Insulation | None |
| Calculated Values | |
| Side Door Y/N | 0 |
| Rear Liftgate | |
| Liftgate Preparation | None |
| Hidden | |
| Special Door Spec | Swing |
| Lining / Scuffband | |



Side Lining No Side Lining

Suspension

Pintle Hook None

Rear Ramps and Mud Flaps

Walkramp at Rear None

Calculated Values

Lock Rod Length (Calculated) 113.56

Lock Rod Stocking Compliance This Lock Rod Length is Stocked

| | | |
|---|--------------|------|
| Brake Adjusters - WABCO EASYFIT 5.50" SLACK ADJUSTER | | |
| EENID-1 | BOMID-561616 | CPQ- |
| Front Sheets - 0.265" WITH .016" PP GALV. STEEL SKINS | | |
| EENID-2 | BOMID-569503 | CPQ- |