



Booking #: 649952

Booking Name: Dry Van Stock Spec KW 10/2022

Booking Revision #: 1

Dealer/Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL
Contact: MAXIM TRANSPORTATION SERVICES INC
Sales Person: Chris Kowaliszyn
Dealers Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL
Dealers Customer #: 91870

Expiration Date:
Date: 1/5/2023
Requested Date: 04/07/2023
Dealer/Branch P.O: 6-3334
Customer #: 91870
Customer P.O: 6-3334

Itm	Product	Reference #	Name	Model #	Qty
1	CS1 - Champion 101	C-163293	***Built as of 18 Dec 2015*** Copy of C-163262	CS1-1314-21053	20

Line Item 1

Configuration Reference #: C-163293
Configuration Name: ***Built as of 18 Dec 2015*** Copy of C-163262
FG Item: 242400790
Product: CS1 - Champion 101
Model #: CS1-1314-21053
Mode of Transportation: Customer Pick-Up

Product

Product	CS1 - Champion 101
Manufacturing Plant	Kewanee, IL
Model Year	2024

Geometric Dimensions

CARB/GHG Phase 2	CARB/GHG2 compliance not required.
Packaged Options	None
Serial Identification	Canadian and U.S. Certification
Overall Height	13' 6"
Overall Length	53' 0"
Overall Width	102.36"
Upper Coupler Height	47"
Kingpin Location	36.00"
Landing Gear Location	98.5" From Kingpin
Wedge	1.00" Wedge
Undercarriage Design	Tandem Axle, Slide Air-Ride Suspension, 49" Axle Centers
Miscellaneous Text (TAB A)	None

Front



Front Corner Type	4.7" Extruded Aluminum Radius
Front Corner Sheet	0.125" Extruded Aluminum Mill Finish
Front Corner Protectors	None
Front Sheets	Aluminum, 0.050"
Front Upright	Four (4) 16ga STL, 2.5" Hats
Front Vents	None
Quantity and Type of Front Vent	None
Location of Front Vent	None
Electrical Connector and Gladhand Location	Offset Roadside, Overlaid
Hose Couplers (Gladhands)	Great Dane Control and Supply with Urethane Seals
In-Line Air Filter	None
Document Holder	Great Dane Standard with Logo At Roadside Front
Additional Manifest Box	None
Additional Manifest Box Location	None
Miscellaneous Text (TABB)	None
Telematics	
Telematics / Tracking System	Install FleetPulse Base Telematics System
Alternative Telematics System	...
Telematics System Install and Commission	Factory Furnished and Commissioned
Telematics System Installation Detail	Great Dane Standard Location
Telematics Data Contract	FleetPulse 1 Year Data Contract
Side Exterior and Structural	
Side Sheet Material	Aluminum, 0.050"
Side Sheet Texture	Flat
Side Post Type	Logistic, 0.503" Sgl-Punch "A" (14 Gauge)
Side Post Spacing	16" Centers
Bottom Rail Fasteners	0.38" Aluminum Rivets
Rub Rail Type	None
Rub Rail Location	None
Side Skylight Quantity	None
Side Skylight Location	None
External Protection Package (Lift Pads)	None
Miscellaneous Text (TABC)	None
Rear	
Rear Frame Type	EnduroGuard Swing Door Frame
Header Type	2.5" Narrow Header
Rear Liftgate	None
Rear Bumpers	Rubber Dock Bumper
Rear Impact Guard	Carbon Steel Rear Impact Guard, Bolt On Vertical, Weld On Horizontal
Dock Lock Bracing	None
Rear Access System	Handhold Roadside Door (With RIG Intermediate Channel When Clearance Allows)



Tag Bracket Location	Standard Location
License Plate Installation	None
Miscellaneous Text (TABE)	None
Rear Doors	
Rear Door Type	0.50" Composite Swing Door, Dual-Seal Gaskets, Galvanized Steel Cover Sheet
Lockrod	1 Per Door
Hinge per Door	4 Per Rear Door
Rear Door Holdback	S-Link
Rear Door Telematics Sensor	Harness Furnished with FleetPulse Base (No Sensor)
Rear Door Vent	None
Rear Vent Location	None
Hazardous Placard	None
Haz. Mat. Placard Location	None
Miscellaneous Text (TABF)	None
Roof Options	
Roof Bows	1" Aluminum, 24"centers
Roof Sheet	Aluminum
Miscellaneous Text (TABG)	None
Floor	
Special Floor Rating	None
Type of Floor	Hardwood, Lam. 1.38"
Floor Brand	Factory Choice
Quantity of Wood Floor Screws	3 Screws per Board
Hardwood Floor Top Finish	Water Repellant Coating Rear 8'
Threshold Plate	Steel Diamondette, 0.125" x 12"
Miscellaneous Text (TABH)	None
Lining / Scuffband	
Side Lining	Thermoplastic Side Lining Recessed Between Uprights
Front Lining	Pine Plywood, 0.50"X48" High, 0.25" to Ceiling
Ceiling Lining	None
Unit Numbers on Lining	None
Rows of Front Scuffband	1 Row
Rows of Side Scuffband	1 Row
Quantity of Rows of Logistic track	None
Miscellaneous Text (TABI)	None
Scuff/Logistic Track	
Type of Front Scuffband	12" Carbon Steel Welded to Coupler, 7 Gauge
Front Scuffband Location	Installed at Floor Level
Front Scuffband Position	Overlaid
Type of Side Scuffband (Row One)	10" Galvanized Steel 18 guage Roll Formed
Scuffband Location (Row One)	Installed At Floor Level And Overlaid On Lining
Miscellaneous Text (TABJ)	None
Understructure	



Upper Coupler Type	3.50" Channel
Bottom Plate Thickness	0.25" with Rolled-Lip
Landing Gear	GD60, No-Lube, 10yr Vendor Warranty
Landing Gear Foot / Shoe Type	10" X 10" Cushion Foot
Landing Gear Handle Location	Roadside
Landing Gear Lube System	No Special Lube System
Tire Carrier	None
Crossmembers Ahead of Landing Gear	Steel Hat type on 12" Centers, 2" Deep
Crossmembers Over Landing Gear	4" Steel I-Beam on 12" Centers
Bay Area Crossmembers	4" Steel I-Beam on 12" Centers
URG Crossmembers	4" Steel I-Beam on 12" Centers
Extra Crossmembers at Rear	None
Extra URG Rail Length	None
Miscellaneous Text (TBHH)	None

Aerodynamic Devices

Aerodynamic Fairings - Front, Gap Reducers	None
Front Fairing Color	None
Aerodynamic Fairings - Skirts, Undercarriage	Transtex Edge E-1930T
Side Fairing Color	Default White
Aerodynamic Fairings - Tails, Rear	None
Frame Top Kits	
Rear Fairing Color	None
Miscellaneous Text (TABK)	None

Suspension

Model of Suspension	Hendrickson ULTRAAK 40K
Axle Type	Hendrickson Tapered Spindle Standard Wall
Ready-to-Roll Wheel End	HXL5 Hendrickson Extended-Life 5-Year System
Locking Mechanism	Air-Assist Pin Release
Dump Valve	Hose Coupler Activated (Automatic) Dump Valve
Pintle Hook	None
Miscellaneous Text (TABL)	None

Rear Ramps and Mud Flaps

Mudflaps	Great Dane, Smooth Black with Logo
Mudflap Quantity/Bracket Material	1-Pair
Mudflap Mounting Location	On Undercarriage
Miscellaneous Text (TABM)	None

Brakes, Tire Inflation Systems and Wheel Ends

Brake Size	16.50" x 7.00"
Brake Actuators	WABCO Tristop with IBV 2.5" Stroke
Brake Lining	Standard Brake Lining
Brake Shoe Type	Extended Service
Brake Adjusters	WABCO EASYFIT 5.50" SLACK ADJUSTER



Supplemental Brake Stroke Indicator	None
Dust Shield Type	Great Dane Standard
Tire-Inflation-System/Tire/Wheel Options	Hendrickson TIREMAAX PRO
Tire Inflation System Pressure	Great Dane Standard Pressure Setting
Auxiliary Pressure Check Port	None
Wheel Seals	Furnished with RTR Wheel End System
Axle Spindle Nuts	Furnished with RTR Wheel End System
Hubcaps	Hubcap To Accommodate Tire Inflation System
Wheel Lubricant	Semi-Fluid Grease Furnished with RTR Wheel End System
Anti-Lock Brakes	Wabco 2S/2M iABS Premium
ECU Monitored Option	None
Optional Diagnostic Cable	None
Brake Valves	Sealco
Air-Tank Drain Valve	Manual
Hubodometer YN	None
Miscellaneous Text (TABN)	None
Tires / Wheels / Hubs and Drums	
Rim/Disc Wheel Size	22.5" X 8.25"
Hub/Wheel And Drum	Hendrickson HXL Ductile Iron Hub Piloted 10 Stud Hub With Webb Outboard Cast Drums
Brake Drum Balancing	Supplied Balanced Only
Wheel Type	22.5" Steel Disc Wheel, Hub Piloted, 2HH
Wheel/Rim Vendor	Great Dane
Wheel Stud Options	Long Studs Furnished with HXL Wheel End System
Wheel Spacer (Corrosion Barrier)	None
Tire Size	11R 22.5
Tire Brand	Bridgestone Ecopia R123 (G)
Spare Tire	None
Miscellaneous Text (TABO)	None
Electrical	
Exterior Light Package	All Lights LED, Grote Long Life Light System, AMP Connector, Grote MicroNova Dot Lamps
Electrical Connector Type	Great Dane Standard 7-Way Split Pin
Telematics Data Bus	CAN Bus Communications with FleetPulse Base
Front Top Rail Lights Loc	1 Top Mounted on Front Corner at 45 Degrees; Roadside and Curbside (Canadian Requirement)
Buckplate Light Type	Grote Series 40, LED Flange Mount
Buckplate Lights Qty & Loc	2 Each Side
Stainless Theft-Resistant Flange for LED Lamps	Installed on Buckplate lamps with Stainless Rivets
Rear Header Light Locations	Center Cluster of 3 with Dual Intensity Brake Indication
Top and Bottom Side Marker Lamps/ Location	Standard Lamp Package, 1 Each Side Top Rail @ Front, 1 Each Side Mid-ship Combination (req'd on trlrs 30' and over), 1 Each Side Bottom Rail @ Rear
Midship Turn Signal	Grote LED Combination Turn and Clearance



Location of Turn Signal	Roadside and Curbside,Center of Trailer
Installation of Turn Signal	Install Below Bottom rail
Supplemental Turn Signal	None
Type of Supplemental Turn-Signal	None
Location of Supplemental Turn Signal	None
Installation of Supplemental turn Signal	None
Miscellaneous Text (TABP)	None
Electrical Interior	
Dome Light Quantity	None
Dome Light Vendor/Type	None
Dome Light Location Width-wise	None
Dome Light Location Length-wise	None
Domelight Switch Qty / Type / Loc	None
Miscellaneous Text (TABQ)	None
Finish/Paint/Decal	
Front Finish	Pre-Painted White
Side Finish	Pre-Painted White
Rivet Color	Unpainted
Rear Frame Finish	Great Dane Gray Rear Frame with Hot Dip Galvanized Rear Impact Guard
Rear Door Finish	Pre-Painted White
Undercarriage / Frame Finish	Black Undercoat
Wheel Finish	White Powder Coat
Upper Coupler Finish	Great Dane Standard Coating
Landing Gear Finish	Hot Dip Galvanized Wingplates, Fore/Aft Bracing and K Brace
Upper Running Gear Finish	Great Dane Standard Coating
Conspicuity Treatment Location	Great Dane on Bottom Rail
Manufacturer's Logo Installation	Red Logos
Installation Of Customer Decals	None
Exterior Unit Numbers	None
Miscellaneous Text (TABR)	None
Calculated Values	
Lock Rod Calculated Length	Champion Series PD DE
CARB Compliance Year	2023
Insulation	
Floor Insulation	None
Rear Liftgate	
Liftgate Preparation	None
Rear Ramps and Mud Flaps	
Walkramp at Rear	None
Calculated Values	
Lock Rod Length (Calculated)	113.56
Lock Rod Stocking Compliance	This Lock Rod Length is Stocked



Brake Adjusters - WABCO EASYFIT 5.50" SLACK ADJUSTER		
EENID-1	BOMID-525638	CPQ-

Note: All Model year 2022 quotes subject to change pending legal regulations in regard to GHG2 requirements.
