



Order #: 169997-2 Order Name: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL 232161962 rewrite Order Revision #: 2

Dealer/Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL Date: 11/4/2022
Contact: MAXIM TRANSPORTATION SERVICES INC Requested Date: 04/07/2023
Sales Person: Unknown Dealer/Branch P.O: 6-3243
Dealers Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL Customer #: 91870
Dealers Customer #: 91870 Customer P.O: 6-3243

Table with 6 columns: Itm, Product, Reference #, Name, Model #, Qty. Row 1: 1, ESS - Everest Super Seal Reefer, C-160693, Copy of C-159655, ESS-1114-31053, 10

Line Item 1

Configuration Reference #: C-160693
Configuration Name: Copy of C-159655
FG Item: 242160229
Product: ESS - Everest Super Seal Reefer
Model #: ESS-1114-31053
Mode of Transportation: Customer Pick-Up

Product

Product: ESS - Everest Super Seal Reefer
Manufacturing Plant: Wayne, NE
Model Year: 2024

Geometric Dimensions

Foam Insulation Requirements: This Vehicle is prohibited from using HFCs in its construction by locations like California, Washington, Canada.
Foam Insulation Composition: This refrigerated vehicle contains non-HFC insulation and is compliant with State and Canadian HFC-regulations.
CARB/GHG Phase 2: CARB/GHG2 compliance not required.
Packaged Options: None
Serial Identification: Canadian and U.S. Certification
Overall Height: 13' 6"
Overall Length: 53' 0"
Overall Width: 102.36"
Upper Coupler Height: 47"
Kingpin Location: 30.00"
Landing Gear Location: 105.0" From Kingpin
Wedge: No Wedge
Undercarriage Design: Tandem Axle, Slide Air-Ride Suspension, 49" Axle Centers



| | |
|---|---|
| Miscellaneous Text (TABA) | None |
| Front | |
| Front Corner Type | 6" Extruded Aluminum Radius |
| Front Corner Sheet | Stainless Steel 0.021" |
| Front Sheets | Stainless Steel, 0.035" |
| Front Upright | Zee, Aluminum, 1.63" |
| Front Vents | None |
| Quantity and Type of Front Vent | None |
| Vent Screens | None |
| Location of Front Vent | None |
| Electrical Connector and Gladhand Location | Offset Roadside, Overlaid |
| Hose Couplers (Gladhands) | Great Dane Control and Supply with Urethane Seals |
| In-Line Air Filter | None |
| Document Holder | Great Dane Standard with Logo At Roadside Front |
| Additional Manifest Box | None |
| Additional Manifest Box Location | None |
| Miscellaneous Text (TABB) | None |
| Telematics | |
| Telematics / Tracking System | Install FleetPulse Base Telematics System |
| Alternative Telematics System | ... |
| Telematics System Install and Commission | Factory Furnished and Commissioned |
| Telematics System Installation Detail | Great Dane Standard Location |
| Telematics Data Contract | FleetPulse 1 Year Data Contract |
| Side Exterior and Structural | |
| Side Sheet Material | Aluminum, 0.040" |
| Side Sheet Texture | Corrugated |
| Side Post Type | Jay, Aluminum 1.13" |
| Side Post Spacing | 12/16/24" Centers |
| Bottom Rail Fasteners | 0.38" Aluminum Rivets |
| Rub Rail Type | None |
| Rub Rail Location | None |
| External Protection Package (Lift Pads) | None |
| Miscellaneous Text (TABC) | None |
| Rear | |
| Rear Frame Type | Stainless Steel Swing Door Frame |
| Header Type | 4" Header |
| Rear Bumpers | Rubber Dock Bumper |
| Bars Between Buckplate Lamps | Install Stainless Steel Vertical Bars Between Each Tail Lamp |
| Rear Impact Guard | Stainless Steel Rear Impact Guard, Bolt on Vertical, Weld On Horizontal |
| Rear Access System | Handhold Roadside Door (Customer Elects To Delete Intermediate Channel) |
| Tag Bracket Location | Standard Location |
| License Plate Installation | None |



| | |
|---------------------------------------|---|
| Miscellaneous Text (TABE) | None |
| Rear Doors | |
| Rear Door Type | Frame Type Swing With Triple Seal Gasket And Stainless Steel Diamond Pattern Finish Cover Sheet |
| Lockrod | 1 Per Door |
| Hinge per Door | 5 Per Rear Door |
| Rear Door Holdback | Standard |
| Rear Door Telematics Sensor | Harness Furnished with FleetPulse Base (No Sensor) |
| Floor-Door Jamb | Standard |
| Type of Scuffband on Rear Door | None |
| Rear Door Scuffband Location | None |
| Rear Door Scuffband Position | None |
| Inside Safety Release | Without Inside Safety Release |
| Rear Door Vent | One Swing Vent 5" X 15" Opening |
| Rear Vent Location | Lower Curbside |
| Rear Door Vent Screen | With Screen |
| Hazardous Placard | None |
| Haz. Mat. Placard Location | None |
| ERC Switch (Rear) | None |
| Miscellaneous Text (TABF) | None |
| Roof Options | |
| Roof Bows | 1.13" Roof Bows on 32" Centers |
| Roof Sheet | Aluminum |
| Miscellaneous Text (TABG) | None |
| Floor | |
| Type of Floor | Alum Duct 1.38" Smooth |
| Front And Rear Floor Gutter | Install Front Gutters And Front Drains, Install Rear Gutters And Rear Drains |
| Reefer Rear Threshold / Dockplates | (5) Smooth Aluminum Dock Plates Over Rear Gutter |
| Reefer Floor Inserts | 44" Long Inserts in Center 72" of Floor |
| Miscellaneous Text (TABH) | None |
| Lining / Scuffband | |
| Side Lining | 0.070" PunctureGuard |
| Anti-Microbial Protection - Side | With Microban antimicrobial technology |
| Front Lining | LNG Front Lining - 0.060" GRP (GLASS-REINFORCED-POLYESTER) HIGH GLASS CONTENT LNG100 |
| Anti-Microbial Protection - Front | None |
| Ceiling Lining | LNP Ceiling Lining - 0.060"L GRP (GLASS-REINFORCED-POLYESTER) LNP100 |
| Anti-Microbial Protection - Ceiling | None |
| Rear Door Lining | LNK Rear Door Lining - 0.060" GRP (GLASS-REINFORCED-POLYESTER) HIGH GLASS CONTENT LNK095 |
| Anti-Microbial Protection - Rear Door | None |
| Unit Numbers on Lining | None |
| Rows of Front Scuffband | None |
| Rows of Side Scuffband | 1 Row |



| | |
|--|--|
| Quantity of Rows of Logistic track | 1 Row Horizontal |
| Miscellaneous Text (TABI) | None |
| Scuff/Logistic Track | |
| Type of Side Scuffband (Row One) | 16" High Integral Extruded Aluminum |
| Scuffband Location (Row One) | Installed at Floor Level |
| Side Scuffband Position (Row One) | Recessed on Sidewall |
| Type Of Track And Length | "A" Overlaid on Lining, Full Length, Each Side |
| Track Height (First Row) | 48" Floor to Centerline |
| Miscellaneous Text (TABJ) | None |
| Understructure | |
| Upper Coupler Type | 4.25" Channel |
| Bottom Plate Thickness | 0.25" with Rolled-Lip |
| Landing Gear | GD60, No-Lube, 10yr Vendor Warranty |
| Landing Gear Foot / Shoe Type | 10" X 10" Cushion Foot |
| Landing Gear Bracing | 'K' Bracing |
| Special Landing Gear Wing Plate | Carbon steel mounting plates |
| Landing Gear Handle Location | Roadside |
| Landing Gear Lube System | No Special Lube System |
| Front Tire Protector Plates | None |
| Tire Carrier | None |
| Crossmembers Ahead of Landing Gear | Aluminum Hat Type on 12" Centers |
| Crossmembers Over Landing Gear | 4" Steel I-Beam on 12" Centers |
| Bay Area Crossmembers | 5" Aluminum I-Beam on 12" Centers |
| URG Crossmembers | 4" Steel I-Beam on 12" Centers |
| Extra Crossmembers at Rear | 8" centers Last 4' of Body (1 extra typical) |
| Extra URG Rail Length | None |
| Rear Tire Protector Plates | None |
| Miscellaneous Text (TBHH) | None |
| Aerodynamic Devices | |
| Aerodynamic Fairings - Skirts, Undercarriage | Transtex Edge E-1930T |
| Side Fairing Color | Default White |
| Aerodynamic Fairings - Tails, Rear Frame Top Kits | None |
| Rear Fairing Color | None |
| Miscellaneous Text (TABK) | None |
| Suspension | |
| Model of Suspension | Hendrickson ULTRAAK 40K |
| Axle Type | Hendrickson Tapered Spindle Standard Wall |
| Ready-to-Roll Wheel End | HXL5 Hendrickson Extended-Life 5-Year System |
| Removable Location Stop Bar | None |
| Locking Mechanism | Air-Assist Pin Release |
| Dump Valve | Manual Dump Valve w/Weatherproof Box and Liquid Air Pressure Gauge |
| Pintle Hook | None |



| | |
|--|--|
| Miscellaneous Text (TABL) | None |
| Rear Ramps and Mud Flaps | |
| Mudflaps | Great Dane, Smooth Black with Logo |
| Mudflap Quantity/Bracket Material | 1-Pair |
| Mudflap Mounting Location | On Undercarriage |
| Miscellaneous Text (TABM) | None |
| Brakes, Tire Inflation Systems and Wheel Ends | |
| Brake Size | 16.50" x 7.00" |
| Brake Actuators | WABCO Tristop with IBV 2.5" Stroke |
| Brake Lining | Standard Brake Lining |
| Brake Shoe Type | Extended Service |
| Brake Adjusters | WABCO EASYFIT 5.50" |
| Supplemental Brake Stroke Indicator | None |
| Dust Shield Type | Great Dane Standard |
| Tire-Inflation-System/Tire/Wheel Options | Hendrickson TIREMAAX PRO |
| Tire Inflation System Pressure | 100 PSI |
| Auxiliary Pressure Check Port | Hoses Equipped With Integral Pressure Check Port |
| Wheel Seals | Furnished with RTR Wheel End System |
| Axle Spindle Nuts | Furnished with RTR Wheel End System |
| Hubcaps | Hubcap To Accommodate Tire Inflation System |
| Wheel Lubricant | Semi-Fluid Grease Furnished with RTR Wheel End System |
| Anti-Lock Brakes | Wabco 2S/2M iABS Premium |
| ECU Monitored Option | None |
| Optional Diagnostic Cable | None |
| Brake Valves | Great Dane Standard |
| Air-Tank Drain Valve | Manual |
| Hubodometer YN | None |
| Miscellaneous Text (TABN) | None |
| Tires / Wheels / Hubs and Drums | |
| Rim/Disc Wheel Size | 22.5" X 8.25" |
| Hub/Wheel And Drum | Hendrickson HXL Ductile Iron Hub Piloted 10 Stud Hub With Webb Outboard Cast Drums |
| Brake Drum Balancing | Supplied Balanced Only |
| Wheel Type | 22.5" Aluminum Disc Wheel, Hub Piloted |
| Wheel/Rim Vendor | Great Dane |
| Wheel Stud Options | Long Studs Furnished with HXL Wheel End System |
| Wheel Spacer (Corrosion Barrier) | Spacer between Hub and Disc Wheel |
| Tire Size | 11R 22.5 |
| Tire Brand | Bridgestone Ecopia R123 (G) |
| Spare Tire | None |
| Miscellaneous Text (TABO) | None |
| Electrical | |



| | |
|---|---|
| Exterior Light Package | ALL LIGHTS LED, GROTE LONG LIFE LIGHT SYSTEM, GROTE MICRONOVA DOT LAMPS ELP118 |
| Electrical Connector Type | Great Dane Standard 7-Way Split Pin |
| Telematics Data Bus | CAN Bus Communications with FleetPulse Base |
| Front Top Rail Lights Loc | 1 Top Mounted on Front Corner at 45 Degrees; Roadside and Curbside (Canadian Requirement) |
| Buckplate Light Type | Grote Series 40, LED Flange Mount |
| Buckplate Lights Qty & Loc | 3 Each Side, Stop/Tail/Red Turn |
| Stainless Theft-Resistant Flange for LED Lamps | Installed on Buckplate lamps with Stainless Rivets |
| Rear Header Light Locations | Center Cluster of 3 with 1 Each Side Outboard Corner, Dual Intensity Brake Indication |
| Top and Bottom Side Marker Lamps/ Location | 5 Each Side Top and Bottom Rail Evenly Spaced |
| Midship Turn Signal | Grote LED Combination Turn and Clearance |
| Location of Turn Signal | Roadside and Curbside, Center of Trailer |
| Installation of Turn Signal | Install Below Bottom rail |
| Supplemental Turn Signal | None |
| Type of Supplemental Turn-Signal | None |
| Location of Supplemental Turn Signal | None |
| Installation of Supplemental turn Signal | None |
| Filler Plate Size | None |
| Miscellaneous Text (TABP) | None |
| Electrical Interior | |
| Dome Light Quantity | None |
| Dome Light Vendor/Type | None |
| Dome Light Location Width-wise | None |
| Dome Light Location Length-wise | None |
| Domelight Switch Qty / Type / Loc | None |
| Miscellaneous Text (TABQ) | None |
| Finish/Paint/Decal | |
| Front Finish | Stainless Steel |
| Front Finish, Front Corner Sheet | Stainless Steel |
| Side Finish | Pre-Painted White W/Ultra Road Shield |
| Rivet Color | Unpainted |
| Top Rail Paint | None |
| Bottom Rail Paint | None |
| Rear Frame Finish | None (Stainless Steel) |
| Rear Door Finish | Stainless Steel |
| Undercarriage / Frame Finish | Black Undercoat |
| Wheel Finish | Standard Finish |
| Upper Coupler Finish | Great Dane Standard Coating |
| Landing Gear Finish | Finish to Match Undercarriage |
| Upper Running Gear Finish | Great Dane Standard Coating |



| | |
|--|---|
| Conspicuity Treatment Location | Great Dane on Bottom Rail |
| Manufacturer's Logo Installation | Red Logos |
| Microban Logo Installation | Great Dane Standard |
| Installation Of Customer Decals | None |
| Exterior Unit Numbers | None |
| Miscellaneous Text (TABR) | None |
| Insulation | |
| Front Insulation | 3.50" Urethane |
| Side Insulation | 2.00" Urethane |
| Roof Insulation | 2.50" Urethane |
| Rear Door Insulation | 3.00" Urethane |
| Floor Insulation | 2.00" Urethane |
| Subfloor Type | 0.040" Great Dane GRPP (Glass-Reinforced-Polypropylene) |
| Floor Sills | Composite |
| Miscellaneous Text (TABS) | None |
| Controlled Temperature Unit | |
| Preparation for Nose Mounted Unit | No Unit Installation, Brace and Cut Hatch |
| Type of Nose Mounted Unit | Carrier Vector (Large Opening) |
| Unit Position | Standard |
| Quantity of Ceiling Evaporators | None |
| Miscellaneous Text (TABT) | None |
| Controlled Temperature Accessories | |
| Fuel Tank Capacity | Install Fuel Lines Only for Future Installation of Roadside Fuel Tank, Coil Excess at Each End. Run Fuel Lines up Through a Conduit in the Nose, Exit Front Wall Behind Unit. |
| Fuel Tank Location | Roadside Undermount, Width-Wise |
| Battery | None |
| Refrigeration Remote Indicator Lights | None |
| Refrigeration Unit Duct And Transition | None |
| Remote Control Panel | None |
| Miscellaneous Text (TABV) | None |
| Bulkheads, Air Return | |
| Bulkhead/Air Return | None |
| Factory Furnished Pallet Stops Air Return | None |
| Center Partitions and Preparation | None |
| Miscellaneous Text (TABW) | None |
| Calculated Values | |
| Lock Rod Calculated Length | ESS Reefer Van 4 Hdr Eberhard |
| CARB Compliance Year | 2023 |
| Rear Liftgate | |
| Liftgate Preparation | None |
| Floor | |
| Special Floor Rating | None |



Rear Ramps and Mud Flaps

| | |
|-------------------------|------|
| Walkramp at Rear | None |
|-------------------------|------|

Remote Evaporators

| | |
|--|------|
| First Ceiling Evaporator Protector | None |
| Second Ceiling Evaporator Protector | None |

Calculated Values

| | |
|-------------------------------------|---------------------------------|
| Lock Rod Length (Calculated) | 107.25 |
| Lock Rod Stocking Compliance | This Lock Rod Length is Stocked |

| | | |
|---|--------------|------|
| Rear Door Lining - LNK Rear Door Lining - 0.060" GRP (GLASS-REINFORCED-POLYESTER) HIGH GLASS CONTENT LNK095 | | |
| EENID-1 | BOMID-520479 | CPQ- |
| Brake Adjusters - WABCO EASYFIT 5.50" | | |
| EENID-2 | BOMID-510901 | CPQ- |
| Exterior Light Package - ALL LIGHTS LED, GROTE LONG LIFE LIGHT SYSTEM, GROTE MICRONOVA DOT LAMPS ELP118 | | |
| EENID-3 | BOMID-520480 | CPQ- |
| Front Lining - LNG Front Lining - 0.060" GRP (GLASS-REINFORCED-POLYESTER) HIGH GLASS CONTENT LNG100 | | |
| EENID-4 | BOMID-520477 | CPQ- |
| Ceiling Lining - LNP Ceiling Lining - 0.060"L GRP (GLASS-REINFORCED-POLYESTER) LNP100 | | |
| EENID-5 | BOMID-520478 | CPQ- |