



Order #: 167178

Order Name: All-Steel Step Triaxle - QTY 3 - 09.16.21

Order Revision #: 0

Dealer/Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL

Date: 9/21/2021

Contact: MAXIM TRANSPORTATION SERVICES INC

Requested Date: 1/28/2022

Sales Person: Tom Klassen

Dealer/Branch P.O: 6

Dealers Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL

Customer #: 91870

Dealers Customer #: 91870

Customer P.O: 3132

Itm	Product	Reference #	Name	Model #	Qty
1	FSD - Steel Drop Deck Platform	C-138395	2023 Steel Drop Deck x 3 - 09.15.21	FSD-0026-00053	3

Line Item 1

Configuration Reference #: C-138395

Configuration Name: 2023 Steel Drop Deck x 3 - 09.15.21

FG Item: 232480021

Product: FSD - Steel Drop Deck Platform

Model #: FSD-0026-00053

Mode of Transportation: Customer Pick-Up

Product

Product FSD - Steel Drop Deck Platform
Manufacturing Plant Huntsville, TN
Model Year 2023

Geometric Dimensions

Serial Identification Canadian and U.S. Certification
Overall Length 53' 0"
Overall Width 102.00"
Upper Coupler Height 48"
Kingpin Location 30.00"
Upper Deck Length 132.00" Nose to Face of Drop
Landing Gear Location 88.75" From Kingpin
Undercarriage Design Tridem Axle, Fixed Air-Ride Suspension, 60" Axle Centers
Miscellaneous Text (TABA) None

Front

Front Corner Type Diagonal Platform Trailer Corner



Telematics / Tracking System	None
Telematics System Installation Detail	None
Telematics Data Contract	None
Electrical Connector and Gladhand Location	Near Center Front
Hose Couplers (Gladhands)	Great Dane Control and Supply with Urethane Seals
Document Holder	Tite Seal #158 Located at Landing Gear Crossmember Roadside
Additional Manifest Box	None
Additional Manifest Box Location	None
Stake Pockets Front	Five
Front Stake Pockets Material and Size	0.25 Steel, 7.00" Deep with 4" x 3.88" ID Opening
Miscellaneous Text (TABB)	None
Front Bulkhead	
Bulkhead Type	None
Bulkhead Design	None
Side Kit Modification	None
Tarp Tie Bar	None
Chain Rack	None
Miscellaneous Text (TBAA)	None
Tarp Restraint Front	
Tarp Restraint (Rope Hook) Location, Front	None
Front Rope Hook Type	None
Front Rope Hook Quantity	None
Rope Hook Installation, Front	None
Rope Hook Spacing	None
Miscellaneous Text (TABZ)	None
Side Exterior and Structural	
Side Rail Type	6" Deep 8.2# Structural Channel
Side Stake Pockets	Outside
Stake Pockets Material and Size Side	Steel 0.19" x 1.81" x 3.38" Inside x 3" Deep
Stake Pockets Spacing	24" Centers
Stake Pocket Location	0.38" Below Top of Side Rail
Rub Rail Type	0.25" X 2.00"
Rub Rail Location	Centered on Stake Pocket
Spool Quantity	Single



Miscellaneous Text (TBBB)	None
Rear	
Buckplate Material	Carbon Steel
Rear Stake Pockets	Five
Stake Pocket Material and Size Rear	Steel, .019" X 1.81" Inside X 3.38" Inside X 3" Deep
Filler Plate	Aluminum
Rear Bumpers	Rubber Blocks, 1 Pair at Rear Corners
Rear Impact Guard	Carbon Steel Rear Impact Guard
Tag Bracket Location	None
License Plate Installation	None
Tarp Restraint (Rope Hook) Location, Rear	None
Rear Rope Hook Type	None
Rear Rope Hook Quantity	None
Rear Rope Hook Installation	None
Rear Rope Hook Spacing	None
Miscellaneous Text (TABE)	None
Floor	
Type of Floor	Apitong 1.13"
Floor Cargo Restraint Type	None
Floor Cargo Restraint Quantity	None
Floor Cargo Restraint Location	None
Miscellaneous Text (TABH)	None
Understructure	
Upper Coupler Type	Unitized
Bottom Plate Thickness	0.38"
Landing Gear	GD65
Landing Gear Foot / Shoe Type	10" X 10" Cushion Foot
Landing Gear Handle Location	Roadside
Loaded Rear Deck Height	40"
Tire Carrier	None
Mainbeam Flanges	0.50" x 5.00" Top; 0.63 x 5.00" Bottom
Bay Area Crossmembers	4" Steel I-Beam on 16" Centers
Extra Crossmembers	None
Tool Box Quantity	None
Dunnage Rack	None
Dunnage Rack Location	None
Miscellaneous Text (TBHH)	None



Side Winch and Tarp Restraint

Quantity of Fixed Winches Mounted between Crossmembers	None
Quantity of Fixed Undermount Winches In Bay-Area	None
Quantity of Sliding Winches	None
Miscellaneous Text (TBCC)	INSTALL (22) LOW-PROFILE WINCHES WELDED TO BODY BORDER UNDER RUB-RAIL POINTING OUTWARD. EQUALLY SPACE AND STAGGER WINCHES STARTING 2FT FROM NOSE AND APPROX EVERY 2FT. ENSURE THAT SPLINE LOCKS FALL FROM THE TOP AND WINCHES AND "C" HOOK LOCATIONS DO NOT INTERFERE WITH PIPE SPOOLS. MAINTAIN ADEQUATE CLEARANCE BETWEEN SPOOLS, STAKE POCKETS AND WINCHES. (TOTAL OF 5 WINCHES AND HOOKS ON FRONT DECK & 17 WINCHES AND HOOKS ON THE REAR DECK)

Suspension

Model of Suspension	Hendrickson AANL 23K
Axle Type	Hendrickson Tapered Spindle Standard Wall
Ready-to-Roll Wheel End	None
Bogie Location	120" Fixed Bogie Location Ensure Setting is RTAC Compliant.
Dump Valve	Manual Dump Valve w/Weatherproof Box and Liquid Air Pressure Gauge
Auxillary Dump Valve	None
Auxillary Dump Valve Location	None
Miscellaneous Text (TABL)	None

Rear Ramps and Mud Flaps

Mudflaps	Great Dane, Ribbed Black with Logo
Mudflap Mounting Location	Behind Rear Axle
Miscellaneous Text (TABM)	None

Brakes, Tire Inflation Systems and Wheel Ends

Brake Size	16.50" x 7.00"
Brake Actuators	Great Dane Standard 2.5" Stroke
Brake Lining	Standard Brake Lining
Brake Shoe Type	Extended Service
Brake Adjusters	Meritor Automatic 5.50"
Supplemental Brake Stroke Indicator	None
Dust Shield Type	Great Dane Standard
Tire-Inflation-System/Tire/Wheel Options	Prep axle(s) for future installation of tire inflation system (3 Holes)
Tire Inflation System Pressure	None
Auxiliary Pressure Check Port	None
Wheel Seals	Platinum-Plus Performance Package
Axle Spindle Nuts	Zip-Torq Spindle Nut



Hubcaps	Aluminum Sentinel
Wheel Lubricant	Oil
Anti-Lock Brakes	Wabco 2S/1M Easy Stop
Optional Diagnostic Cable	None
Brake Valves	Sealco
Air-Tank Drain Valve	Manual
Hubodometer YN	None
Miscellaneous Text (TABN)	None
Tires / Wheels / Hubs and Drums	
Rim/Disc Wheel Size	22.5" X 8.25"
Hub/Wheel And Drum	Great Dane Hub Piloted Universal 10 Stud Hub with Outboard Cast Drums
Brake Drum Balancing	None-Not Balanced
Wheel Type	22.5" Steel Disc Wheel, Hub Piloted, 5HH
Wheel/Rim Vendor	Great Dane
Wheel Stud Options	Long Studs for Future Alum Wheels
Wheel Spacer (Corrosion Barrier)	None
Tire Size	255/70R 22.5
Tire Brand	Bridgestone R250ED (H)
Miscellaneous Text (TABO)	None
Electrical	
Exterior Light Package	All Lights LED, Grote Long Life Light System, Grote MicroNova Dot Lamps
Type of Clearance Lights	Grote, LED MicroNova Dot Lamps with Dual Intensity ID Lamps
Electrical Connector Type	Great Dane Standard 7-Way Split Pin
Side Bottom Lights	3 Each Side (Front, Rear, and standard Midship Combination)
Side Bottom Light Locations	Evenly spaced Front to Rear
Buckplate Light Type	Grote Series 40, LED Flange Mount
Buckplate Lights Qty & Loc	2 Each Side
Midship Turn Signal	Grote LED Combination Turn and Clearance
Location of Turn Signal	Roadside and Curbside,Center of Trailer
Installation of Turn Signal	Attach To Bottom Of Crossmember
Supplemental Turn Signal	None
Type of Supplemental Turn-Signal	None
Location of Supplemental Turn Signal	None
Installation of Supplemental turn Signal	None
Miscellaneous Text (TABP)	F&I 4-Way Plug Wired to the Clearance Light Circuit and Installed in the Buckplate
Miscellaneous Text (TBDD)	None
Finish/Paint/Decal	



Paint	Black, Urethane
Wheel Finish	White Powder Coat
Conspicuity Treatment Location	Great Dane on Siderails
Manufacturer's Logo Installation	Red Logos
Installation Of Customer Decals	None
Exterior Unit Numbers	None
Miscellaneous Text (TABR)	None
Miscellaneous Text (TBFF)	None
Miscellaneous Text (TBGG)	None

Geometric Dimensions

CARB/GHG Phase 2	None
-------------------------	------

Calculated Values

CARB Compliance Year	2022
-----------------------------	------

Geometric Dimensions

Packaged Options	None
-------------------------	------

GHG2 Green House Gas Compliance

GHG2 Green House Gas Classification	Excluded
--	----------

Floor

Special Floor Rating	None
-----------------------------	------

Tool Boxes

Type of Tool Box	None
Tool Box Mounting Location	None
Tool Box Door Hinge Location	None

Suspension

Locking Mechanism	None
Pintle Hook	None

Rear Ramps and Mud Flaps

Mudflap Quantity/Bracket Material	1-Pair
--	--------

Tires / Wheels / Hubs and Drums

Spare Tire	None
-------------------	------

Miscellaneous Text (TABP) - F&I 4-Way Plug Wired to the Clearance Light Circuit and Installed in the Buckplate		
EENID-138395-2	BOMID-442089	CPQ-
Bogie Location - 120" Fixed Bogie Location Ensure Setting is RTAC Compliant.		
EENID-138395-1	BOMID-442090	CPQ-



Miscellaneous Text (TBCC) - INSTALL (22) LOW-PROFILE WINCHES WELDED TO BODY BORDER UNDER RUB-RAIL POINTING OUTWARD. EQUALLY SPACE AND STAGGER WINCHES STARTING 2FT FROM NOSE AND APPROX EVERY 2FT. ENSURE THAT SPLINE LOCKS FALL FROM THE TOP AND WINCHES AND "C" HOOK LOCATIONS DO NOT INTERFERE WITH PIPE SPOOLS. MAINTAIN ADEQUATE CLEARANCE BETWEEN SPOOLS, STAKE POCKETS AND WINCHES. (TOTAL OF 5 WINCHES AND HOOKS ON FRONT DECK & 17 WINCHES AND HOOKS ON THE REAR DECK)

EENID-138395-4

BOMID-442091

CPQ-
