Booking #: 678591 **Booking Name:** 9x Stock Tridem Steel Flat Deck May 2026 **Booking Revision #:** 5

Dealer/Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL
Contact: MAXIM TRANSPORTATION SERVICES INC
Sales Person: Chris Kowaliszyn
Dealers Customer: MAXIM TRANSPORTATION (WINNIPEG,MB)TRL
Dealers Customer #: 91870

Expiration Date: 7/12/2026
Date: 6/12/2026
Requested Date Earliest: 05/15/2026
Requested Date: 10/30/2026
Dealer/Branch P.O:
Customer #: 91870
Customer P.O:

Itm	Product	Reference #	Name	Model #	Qty
1	FSP - Steel Platform	C-227179	6x Stock Tridem Steel Flat Deck May 2026	FSP-0026-00053	9

Line Item 1
Configuration Reference #: C-227179
Configuration Name: 6x Stock Tridem Steel Flat Deck May 2026
FG Item: 27248xxxx
Product: FSP - Steel Platform
Model #: FSP-0026-00053
Mode of Transportation: Customer Pick-Up

Product

Product	FSP - Steel Platform
Manufacturing Plant	Huntsville, TN
Model Year	2027

Geometric Dimensions

CARB/CA Phase 2 GHG	CARB/GHG2 compliance not required.
Serial Identification	Canadian and U.S. Certification
Overall Length	53' 0"
Overall Width	102.00"
Upper Coupler Height	48"
Kingpin Location	24.00"
Landing Gear Location	106.0" From Kingpin
Undercarriage Design	Tridem Axle, Slide Air-Ride Suspension, 60" Axle Centers
Miscellaneous Text (TABA)	None

Front

Front Crossmember	Steel Front Crossmember
Front Corner Type	Diagonal Platform Trailer Corner

Electrical Connector and Gladhand Location	Near Center Front
Hose Couplers (Gladhands)	Great Dane Control and Supply with Urethane Seals
Document Holder	Tite Seal #158 Located at Landing Gear Crossmember Roadside
Additional Manifest Box	None
Additional Manifest Box Location	None
Stake Pockets Front	Five
Front Stake Pockets Material and Size	0.25 Steel, 7.00" Deep with 4" x 3.88" ID Opening
Miscellaneous Text (TABB)	None

Telematics

Telematics / Tracking System	FleetPulseGo Track
Alternative Telematics System	. . .
Telematics System Install and Commission	Factory Furnished and Factory Commissioned
Telematics System Installation Detail	Great Dane Standard Location
Telematics / Tracking Power Supply	. . .

Front Bulkhead

Bulkhead Type	None
Bulkhead Design	None
Side Kit Modification	None
Tarp Tie Bar	None
Chain Rack	None
Miscellaneous Text (TBAA)	None

Tarp Restraint Front

Tarp Restraint (Rope Hook) Location, Front	None
Front Rope Hook Type	None
Front Rope Hook Quantity	None
Rope Hook Installation, Front	None
Rope Hook Spacing	None
Miscellaneous Text (TABZ)	None

Side Exterior and Structural

Side Rail Type	6" Deep 8.2# Structural Channel
Side Stake Pockets	Outside
Stake Pockets Material and Size Side	Steel 0.19" x 1.81" x 3.38" Inside x 3" Deep
Stake Pockets Spacing	24" Centers
Stake Pocket Location	0.38" Below Top of Side Rail
Rub Rail Type	0.25" X 2.00"
Rub Rail Location	Centered on Stake Pocket
Spool Quantity	Single
Miscellaneous Text (TBBB)	None

Rear

Buckplate Material	Carbon Steel
Rear Stake Pockets	Five

Stake Pocket Material and Size Rear	Steel, .019" X 1.81" Inside X 3.38" Inside X 3" Deep
Filler Plate	Aluminum
Rear Bumpers	Rubber Blocks, 1 Pair at Rear Corners
Rear Impact Guard	Carbon Steel Rear Impact Guard
Tag Bracket Location	Centered on Filler Plate
License Plate Installation	None
Tarp Restraint (Rope Hook) Location, Rear	None
Rear Rope Hook Type	None
Rear Rope Hook Quantity	None
Rear Rope Hook Installation	None
Rear Rope Hook Spacing	None
Fork Lift Package	None
Counter Weight	None
Miscellaneous Text (TABE)	None

Floor

Type of Floor	Apitong 1.13"
Floor Cargo Restraint Type	None
Floor Cargo Restraint Quantity	None
Floor Cargo Restraint Location	None
Twist Lock / Container Lock	None
Miscellaneous Text (TABH)	None

Understructure

Upper Coupler Type	Unitized
Bottom Plate Thickness	0.38"
Landing Gear	GD65
Landing Gear Foot / Shoe Type	10" X 10" Cushion Foot
Landing Gear Handle Location	Roadside
Tire Carrier	None
Mainbeam Flanges	0.50" x 5.00" Top; 0.63 x 5.00" Bottom
Curtainside Preparation	None
Bay Area Crossmembers	4" Steel I-Beam on 16" Centers
Extra Crossmembers	None
Tool Box Quantity	One
Dunnage Rack	Aluminum Undermount Dunnage Rack 108"
Dunnage Rack Location	Roadside Bay
Miscellaneous Text (TBHH)	None

Tool Boxes

Type of Tool Box	Aluminum, 24" Wide x 24" High x 48" Long, Double Door (CamLock Style Closure)
Tool Box Mounting Location	Roadside Behind Landing Gear
Tool Box Door Hinge Location	Hinged at Sides

Side Winch and Tarp Restraint

Quantity of Fixed Winches Mounted between Crossmembers	None

Quantity of Fixed Undermount Winches In Bay-Area	None
Quantity of Sliding Winches	None
Miscellaneous Text (TBCC)	INSTALL (25) LOW-PROFILE WINCHES WELDED TO BODY BORDER UNDER RUB-RAIL POINTING OUTWARD. EQUALLY SPACE AND STAGGER WINCHES STARTING 2FT FROM NOSE AND APPROX EVERY 2FT. ENSURE THAT SPLINE LOCKS FALL FROM THE TOP AND WINCHES AND "C" HOOK LOCATIONS DO NOT INTERFERE WITH PIPE SPOOLS. MAINTAIN ADEQUATE CLEARANCE BETWEEN SPOOLS, STAKE POCKETS AND WINCHES.

Suspension

Model of Suspension	Hendrickson AAZNT Platform Slider
Axle Type	Hendrickson Tapered Spindle Standard Wall
Zero Maintenance Damping	None
Integrated Wheel End Package	RTR HXL5 Hendrickson Extended-Life 5-Year System
Bogie Location	48" Slide Travel (Minimum)
Locking Mechanism	Air-Assist Pin Release
Dump Valve	Manual Dump Valve w/Weatherproof Box and Liquid Air Pressure Gauge
Auxillary Dump Valve	None
Auxillary Dump Valve Location	None
Pintle Hook	None
Miscellaneous Text (TABL)	None

Rear Ramps and Mud Flaps

Mudflaps	Great Dane, Ribbed Black with Logo
Mudflap Mounting Location	Behind Rear Axle
Miscellaneous Text (TABM)	None

Brakes, Tire Inflation Systems and Wheel Ends

Brake Size	16.50" x 7.00"
Brake Actuators	Great Dane Standard 2.5" Stroke
Brake Lining	Standard Brake Lining
Brake Shoe Type	Extended Service
Brake Adjusters	Meritor Automatic 5.50"
Supplemental Brake Stroke Indicator	None
Dust Shield Type	Great Dane Standard
Tire-Inflation-System/Tire/Wheel Options	None
Tire Inflation System Pressure	None
Auxiliary Pressure Check Port	None
Wheel Seals	Furnished with Integrated Wheel End System
Axle Spindle Nuts	Furnished with Integrated Wheel End System
Hubcaps	Furnished with Integrated Wheel End System
Wheel Lubricant	Semi-Fluid Grease Furnished with Integrated Wheel End System
Anti-Lock Brakes	Wabco 2S/2M iABS Premium
ECU Monitored Option	None
Brake Valves	Sealco 110500 Spring Brake Priority

Air-Tank Drain Valve	Manual
Hubodometer YN	None
Miscellaneous Text (TABN)	None

Tires / Wheels / Hubs and Drums

Rim/Disc Wheel Size	24.5" X 8.25"
Hub/Wheel And Drum	Hendrickson HXL Ductile Iron Hub Piloted 10 Stud Hub With Webb Outboard Cast Drums
Brake Drum Balancing	Supplied Balanced Only
Wheel Type	24.5" Steel Disc Wheel, Hub Piloted, 5HH
Wheel/Rim Vendor	Great Dane
Wheel Stud Options	Long Studs Furnished with HXL Wheel End System
Wheel Spacer (Corrosion Barrier)	None
Tire Size	11R 24.5
Tire Brand	Bridgestone R196A (G)
Miscellaneous Text (TABO)	None

Electrical

Exterior Light Package	All Lights LED, Grote Long Life Light System, AMP Connector, Grote MicroNova Dot Lamps
Type of Clearance Lights	Grote, LED MicroNova Dot Lamps with Dual Intensity ID Lamps
Electrical Connector Type	Great Dane Standard 7-Way Split Pin
Side Bottom Lights	3 Each Side (Front, Rear, and standard Midship Combination)
Side Bottom Light Locations	Evenly spaced Front to Rear
Buckplate Light Type	Grote Series 40, LED Flange Mount
Buckplate Lights Qty & Loc	3 Each Side, Stop/Tail/Red Turn
Midship Turn Signal	Grote LED Combination Turn and Clearance
Location of Turn Signal	Roadside and Curbside,Center of Trailer
Installation of Turn Signal	Attach To Bottom Of Crossmember
Supplemental Turn Signal	None
Type of Supplemental Turn-Signal	None
Location of Supplemental Turn Signal	None
Installation of Supplemental turn Signal	None
Miscellaneous Text (TABP)	Install 4-Way Plug at Rear of Trailer
Miscellaneous Text (TBDD)	None

Finish/Paint/Decal

Paint	Black, Urethane
Wheel Finish	White Powder Coat
Conspicuity Treatment Location	Great Dane on Siderails
Manufacturer's Logo Installation	Red Logos
Installation Of Customer Decals	None
Exterior Unit Numbers	None
Miscellaneous Text (TABR)	None
Miscellaneous Text (TBFF)	None
Miscellaneous Text (TBGG)	None

Calculated Values

Production Line	Production Line To Be Determined
CARB Compliance Year	2026

Geometric Dimensions

Packaged Options	None
Drop Depth	None

Calculated Values

Side Door Y/N	No

Floor

Special Floor Rating	None

Suspension

Brake Type	010_drum

Rear Ramps and Mud Flaps

Mudflap Quantity/Bracket Material	1-Pair

Tires / Wheels / Hubs and Drums

Spare Tire	None

Miscellaneous Text (TABP) - Install 4-Way Plug at Rear of Trailer		
EENID-1	BOMID-828754	CPQ-
Miscellaneous Text (TBCC) - INSTALL (25) LOW-PROFILE WINCHES WELDED TO BODY BORDER UNDER RUB-RAIL POINTING OUTWARD. EQUALLY SPACE AND STAGGER WINCHES STARTING 2FT FROM NOSE AND APPROX EVERY 2FT. ENSURE THAT SPLINE LOCKS FALL FROM THE TOP AND WINCHES AND "C" HOOK LOCATIONS DO NOT INTERFERE WITH PIPE SPOOLS. MAINTAIN ADEQUATE CLEARANCE BETWEEN SPOOLS, STAKE POCKETS AND WINCHES.		
EENID-2	BOMID-828755	CPQ-

Pricing and lead times are provided as estimates and are subject to change based on final chassis specifications including make, model, configuration, and availability. Complete chassis details must be provided at the time of order. Final pricing, delivery schedules, and product compatibility will be confirmed upon review of the full chassis specification. Any change to chassis information may impact our ability to build the requested solution and could result in adjustments to cost and lead time.